

## Gear oils

### AUTOL ATF - III D

**Automatic Transmission Fluid** for vehicle automatic transmissions, converter transmissions and power steerings according to the manufacturer's specification.

Viscosity	at 40°C	mm <sup>2</sup> /s	35,8
	at 100°C	mm <sup>2</sup> /s	7,5
Viscosity index			195
Density at 15°C		kg/m <sup>3</sup>	863
Flash point o. C.		°C	200
Pourpoint		°C	-42

**AUTOL ATF - III D** is a power transmission oil that meets the requirements of the Dexron III specification of General Motors. The GM number F 30114 identifies the quality proof.

Aside from these requirements also properties such as a good viscosity temperature behaviour, observation of the requested friction values, no foam formation, neutral behaviour against plastics and a distinct wear protection are very important for the formulation.

Enhanced conditions concerning the corrosion protection and the oxidation resistance have to be met as well as the demands for longer oil-change intervals.

#### Applications:

**AUTOL ATF - III D** is suitable for the application in automatic transmissions, torque converters, fluid couplings and power shift gears, also for Ford passenger cars starting year of construction 1991. It also can be used wherever oils according to the specification DEXRON B or C are prescribed.

Please observe the manufacturer's specifications when selecting products.

**AUTOL ATF III D** can be used where the following specifications are required:

GM DEXRON III, Ford MERCON, Voith H55.6335xx (G 607), ZF TE-ML 02F,03D,04D,11B, 14A,17C, MAN 339 Type V-1, Typ Z-1, MB 236.1, 236.5, 236.9, 236.10, 236.11, 236.12, Allison C-4, BMW BG 24, Volvo 97341-12, Ford WSS-M2C 195A, VW G 052 162