



## APPLICATIONS

**Eni Blasia 32** is a lubricant with EP characteristics for gears and hydraulic systems severely loaded.

**Eni Blasia 32** has been specifically formulated for joints, hydrodynamic converters and relative gear trains (Voith hydrodynamic turbo-transmissions, feed pumps in thermoelectric power stations, etc.).

## CUSTOMER ADVANTAGES

- Protection of lubricated components during operation thanks to a robust antiwear additive system
- Non-corrosive behaviour against gaskets and seals as well as metals such as steel, cast iron, copper and bronze
- Quick separation from water that could accidentally enter the system thanks to an outstanding demulsive capacity
- Protection from rust, even in presence of humid environment
- Regular and efficient lubrication thanks to antifoam and air-release properties

## SPECIFICATIONS - APPROVALS

- ISO 12925-1 CKD
- DIN 51517-3 CLP
- Voith Turbo
- ANSI/AGMA 9005-E02
- Deckel





## CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	APM 27	-	clear
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	874
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	32.0
Viscosity Index	ASTM D 2270	-	110
Flash point COC	ASTM D 92	°C	216
Pour point	ASTM D 5950	°C	-30
Demulsibility at 54°C	ASTM D 1401	mins	15
Copper corrosion	ASTM D 130	-	1

