



eni i-Sigma performance E4 10W-40

eni i-Sigma performance E4 10W-40 is a top performance multigrade oil with synthetic technology suitable for Heavy Duty Diesel engines operating under severe duty. It permits long oil-drain intervals and fuel economy.

Characteristics (typical figures):

| eni i-Sigma performance E4 | Unit | 10W-40 |
|----------------------------|--------------------|--------|
| Density at 15°C | kg/m ³ | 875 |
| Viscosity at 100°C | mm ² /s | 14.3 |
| Viscosity at -25 °C | mPa·s | 6850 |
| Viscosity Index | - | 150 |
| Flash Point COC | °C | 230 |
| Pour Point | °C | -30 |

Properties and performance:

- **eni i-Sigma performance E4 10W-40** showed outstanding results when submitted to the engine tests included in the relevant performance specifications. All the metal parts of the engine are protected from deposit build-up and wear is reduced, ensuring maximum engine efficiency throughout its life.
- The fuel saving properties allow a reduction in fuel consumption compared to traditional Diesel lubricants.
- The SAE 10W-40 grade allows the usage under a wide range of ambient temperature. The product stays fluid and facilitates the engine start-up at low ambient temperatures while keeping its high viscosity at high temperatures.

Specifications:

eni i-Sigma performance E4 10W-40 is officially approved or meets the requirements* of the following service specifications:

- ACEA E4
- ACEA E7
- MB Approval 228.3
- MAN M 3277*
- MAN M 3377
- MTU Type 3