



## Eni i-Sint 5W-30

**Eni i-Sint 5W-30** is a top synthetic technology engine oil with mid SAPS characteristics, for modern passenger cars and light vans gasoline or diesel engines with or without particulate filters (DPF) also at prolonged oil-change intervals according to the manufacturer's recommendations.

### Characteristics (typical figures):

Eni i-Sint 5W-30	Unit	5W-30	Test method
Kin. Viscosity	at 40°C	70	DIN 51 562
	at 100°C	12	
	at -30°C	6100	
Viscosity index		161	DIN ISO 2909
Density at 15°C	kg/m <sup>3</sup>	852	DIN 51 757
Flashpoint o. C.	°C	210	DIN ISO 2592
Pourpoint	°C	-42	DIN ISO 3016

### Properties and Performance:

**Eni i-Sint 5W-30** offers the following performances:

- Excellent wear protection and deposits formation
- Optimum cold start properties
- Outstanding fuel economy and reduction of CO<sub>2</sub> emissions
- Low oil consumption
- High compatibility with after-treatment devices for exhaust emissions meeting the requirements fixed by some important car manufacturers

### International specifications:

- ACEA C3
- API SN

### Approvals:

- MB approval 229.51
- VW 504 00, 507 00
- BMW LL-04
- Porsche C30