

Gear oils

AUTOL SUPERGEAR FE

SAE 75W-80
API GL-4/ GL-5

Synthetic gear oil with lowered cold viscosity for the optimization of the efficiency of modern manual transmissions.

Characteristics (typical figures):

Kin. Viscosity	at 40°C	mm ² /s	50,5
	at 100°C	mm ² /s	9,2
Viscosity index			166
Density at 15°C		kg/l	0,854
Flashpoint o. C.		°C	180
Pourpoint		°C	-44

AUTOL SUPERGEAR FE is a high-performance gear oil for manual transmissions which contributes to the reduction of fuel consumption due to the lowered Viscosity and the excellent Viscosity-temperature-behaviour.

Due to the application of fully synthetic base oils it guarantees a high temperature and oxidation stability, a heavy duty lubrication film for the reduction of friction and wear as well as “stay-in-grade” properties due to the shear stable components.

Due to the reduction of the base oil viscosity a comfortable shifting behaviour is achieved also at lowest temperatures and the efficiency is increased.

Applications:

AUTOL SUPERGEAR FE can be used wherever the following specifications are required: BMW MTF LT-1/ LT-2/ LT-3/ LT-4, Ford WSS-M2C 200D, MB 235.10, PSA 9730 A2/ A8, PSA B71 2330, Fiat 9.55550-MZ2, Toyota JWS 227, VW 052 171/ 052 178/ 052 512/ 052 527/ 052 532/ 0520726/ 052 798/ 055 726.

Please observe the manufacturer’s specifications when selecting products.