

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Revision date: 11/18/2022 Supersedes: 8/8/2018 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : Eni Rotra ATF VI

Product code : 1318

Type of product : Lubricants

Formula : 0048-2012

Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use

Industrial/Professional use spec : Used in closed systems

Wide dispersive use

Use of the substance/mixture : Gearbox lubricant

Do not use the product for any purposes that have not been advised by the manufacturer.

Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Eni S.p.A., P.le E. Mattei 1, 00144 Rom, ITALY, Tel. +39 06 59821, www.eni.com Competent person responsible for the safety data sheet (Reg. EC nr. 1907/2006): SDSInfo@eni.com

Distributed by: Eni Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY, www.enischmiertechnik.de Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0 e-mail: technik.wuerzburg@eni.com

1.4. Emergency telephone number

Emergency number : CNIT +39 0382 24444 (24h) (IT + EN)

Poison centre (UK):

National Poisons Information Service Edinburgh (24h)

(+44) 844 892 0111 0870 600 6266 (UK only) (Source: UN-WHO)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Contact with eyes may cause temporary reddening and irritation. Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, due to a defatting effect. May produce an allergic reaction. Harmful to aquatic life with long lasting effects. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

CLP Signal word

Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P273 - Avoid release to the environment.

P501 - Dispose of contents/container to according to national or local regulations.

EUH-statements : EUH208 - Contains Reaction products of amines, dicoco alkyl and glycollic acid, 1,2-

Propanediol, 3-amino-, N,N dicocoalkyl derivatives, 2-tetradecyloxirane, reaction products

with boric acid. May produce an allergic reaction.

2.3. Other hazards (not relevant for classification)

Other hazards not contributing to the classification

: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment. Do not wait for symptoms to develop. A potential risk may arise from the release of hydrogen sulfide, when the product is stored or handled at high temperature. Hydrogen sulfide may accumulate in the tanks or other confined spaces, with danger to the workers that enter the spaces. In these cases overexposure to hydrogen sulfide may cause irritation to airways, nausea, dizziness, loss of consciousness and death.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Mineral base oil, severely refined (N/A)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
1-Decene, Dimer, Hydrogenated (68649-11-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component		
Mineral base oil, severely refined(N/A)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	
1-Decene, Dimer, Hydrogenated(68649-11-6)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	
Distillates (petroleum), hydrotreated light paraffinic(64742-55-8)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Notes

: Composition/ Information on ingredients:

Mixture of hydrocarbons

Additives

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (Main component, see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889- 13	80 - 90	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889- 13	30 – 35	Not classified
Mineral base oil, severely refined (For identification of the substance, see note [*]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: N/A EC-No.: N/A	1 - 5	Asp. Tox. 1, H304
1-Decene, Dimer, Hydrogenated (Additive)	CAS-No.: 68649-11-6 EC-No.: 500-228-5 REACH-no: 01-2119493069- 28	1 - 2	Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.50000 mg/l/4h) Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic (Component, see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077-	1 - 2	Asp. Tox. 1, H304
Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich (Additive)	CAS-No.: 398141-87-2 EC-No.: 800-172-4 EC Index-No.: N/A REACH-no: 01-2119969520- 35	1 - 2	Aquatic Chronic 2, H411
Reaction products of amines, dicoco alkyl and glycollic acid (Additive)	EC-No.: 471-920-1 REACH-no: 01-0000019770- 68	0,5 - 1,5	Skin Sens. 1, H317
1-(tert-dodecylthio)propan-2-ol (Additive)	CAS-No.: 67124-09-8 EC-No.: 266-582-5 EC Index-No.: N/A REACH-no: 01-2119953277- 30	0,1 - 0,9	Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
1,2-Propanediol, 3-amino-, N,N dicocoalkyl derivatives (Additive)	EC-No.: 482-000-4 REACH-no: 01-0000020142- 86	0,1 - 0,9	Skin Sens. 1, H317 Aquatic Chronic 3, H412 (M=1)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol (Additive)	CAS-No.: 1218787-32-6 EC-No.: 620-540-6 REACH-no: 01-2119510877- 33	0,1 - 0,15	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)
Calcium sulphonate	CAS-No.: N/D EC-No.: Polymer EC Index-No.: N/A REACH-no: N/A	0.015 – 0.154	Skin Sens. 1, H317
2-tetradecyloxirane, reaction products with boric acid	EC-No.: 701-392-2 REACH-no: 01-2119976364- 28	0.015 – 0.154	Skin Sens. 1B, H317
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	CAS-No.: 95-38-5 EC-No.: 202-414-9 REACH-no: 01-2119777867- 13	0.015 - 0.039	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1C, H314 Eye Dam. 1, H318 STOT RE 2, H373 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
Reaction products of amines, dicoco alkyl and glycollic acid (Additive)	EC-No.: 471-920-1 REACH-no: 01-0000019770- 68	(9.4 ≤C < 100) Skin Sens. 1, H317
1-(tert-dodecylthio)propan-2-ol (Additive)	CAS-No.: 67124-09-8 EC-No.: 266-582-5 EC Index-No.: N/A REACH-no: 01-2119953277-	(14.2 ≤C < 100) Skin Sens. 1, H317
Calcium sulphonate	CAS-No.: N/D EC-No.: Polymer EC Index-No.: N/A REACH-no: N/A	(10 ≤C < 100) Skin Sens. 1, H317

Notes

: [*] Note: this product may be formulated with one or more of the following severely refined mineral base oils (not classified as hazardous):

CAS 64742-54-7/EC 265-157-1/REACH Reg. # 01-2119484627-25-xxxx; CAS 64742-65-0/EC 265-169-7/REACH Reg. # 01-2119471299-27-xxxx; CAS 64742-70-7/EC 265-174-4/REACH Reg. # 01-2119487080-42-xxxx; CAS 64742-56-9/EC 2265-159-2/ REACH Reg. # 01-2119480132-48-xxxx.

All these substances have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)

Note [**]:

this product has a value of DMSO extract < 3% wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

Full text of H- and EUH-statements: see section 16

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove to fresh air, keep the casualty warm and at rest. If breathing is difficult, give oxygen if possible, or assisted ventilation. If necessary, give external cardiac massage and obtain

medical advice. See also section 4.3.

First-aid measures after skin contact : Remove contaminated clothing and shoes. Wash skin with soap and water. If skin irritation

occurs: Get medical advice/attention. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an

hospital. Do not use salves or ointments, unless directed by doctor. First-aid measures after eye contact

: Remove contact lenses, if present and easy to do so. Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation persists, seek medical advice. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless

directed by doctor.

Rinse mouth thoroughly with water. Give water to drink if victim completely conscious/alert. First-aid measures after ingestion

Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Inhalation of fumes or oil mists produced at high temperatures may cause irritation of the respiratory tract. Symptoms of overexposure to vapours include drowsiness, weakness,

headache, dizziness, nausea, vomiting, dimming of vision.

Symptoms/effects after skin contact : Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, due to a defatting effect. May cause an allergic skin reaction. Contact with hot product may cause

thermal burns.

Symptoms/effects after eye contact : Contact with eyes may cause temporary reddening and irritation. Contact with hot product

or vapours may cause burns. : Accidental ingestion of small quantities of the product may cause nausea, discomfort and

gastric disturbances.

Symptoms/effects upon intravenous administration No information available

Chronic symptoms : None to be reported, according to the present classification criteria.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Symptoms/effects after ingestion

Suitable extinguishing media : Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other

extinguishing gases (according to regulations).

Unsuitable extinguishing media Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use

of foam and water on the same surface is to be avoided as water destroys the foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard : This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.

Explosion hazard : In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m3 of air. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous decomposition products in case of fire : Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, NOx, H2S and SOx (harmful/toxic gases).

Oxygenated compounds (aldehydes, etc.). POx. CaOx. BOx.

11/18/2022 (Revision date) FU - en 5/27

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

5.3. Advice for firefighters

Firefighting instructions

: Shut off source of product, if possible. If possible, move containers and drums away from danger area. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.

Special protective equipment for firefighters

: Personal protection equipment for firefighters (see also sect. 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN 443. EN 469. EN 659.

Other information

: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid accidental sprays on hot surfaces or electrical contacts. Avoid direct contact with released material. Keep upwind.

6.1.1. For non-emergency personnel

Protective equipment Emergency procedures : See Section 8.

: Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

6.1.2. For emergency responders

Protective equipment

: Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work helmet. Antistatic non-skid safety shoes or boots. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with combined dust/organic vapour filter(s), or a Self-Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

Emergency procedures

: Notify local authorities according to relevant regulations.

6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

6.3. Methods and material for containment and cleaning up

For containment

: Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.

Methods for cleaning up

: Transfer recovered product and other materials to suitable tanks or containers and store/dispose according to relevant regulations.

Other information

: Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

11/18/2022 (Revision date) EU - en 6/27

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Ensure that proper housekeeping measures are in place. Keep away from heat/sparks/open flames/hot surfaces. Use and store only outdoors or in a well-ventilated area. Ensure good ventilation of the work station. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. The product may release Hydrogen Sulphide: a specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.

Handling temperature Hygiene measures : This product can be handled at ambient temperatures.

: Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in dry, well ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.

Incompatible products

: Strong oxidizing agents.

regulations.

Storage area

: Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company

Packages and containers:

If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.

Packaging materials

: For containers, or container linings use materials specifically approved for use with this product. Compatibility should be checked with the manufacturer.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Safety Data Sheet

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)		
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KTV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	eated neutral oil-based	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KTV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Safety Data Sheet

Mineral base oil, severely refined (N/A)			
Austria - Occupational Exposure Limits			
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Belgium - Occupational Exposure Limits			
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Denmark - Occupational Exposure Limits			
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Hungary - Occupational Exposure Limits			
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Netherlands - Occupational Exposure Limits			
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Sweden - Occupational Exposure Limits			
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
KTV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Distillates (petroleum), hydrotreated light par	affinic (64742-55-8)		
Austria - Occupational Exposure Limits			
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Belgium - Occupational Exposure Limits			
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Denmark - Occupational Exposure Limits			
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Hungary - Occupational Exposure Limits			
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Netherlands - Occupational Exposure Limits	Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Sweden - Occupational Exposure Limits			
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
KTV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

8.1.4. DNEL and PNEC		
Eni Rotra ATF VI		
DNEL/DMEL (additional information)		
Additional information	Not applicable	
PNEC (additional information)		
Additional information	Not applicable	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2.73 mg/m³	
Long-term - local effects, inhalation	5.58 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day	
Long-term - local effects, inhalation	1.19 mg/m³	
PNEC (additional information)		
Additional information	Not applicable (UVCB)	
Mineral base oil, severely refined (N/A)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, inhalation	= 5.4 mg/m³/day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
DNEL/DMEL (General population)		
Long-term - local effects, inhalation	= 1.2 mg/m³/day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
1-Decene, Dimer, Hydrogenated (68649-11-6)		
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	60 mg/m³	
Acute - local effects, inhalation	60 mg/m³ (DNEL, 15 min)	
DNEL/DMEL (General population)		
Acute - systemic effects, inhalation	50 mg/m³	
Acute - local effects, inhalation	50 mg/m³ (DNEL, 15 min)	
	I	

Safety Data Sheet

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)			
DNEL/DMEL (Workers)			
Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	2.73 mg/m³		
Long-term - local effects, inhalation	5.58 mg/m³		
DNEL/DMEL (General population)			
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day		
Long-term - local effects, inhalation	1.19 mg/m³		
PNEC (Oral)			
PNEC oral (secondary poisoning)	9.33 mg/kg food		
Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11	branched alkyloxy) derivs., C10-rich (398141-87-2)		
DNEL/DMEL (Workers)			
Long-term - systemic effects, dermal	350 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	24.7 mg/m³		
DNEL/DMEL (General population)			
Long-term - systemic effects,oral	2.5 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	4.35 mg/m³		
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day		
PNEC (Water)			
PNEC aqua (freshwater)	2.4 μg/l		
PNEC aqua (marine water)	0.33 μg/l		
PNEC aqua (intermittent, freshwater)	24 μg/l		
PNEC aqua (intermittent, marine water)	3.3 µg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	0.433 mg/kg dwt		
PNEC sediment (marine water)	0.056 mg/kg dwt		
PNEC (Soil)			
PNEC soil	85.3 µg/kg		
PNEC (Oral)			
PNEC oral (secondary poisoning)	111.11 mg/kg food		
PNEC (STP)			
PNEC sewage treatment plant	100 mg/l		
Reaction products of amines, dicoco alkyl and glycollic acid			
DNEL/DMEL (Workers)			
Acute - local effects, dermal	417.36 μg/cm²		
PNEC (Water)	PNEC (Water)		
PNEC aqua (freshwater)	400 μg/L		
PNEC aqua (marine water)	40 μg/l		
PNEC aqua (intermittent, freshwater)	13 μg/l		

Safety Data Sheet

Reaction products of amines, dicoco alkyl and glycollic acid	
PNEC (Sediment)	
PNEC sediment (freshwater)	17100 mg/kg dwt
PNEC sediment (marine water)	1701 mg/kg dwt
PNEC (Soil)	
PNEC soil	3.416 g/kg food
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l
1-(tert-dodecylthio)propan-2-ol (67124-09-8)	
DNEL/DMEL (Workers)	
Acute - local effects, dermal	0.2154 mg/cm²
Long-term - systemic effects, dermal	3.34 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	11.8 mg/m³
DNEL/DMEL (General population)	
Acute - local effects, dermal	0.1077 mg/cm ²
Long-term - systemic effects,oral	0.84 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2.9 mg/m³
Long-term - systemic effects, dermal	1.67 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	6.4 µg/l
PNEC aqua (marine water)	0.64 μg/l
PNEC aqua (intermittent, freshwater)	5.8 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	8.28 mg/kg dwt
PNEC sediment (marine water)	0.828 mg/kg dwt
PNEC (Soil)	
PNEC soil	244 μg/kg
PNEC (Oral)	
PNEC oral (secondary poisoning)	33.33 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l
1,2-Propanediol, 3-amino-, N,N dicocoalkyl derivatives	
DNEL/DMEL (additional information)	
Additional information	not derived
PNEC (additional information)	
Additional information	Not yet determined.
2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol (1218787-32-6)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0.3 mg/kg bodyweight/day

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol (1218787-32-6)	
Long-term - systemic effects, inhalation	2.112 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0.214 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	745 μg/m³
Long-term - systemic effects, dermal	0.214 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	214 ng/l
PNEC aqua (marine water)	21.4 ng/l
PNEC aqua (intermittent, freshwater)	0.87 μg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1.692 mg/kg dwt
PNEC sediment (marine water)	169.2 µg/kg dw
PNEC (Soil)	
PNEC soil	5 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	2 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	1.5 mg/l
Note	: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived

Note

The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), check the atmosphere for oxygen content, presence of hydrogen sulphide (H2S) and SOx, and flammability. See also Section 16, "Other information".

8.2.2. Personal protection equipment

Personal protective equipment (for industrial or professional use):

Gloves. Safety glasses.

Personal protective equipment symbol(s):





Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

8.2.2.1. Eye and face protection

Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure

8.2.2.2. Skin protection

Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

Hand protection:

When there is a risk of contact with the skin, use hydrocarbon-resistant, felt-lined gloves. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.

8.2.2.3. Respiratory protection

Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: if the product is handled without adequate containment: use full or half-face masks with adequate filter for organic vapours. (EN 136/140/145). Combination filter device (DIN EN 141). Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H2S) or self-contained breathing apparatus (SCBA). (EN 136/140/145). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145)

8.2.2.4. Thermal hazards

Thermal hazard protection:

None in normal use conditions.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Do not discharge the product into the environment. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Prevent discharge of undissolved substance to or recover from onsite wastewater. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills.

Consumer exposure controls:

No special requirements necessary, if handled at room temperature.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Red.
Appearance : Clear liquid.
Odour : characteristic.
Odour threshold : Not available

Melting point : -48 °C (pour point) (ASTM D 97)

Freezing point : Not determined
Boiling point : Not determined
Flammability : Not flammable

Explosive properties : None (according to composition).

Oxidising properties : None (according to composition).

Explosive limits : Not available
Lower explosion limit : Not determined
Upper explosion limit : Not determined
Flash point : 180 °C (ASTM D 92)
Auto-ignition temperature : Not determined
Decomposition temperature : Not determined
pH : Not available

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Viscosity, kinematic : > 20.5 mm²/s (40 °C) (ASTM D 445); 5,7 mm2/s (100°C)

Solubility : This product is not soluble in water.

Log Kow : Not available
Vapour pressure : Not determined
Vapour pressure at 50°C : Not determined

Density : 850 kg/m³ (15°C) (ASTM D 4052)

Relative density : Not determined Relative vapour density at 20°C : Not determined Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Additional information : No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

10.2. Chemical stability

Stable product, according to its intrinsic properties (in normal conditions of storage and handling).

10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard. Sensitivity to heat, friction or shock cannot be assessed in advance.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Avoid the build-up of electrostatic charge.

10.5. Incompatible materials

Strong oxidants.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce: Carbon dioxide, Carbon monoxide. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. See also Section 16, "Other information".

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

		(account of the control of the contr
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-		ated neutral oil-based, Baseoil - unspecified (72623-87-1)
	LD50 oral rat	> 5000 mg/kg (OECD 401)
	LD50 dermal rat	> 5000 mg/kg (OECD 402)
	LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)

Safety Data Sheet

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based		
Baseoil - unspecified (72623-87-1)		
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
Mineral base oil, severely refined (N/A)		
LD50 oral rat	≥ 5000 mg/kg bodyweight (OECD 401)	
LD50 dermal rat	≥ 5000 mg/kg bodyweight (OECD 402)	
1-Decene, Dimer, Hydrogenated (68649-11-6)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LC50 Inhalation - Rat	1.17 mg/l/4h (Inhalable aerosol)	
Distillates (petroleum), hydrotreated light pa	raffinic (64742-55-8)	
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11	branched alkyloxy) derivs., C10-rich (398141-87-2)	
LD50 oral rat	10 ml/kg	
LD50 dermal rabbit	4000 – 8000 mg/kg bodyweight	
Reaction products of amines, dicoco alkyl a	nd glycollic acid	
LD50 oral rat	2500 mg/kg bodyweight	
LD50 dermal rat	2000 mg/kg bodyweight	
1-(tert-dodecylthio)propan-2-ol (67124-09-8)		
LD50 oral rat	5000 mg/kg bodyweight	
LD50 dermal rabbit	2000 mg/kg bodyweight	
1,2-Propanediol, 3-amino-, N,N dicocoalkyl d	erivatives	
LD50 oral	> 2500 mg/kg bodyweight Animal: other:, Guideline: other:	
2,2'-(C16-18 (evennumbered, C18 unsaturate	d) alkyl imino) diethanol (1218787-32-6)	
LD50 oral rat	1200 – 2000 mg/kg bodyweight	
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethan	ol (95-38-5)	
LD50 oral rat	1000 – 1265 mg/kg bodyweight	
Skin corrosion/irritation Additional information Serious eye damage/irritation Additional information Respiratory or skin sensitisation Additional information	Not classified (Based on available data, the classification criteria are not met) (according to composition) Not classified (Based on available data, the classification criteria are not met) (according to composition) Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Germ cell mutagenicity Additional information	Contains {0 message= <name of="" sensitizing="" substance="" the=""> fieldvalue=_SENSITIZER_COMPONENTS}. May produce an allergic reaction. This product contains components with a Specific Concentration Limit (SCL). Not classified (Based on available data, the classification criteria are not met) (according to composition)</name>	

Safety Data Sheet

Aspiration hazard

Additional information

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition) All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3) This product contains also the following substances: Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil, and; solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil having a viscosity of approximately 112cSt at 40 °C. It contains a relatively large proportion of saturated hydrocarbons.], Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.
	Not classified (Based on available data, the classification criteria are not met)
	(according to composition)
STOT-single exposure :	Not classified (Based on available data, the classification criteria are not met)
Additional information :	(according to composition)
2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol (1218787-32-6)
NOAEL (acute, oral, animal/male)	13 mg/kg bodyweight
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	l (95-38-5)
NOAEL (oral, rat)	20 mg/kg bodyweight
	Not classified (Based on available data, the classification criteria are not met) (according to composition)
ubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)
ubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)
Mineral base oil, severely refined (N/A)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)
Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)
Reaction products of amines, dicoco alkyl and glycollic acid	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight/day
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethano	(95-38-5)
NOAEL (oral, rat, 90 days)	20 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

: (according to composition)

: Not classified (Based on available data, the classification criteria are not met)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Eni Rotra ATF VI	
Viscosity, kinematic	> 20.5 mm²/s (40 °C) (ASTM D 445); 5,7 mm2/s (100°C)

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2. Other information

Potential adverse human health effects and symptoms

: Contact with eyes may cause temporary reddening and irritation, Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, due to a defatting effect, May produce an allergic reaction

Other information

None

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment. An uncontrolled release to the environment may produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment. Notify authorities if product enters sewers or public waters.

Ecology - water This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)

Ecology - water Harmful to aquatic life.

Hazardous to the aquatic environment, short-term

Hazardous to the aquatic environment, long-term (chronic)

Not classified (Based on available data, the classification criteria are not met)

: Harmful to aquatic life with long lasting effects.

Lubricating oils (petroleum), C20-50, hydrotre	ated neutral oil-based, Baseoil - unspecified (72623-87-1)
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
Baseoil - unspecified (72623-87-1)	

Minoral base oil severely refined (N/A)	
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
LC50 fish 1	> 100 mg/l (LL 50)

nineral base oil, severely refined (N/A)	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

1-Decene, Dimer, Hydrogenated (68649-11-6)	
LC50 fish 1	≥ 1000 mg/l (96h, Oncorhynchus mykiss)
EC50 Daphnia 1	≥ 1000 mg/l (48 h)
ErC50 (algae)	≥ 1000 mg/l (72 h, Scenedesmus capricornutum)
NOEC (chronic)	= 125 mg/l (21 d, Daphnia magna)

	NOEC (chronic)	= 125 mg/l (21 d, Daphnia magna)
Distillates (petroleum), hydrotreated light paraffinic (64742-5		affinic (64742-55-8)
	LC50 fish 1	> 100 mg/l (LL 50)

Safety Data Sheet

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)		
EC50 Daphnia 1 > 10000 mg/l WAF, 48 h (OECD 202)		
Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich (398141-87-2)		
LC50 fish 1	2.4 mg/l	
EC50 Daphnia 1	4.6 mg/l	
Reaction products of amines, dicoco alkyl and	d glycollic acid	
LC50 fish 1	610 mg/l (LL50)	
EC50 Daphnia 1	210 – 180000 μg/l	
EC50 72h - Algae [1]	130 – 160 mg/l (EL50)	
NOEC chronic crustacea	56 mg/l (21d, NOELR)	
1-(tert-dodecylthio)propan-2-ol (67124-09-8)		
LC50 fish 1	750 μg/l	
EC50 Daphnia 1	580 μg/l	
EC50 96h - Algae [1]	> 100 mg/l	
1,2-Propanediol, 3-amino-, N,N dicocoalkyl de	rivatives	
LC50 fish 1	> 100 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)	
EC50 other aquatic organisms 1	230 mg/l Test organisms (species): other aquatic crustacea:	
EC50 72h - Algae [1]	10 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
EC50 72h - Algae [2]	16 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
2,2'-(C16-18 (evennumbered, C18 unsaturated	l) alkyl imino) diethanol (1218787-32-6)	
LC50 fish 1	0.1 mg/l (Brachydanio rerio)	
EC50 Daphnia 1	0.043 mg/l (Daphnia Magna)	
EC50 72h - Algae [1]	0.0538 mg/l (Pseudokirchneriella subcapitata)	
NOEC chronic algae	0.0158 mg/l (Pseudokirchneriella subcapitata)	
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethano	I (95-38-5)	
LC50 fish 1	0.3 mg/l (Brachydanio rerio)	
EC50 Daphnia 1	0.163 mg/l (Daphnia magna)	
EC50 72h - Algae [1]	0.03 mg/l	
EC50 72h - Algae [2]	0.0169 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
NOEC chronic algae	0.011 mg/l	
2-tetradecyloxirane, reaction products with be	oric acid	
LC50 fish 1	> 100 mg/l	
EC50 Daphnia 1	> 100 mg/l (Daphnia magna, 2 d)	
EC50 Daphnia 2	20 mg/l (Daphnia magna, 21 d)	
EC50 72h - Algae [1]	> 100 mg/l (Selenastrum capricomutum)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

12.2. Persistence and degradability

,		
Eni Rotra ATF VI		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
Lubricating oils (petroleum), C20-50, hydrotre	ated neutral oil-based, Baseoil - unspecified (72623-87-1)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	ated neutral oil-based	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
Mineral base oil, severely refined (N/A)		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
1-Decene, Dimer, Hydrogenated (68649-11-6)		
Persistence and degradability	Inherently biodegradable.	
Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11	branched alkyloxy) derivs., C10-rich (398141-87-2)	
Biodegradation	9.6 % (28d, OECD TG 301 C)	
1-(tert-dodecylthio)propan-2-ol (67124-09-8)		
Biodegradation	5.9 % (28d, OECD TG 301 F)	
2,2'-(C16-18 (evennumbered, C18 unsaturated	l) alkyl imino) diethanol (1218787-32-6)	
Biodegradation	63 % (28 d, OECD TG 301 D)	
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol (95-38-5)		
Biodegradation	1 % (28 d, OECD TG 301 B)	
2-tetradecyloxirane, reaction products with boric acid		
Persistence and degradability	Not readily biodegradable.	
Biodegradation	17.3 % 28 d	
12.3. Bioaccumulative potential		

Eni Rotra ATF VI		
Bioaccumulative potential Not established.		
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)		
Log Kow > 6		

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)			
g Kow > 6			
Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11	branched alkyloxy) derivs., C10-rich (398141-87-2)		
Bioconcentration factor (BCF REACH)	27.54		
Log Kow	4.1		
1-(tert-dodecylthio)propan-2-ol (67124-09-8)			
Log Kow	5.7		
2,2'-(C16-18 (evennumbered, C18 unsaturated	l) alkyl imino) diethanol (1218787-32-6)		
Bioconcentration factor (BCF REACH)	110.2		
Log Kow	3.6		
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol (95-38-5)			
Log Kow	> 7		
2-tetradecyloxirane, reaction products with boric acid			
Log Kow 9.4			

12.4. Mobility in soil

Eni Rotra ATF VI	
Mobility in soil Not determined	
Ecology - soil	No data available.

12.5. Results of PBT and vPvB assessment

	ATF VI

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Component

Mineral base oil, severely refined (N/A)

This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

12.7. Other adverse effects

Other adverse effects : None

Additional information : No other effects known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

11/18/2022 (Revision date) EU - en 21/27

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Waste treatment methods : Do not dispose of the product, either new or used, by discharging into sewers, tunnels,

lakes or water courses. Deliver to a qualified official collector. Dispose of empty containers

and wastes safely.

Sewage disposal recommendations : Dispose of in a safe manner in accordance with local/national regulations. Do not apply

industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Product/Packaging disposal recommendations : European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based

non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual

use of the product, alterations and contaminations.

Ecology - waste materials : The product as it is does not contain halogenated substances.

EURAL code (EWC) : 13 02 05* - Mineral-based non-chlorinated engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID n	umber				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated	
14.2. UN proper shippin	g name				
Not regulated	Not regulated Not regulated Not regulated Not regulated Not regulated				
14.3. Transport hazard	class(es)				
Not regulated	Not regulated Not regulated Not regulated Not regulated Not regulated			Not regulated	
14.4. Packing group					
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated	
14.5. Environmental hazards					
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated	
None.					

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

IBC code : Not applicable.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

	(REACH Annex XVII)	
Reference code	Applicable on	Entry title or description
3(b)	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based, Baseoil - unspecified; Mineral base oil, severely refined; 1- Decene, Dimer, Hydrogenated; Distillates (petroleum), hydrotreated light paraffinic; Reaction products of amines, dicoco alkyl and glycollic acid; 1-(tert- dodecylthio)propan-2-ol; 1,2-Propanediol, 3-amino-, N,N dicocoalkyl derivatives; 2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol; 2-(2-heptadec- 8-enyl-2-imidazolin-1- yl)ethanol; Calcium sulphonate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Eni Rotra ATF VI; Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich; 1-(tert- dodecylthio)propan-2-ol; 1,2-Propanediol, 3-amino-, N,N dicocoalkyl derivatives; 2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol; 2-(2-heptadec- 8-enyl-2-imidazolin-1- yl)ethanol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Other information, restriction and prohibition regulations

: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et seguens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et seguens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances (ODP). Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC. Regulation EU (649/2012) - Export and Import of hazardous chemicals (PIC).

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National laws on classification and labeling of dangerous substances/preparations (Adoption of Directive 67/548/CE and subsequent Adaptations to Technical Progress - ATP, and Directive 1999/45/CE).

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

Finland

Finnish National Regulations : Occupational Safety and Health Act No. 738/2002.

France		
Maladies professionelles (F)		
Code	Code Description	
RG 36	Diseases caused by oils and fats of mineral or synthetic origin	

Germany

Employment restrictions	: Employment prohibitions or restrictions on the protect	ion of young people at work according

to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.

Water hazard class (WGK) (D) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1) WGK remark

Classification based on the components in compliance with Verwaltungsvorschrift

wassergefährdender Stoffe (VwVwS)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

National Rules and Recommendations TRGS 900: Occupational Exposure Limits TRGS 800: Fire protection measures

TRGS 555: Working instruction and information for workers

TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous

Substances: Inhalation Exposure

TRGS 401: Risks resulting from skin contact - identification, assessment, measures TRGS 400: Hazard assessment for activities involving Hazardous Substances

Storage class (LGK, TRGS 510) LGK 10 - Combustible liquids

VbF class (D) Not applicable.

Netherlands

Waterbezwaarlijkheid : 8 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment

9 - Harmful to aquatic organisms

Saneringsinspanningen : C - Minimize discharge

SZW-lijst van kankerverwekkende stoffen None of the components are listed SZW-lijst van mutagene stoffen : None of the components are listed

11/18/2022 (Revision date) FU - en 24/27

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SZW-lijst van reprotoxische stoffen - Borstvoeding

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid

: None of the components are listed: None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling

kkeling :

: None of the components are listed

Denmark

Danish National Regulations

: Young people under 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with it

Norway

Norwegian National Regulations

: Working Environment Act (LOV-2005-06-17 NO. 62).

People under the age of 18 may not work with this product at all.

Sweden

Swedish National Regulations

: This product is in compliance with Ordinance 1998:944.

Work Environment Act (1977: 1160).

Chemical Hazards in the Working Environment (AFS 2011:19).

15.2. Chemical safety assessment

For this mixture a chemical safety assessment has been not carried out

A chemical safety assessment has been carried out for the following components of this mixture::

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Baseoil - unspecified

1-Decene, Dimer, Hydrogenated

Distillates (petroleum), hydrotreated light paraffinic

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich

Reaction products of amines, dicoco alkyl and glycollic acid

1,2-Propanediol, 3-amino-, N,N dicocoalkyl derivatives

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol

2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Notes
1.1	Formula	Modified	
3	Composition/information on ingredients	Modified	
8.2	Personal protective equipment (for industrial or professional use)	Modified	
9.1	Melting point	Modified	
9.1	Viscosity, kinematic	Modified	
12.4	Mobility in soil	Added	
12.6	Adverse effects on the environment caused by endocrine disrupting properties	Added	
15.1	REACH Annex XVII	Modified	

Abbreviations and acronyms:		
Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.		
N/D = not available		
	N/A = not applicable	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:			
ATE	Acute Toxicity Estimate		
BCF	Bioconcentration factor		
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008		
DMEL	Derived Minimal Effect level		
DNEL	Derived-No Effect Level		
EC50	Effective concentration for 50 percent of test population (median effective concentration)		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)		
LD50	Lethal dose for 50 percent of test population (median lethal dose)		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
PBT	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006		
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
vPvB	Very Persistent and Very Bioaccumulative		

Data sources

Training advice

Other information

- : This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
- : Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.
- Do not use the product for any purposes that have not been advised by the manufacturer. In exceptional cases (i.e prolunged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary. This situation is especially relevant for those operations which involve direct exposure to the vapours in the interior of tanks or other confined spaces. If this possibility is suspected, a specific assessment of inhalation risks from the presence of H2S in confined spaces must be made, to help determine prevention measures and controls (i.e. PPE) appropriate to local circumstances, and adequate emergency procedures.

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation:dust,mist)

Acute toxicity (inhalation:dust,mist) Category 4

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:			
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4		
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1		
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1		
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2		
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3		
Asp. Tox. 1	Aspiration hazard, Category 1		
EUH208	Contains Reaction products of amines, dicoco alkyl and glycollic acid, 1,2-Propanediol, 3-amino-, N,N dicocoalkyl derivatives, 2-tetradecyloxirane, reaction products with boric acid. May produce an allergic reaction.		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1		
H302	Harmful if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H314	Causes severe skin burns and eye damage.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H332	Harmful if inhaled.		
H373	May cause damage to organs through prolonged or repeated exposure.		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		
H411	Toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C		
Skin Sens. 1	Skin sensitisation, Category 1		
Skin Sens. 1B	Skin sensitisation, category 1B		
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2		

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:				
Aquatic Chronic 3	H412	Calculation method		

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.