Date of issue: 29.04.2004

ling to 1907/2006/EC Revised on: 18.08.2016 eni

eni Antifreeze Spezial Seite 1 von 8

Section 1. Identification of the substance/mixture and of the company/undertaking.

1.1 Product identifier:	eni Antifreeze Spezial		
1.2 Relevant identified uses of the substance or mixture and uses advised against:			
Identified uses:	Antifreeze/Coolant		
1.3 Details of the supplier of the safety data sheet:	Eni Schmiertechnik GmbH Paradiesstr. 14, 97080 Würzburg TEL. (+ 49) 931 - 900 98-0 FAX (+ 49) 931-98442		
Support:	Technical department, Tel. (+49) 931 900 98-145 technik.wuerzburg@agip.de www.enischmiertechnik-datenblaetter.de		

Section 2. Hazards identification.

2.1 Classification of the substance or mixture:

The mixture has been assessed and/ or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended.

Acute toxicity, oral	Category 4	H302 – Harmful if swallowed
Reproductive toxicity (the unborn child)	Category 2	H361d – Suspected of damaging the unborn child.
Specific target organ toxicity – Repeated exposure	Category 2 (kidney)	H373 – May cause damage to organs (kidney) through
Hazard summary:	Harmful if swallowed. Ma	prolonged or repeated exposure. y cause damage to organs through prolonged or repeate

Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure. Possible reproductive hazard. Occupational exposure to the substance or mixture may cause adverse health effects.

2.2 Label elements:

Label according to Regulation (EC) No. 1272/2008 as amended. Contains: Ethylene glycol, Sodium 2- ethylhexanoate



Signal word: Hazard statements: H302 H361d H373 Precautionary statements: Prevention: P102 P260 P280 Response: P101 P301 + P310 Storage P405: Disposal: P501 Supplemental label information:

2.3 Other hazards:

Harmful if swallowed Suspected of damaging the unborn child. May cause damage to organs (kidney) through prolonged or repeated exposure.

Keep out reach of children. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Wear protective gloves/ protective clothing/ eye protection/ face protection

If medical advice is needed, have product container or label at hand. IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Store locked up.

Dispose of contents/ container in accordance with local/ regional/ national/ international regulations.

None.

Not a PBT or vPvB substance or mixture.



Section 3. Composition/information on ingredients.

General information: Chemical name	%	CAS-No./ EC No.	REACH Registration No.	INDEX No.	Notes
Ethylene glycol	80-98	107-21-1 203-473-3	01-2119456816-28-XXXX	-	#
Classification:	Acute T	ox. 4; H302, STOT RE 2	; H373		
Sodium 2- ethylehexanoate	3-<5	19766-89-3 243-283-8	Exempt	-	
Classification:	Repr. 2	; H361d			E
List of abbreviations and symbols th #: This substance has been assigned	nat may be i ed Union wo	used above: orkplace exposure limit(s)).		
Composition comments:	The full text for all H- statements is displayed in section 16. All concentrations are in percent by weight.				

E Exempted from registration as per Annex V of the regulation 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). This product contains a bittering agent.

Section 4. First aid measures.

General information:	IF exposed or concerned: Get medical advice/ attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
4.1 Description of the first aid measure	S:
Inhalation:	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact:	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact:	Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion:	Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/ attention if you feel unwell.
4.2 Most important symptoms and effects, both acute and delayed:	Convulsions. Dizziness. Nausea, vomiting. Abdominal pain. Oedema. Prolonged exposure may cause chronic effects.
4.3 Indication of any immediate medical attention and special treatment needed.	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Section 5. Fire fighting measures.

General fire hazards:	No unusual fire or explosion hazards noted.
5.1 Extinguishing media:	
Suitable extinguishing media:	Alcohol resistant foam. Powder. Carbon dioxide (CO ₂)
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.
5.2 Special hazards arising from the substance or mixture:	Thermal decomposition may produce smoke, oxides of carbon and lower molecular weight organic compounds whose composition have not been characterised.
5.3 Advice for fire fighters:	
Special protective equipment for Firefighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special firefighting procedures:	Move container from fire area if you can do so without risk.
Specific methods:	Use standard firefighting procedures and consider the hazards of other involved materials.

y (f

Section 6. Accidental release measures.

6.1 Personal precautions, protective equipment and emergency precautions:

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapour. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.
Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.
Avoid discharge into drains, water courses or onto the ground.
Use water spray to reduce vapours or divert vapour cloud drift. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use.
For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

Section 7. Handling and storage.

7.1 Precautions for safe handling:	Obtain special instructions before use. Do not handle until all safety precautions have ben read and understood. Do not breathe mist or vapour. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.	
7.2 Conditions for safe storage, including any incompatibilities:		
General handling information:	Store locked up. Store in original tightly closed container. Store away from incompatible materials (see section 10 of the SDS).	
7.3 Specific end use(s):	Antifreeze/Coolant.	

Section 8. Exposure controls/Personal protection.

General considerations:
Consider the potential hazards of this material (see section 2), applicable exposure limits, job activities and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Refer to appropriate CEN standards.
8.1 Control parameters:

Occupational exposure limits:

UK. EH40 Workplace Exposure Limits (WELs)

Components	Туре	Value	Form
Ethylene glycol (CAS 107-21-1)	STEL	104 mg/m ³	Vapor.
		40 ppm	Vapor.
	TWA	52 mg/m ³	Vapor.
		10 mg/m^3	Particulate.
		20 ppm	Vapor.

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2006/39/EC, 2009/161/EU

Eni Schmiertechnik

MATERIAL SAFETY DATA SHEET according to 1907/2006/EC 29.04.2004 Date of issue:

Revised on: 18.08.2016



eni Antifreeze Spezial Seite 4 von 8

Components	Туре	Value	
Ethylene glycol (CAS 107-21-1)	STEL	104 mg/m ³	
	T\0/ 0	40 ppm 52 mg/m ³	
	IWA	20 ppm	
Biological limit values:	No biological exposure limits note	d for the ingredient(s).	
Recommended monitoring	Follow standard monitoring procee	dures.	
Procedures:			
Derived no effect levels (DNELs)			
General Population:			
Components	Value	Assessment factor	Notes
Ethylene glycol (CAS 107-21-1)	_ / 3		
Long-term, Local, Inhalation	7 mg/m°	10	
Long-term, Systemic, Dermai	55 mg/kg	84	
Workers			
Components	Value	Assessment factor	Notes
Ethylene glycol (CAS 107-21-1)	35 mg/m^3	2	
Long-term, Systemic, Dermal	106 mg/kg	42	
Predicted no offect concentrations (PNI	=Co)		
		Assessment factor	Notes
Ethylene glycol (CAS 107-21-1)	Value		Notes
Freshwater	10 mg/l	10	
Intermittent releases	10 mg /l	10	
Marine water	1 mg/l	100	
Sediment (freshwater)	37 mg/kg 3 7 mg/kg		
Soil	1.53 ma/ka		
STP	199,5 mg/l	10	
Exposure guidelines:			
UK EH 40 WEL: Skin designation			
Ethylene glycol (CAS 107-21-1)	Can be absorbed through the skin	I.	
8.2 Exposure controls:			
Appropriate Engineering controls:	Good general ventilation (typica	ally 10 air changes per hour)	should be used.
	Ventilation rates should be ma	atched to conditions. If applica	ble, use process
	airborne levels below recommend	led exposure limits If exposure lin	nits have not been
	established, maintain airborne lev	els to an acceptable level.	
Individual protection measures, such as	personal protective equipment.		
General information:	Personal protection equipment sh	ould be chosen according to the C	EN standards and
	in discussion with the supplier of t	he personal protective equipment.	
Eye/face protection:	chemical respirator with organic va	apour cartridge and full face piece.	
Skin Protection	Wear appropriate chemical resista	ant gloves. Wear suitable gloves te	sted to EN374.
-Hand protection:	Full contact: Use gloves classifie	d protection index 6 with breakth	rough time of 480
	minutes. Minimum glove thicknes	ss 0,38 mm. neoprene, butyl rubb able, gloves, can be recommend	er, nitrile or Viton
	supplier.	able gloves can be recommente	ied by the giove
Other:	Wash hands thoroughly after hand	dling. Use of an impervious apron i	s recommended.
Respiratory protection:	Chemical respirator with organic v	apour cartridge and full face piece	
Thermal hazards:	Wear appropriate thermal protective clothing, when necessary		
Hydiene measures:	Observe any medical surveilland	ce requirements. Keep away from	n food and drink
	Always observe good personal hv	giene measures, such as washing	after handling the
	material and before eating, drinki	ng, and / or smoking. Routinely \tilde{v}	ash work clothing
	and protective equipment to remo	ve contaminants.	
Environmental exposure controls:	Environmental manager must be i	nformed of all major releases.	

Date of issue: 29.04.2004

Revised on: 18.08.2016



eni Antifreeze Spezial Seite 5 von 8

Section 9. Physical and chemical properties.

9.1 Information on basic physical and chemical properties:

Appearance:	
Colour:	Light Red
Physical state:	Liquid
Form:	Clear liquid.
Odour:	Mild.
Odour threshold:	Not determined.
pH:	8,7 (20°C) (Typical)
Melting point:	Not applicable
Initial boiling point:	175°C (347°F) (Typical)
Flashpoint:	122°C (251,6°F) Pensky-Martens closed cup (Approximate)
Evaporation rate:	Not determined.
Flammability (solid, gas):	No applicable.
Flammability (explosive) limits (% by vol	ume in air):
Lower/upper:	Not determined.
Vapour pressure:	Not determined.
Vapour density (air = 1):	Not determined.
Relative Density at 15,6°C:	Not determined.
Solubility:	Miscible.
Partition coefficient	
(n-octanol/water):	Not determined.
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Viscosity:	Not determined.
Explosive properties:	Not explosive.
Oxidising properties:	Not oxidising.
9.2 Other information:	
Density:	1,113 kg/l (20°C) (Typical)

Section 10. Stability and reactivity.

10.1 Reactivity:	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2 Chemical stability:	Material is stable under normal conditions.
10.3 Possibility of hazardous reactions:	No dangerous reaction known under conditions of normal use.
10.4 Conditions to avoid:	Contact with incompatible materials.
10.5 Incompatible materials to avoid:	Strong acids. Strong oxidising agents. Nitrates. Peroxides. Chlorates.
10.6 Hazardous decomposition	
products:	At elevated temperatures: Kentones. Aldehydes.

Section 11. Toxicological information.

General informations:	Occupational exposure to the substance or mixture may cause adverse effects.
Information on likely routes of exposure	:
Inhalation:	In high concentrations, mists/ vapors may irritate throat and respiratory system and cause coughing.
Skin contact:	Prolonged or repeated contact may dry skin and cause irritation.
Eye contact:	Direct contact with eyes may cause temporary irritation.

MATERIAL SAFETY DATA SHEET according to 1907/2006/EC



Date of issue: 29.04.2004

Revised on: 18.08.2016

Ingestion:	Harmful if swallowed Ingestion of ethylene glycol may result in nausea, vomiting, abdominal cramps, blindness, liver damage, irritation, reproductive effects, verve damage, convulsions, oedema of the lung, cardiopulmonary effects (metabolic acidosis), pneumonia and kidney failure which could result in death. The single lethal dose for humans is about 100 ml. Inhalation of high levels of vapour or mists for prolonged periods of time may also result in toxic effects.	
Symptoms:	Convulsions. Dizziness. Nausea, vomiting. Abdomir	nal pain. Oedema.
11.1 Information on toxicological effects	:	
Acute toxicity:	Harmful if swallowed.	
Product	Species	Test results
Antifreeze Spezial		
Acute		
Oral		
		1720 mg/kg, ATE
Components	Species	Test results
Ethylene glycol (CAS 107-21-1)		
Acute		
Dermal		
LD50	Mouse	>3500 mg/kg
Inhalation		
LC50	Rat	>2,5 mg/l, 6 hours
Oral		
LD50	Cat	1600 mg/kg
Serious eye damage/irritation:	Based on available data, the classification criteria are not met.	
Skin corrosion/irritation:	Based on available data, the classification criteria are not met.	
Respiratory sensitisation:	Due to partial or complete lack of data the classification is not possible.	
Skin sensitization:	Based on available data, the classification criteria are not met.	
Germ cell mutagenicity:	Based on available data, the classification criteria are not met.	
Carcinogenicity:	Due to partial or complete lack of data the classification is not possible.	
Reproductive Toxicity:	Suspected of damaging the unborn child.	
Specific target organ toxicity - single exposure:	Based on available data, the classification criteria are not met.	
Specific target organ toxicity - repeated exposure:	May cause damage to organs (kidney) through prolonged or repeated exposure.	
Aspiration hazard:	Due to partial or complete lack of data the classifica	tion is not possible.
Mixture versus substance information:	No information available.	
Other information:	No data available.	

Section 12. Ecological information.

12.1 Toxicity:	Based on available data, the classification criteria are not met for hazardous to the aquatic environment.		
Components	Specie	s	Test results
Ethylene glycol (CAS 107-21-1) Aquatic			
Crustacean	EC50	Daphnia magna	>100 mg/l, 48 Hours
12.2 Persistence and degradability: 12.3 Bioaccumulative potential: Partition coefficient n-octanol/water (log Kow) Ehylene glycol (CAS 107-21-1):	ECSU Expect	ratiead minitiow (rimephales prometas) red to be readily biodegradable.	72000 Hig/i, 90 Houis

Date of issue: 29.04.2004

Revised on: 18.08.2016



Bioconcentration factor (BCF):Not available.12.4 Mobility in soil:No data available.12.5 Results of PBT and vPvBNot a PBT or vPvB substance or mixture.assessment:12.6 Other adverse effects:No data available.

Section 13. Disposal considerations.

13.1 Waste treatment methods:	
Residual waste:	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging:	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code:	EWC. 16 01 14
Disposal methods/ information:	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/ container in accordance with local/ regional/ national/ international regulation.
Special precautions:	Dispose in accordance with all applicable regulations.

Section 14. Transport information.

ADR	14.1. – 14.6.: Not regulated as dangerous goods.
RID	14.1. – 14.6.: Not regulated as dangerous goods.
AND	14.1. – 14.6.: Not regulated as dangerous goods.
IATA	14.1. – 14.6.: Not regulated as dangerous goods.
IMDG	14.1. – 14.6.: Not regulated as dangerous goods.
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC-Code:	Not established.

Section 15. Regulatory information.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: EU regulations: Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed. Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended Not listed Regulation (EC) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed. Regulation (EC) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed. Regulation (EC) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed. Regulation (EC) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed. Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed. Regulation (EC) No. 1907/2006, REACH Article 59 (10) Candidate List as currently published by ECHA Not listed. Authorisations: Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended Not listed.

Eni Schmiertechnik	
MATERIAL SAFETY DATA SHEET according to 1907/2006/E	C

Date of issue: 29.04.2004

Revised on: 18.08.2016



Restrictions on use:

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Other EU regulations:

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended Not listed.

Other regulations:	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirement of Regulation (EC) No. 1907/2006, as amended.
	All components of this product are compliant with the registration requirements of Regulation (EC) 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals, as amended.
	All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), EINECS (European Union), ENCS (Japan), IECSC (China), KECI (Korea), PICCS (Philippines), TSCA (United States), TCSI (Taiwan), NZIoC (New Zealand).
National regulations:	Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended. According to Directive 92/85/EEC as amended, pregnant women should not work with the product, if there is the least risk of exposure.
15.2 Chemical safety assessment:	No chemical safety assessment has been carried out.

Section 16. Other information.

This information relates only to the specific product and may not be valid if the product is used in combination with any other material or in any process.

The information in this sheet is according to our best knowledge at the date of printing.

Changes: 2 - 16

Full text of CLP H-statements:

H302	Harmful if swallowed
H361d	Suspected of damaging the unborn child
H373	May cause damage to organs through prolonged or repeated exposure