

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Eni metalStanz 4 EP
UFI: 9P50-K0CS-V00J-G4M5

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: lubricants, greases, release products

1.3 Details of the supplier of the safety data sheet

Company name: Enilive Schmiertechnik GmbH
Street/POB-No.: Paradiesstraße 14
Postal Code, city: 97080 Würzburg
Germany
E-mail: info.wuerzburg@enilive.com
Telephone: +49 (0)931-90098-0
Telefax: +49 (0)931-98442
Department responsible for information:
Application Engineering & Product Management (AEPM)
Telephone: +49 (0)931-90098-0
E-mail: technik.wuerzburg@enilive.com

1.4 Emergency telephone number

GIZ-Nord, Göttingen
Telephone: +49 (0)551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Flam. Liq. 3; H226	Flammable liquid and vapour.
Asp. Tox. 1; H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 4; H413 (EUH066)	May cause long lasting harmful effects to aquatic life. Repeated exposure may cause skin dryness or cracking.

2.2 Label elements

Labelling (CLP)



Signal word: **Danger**



Eni metalStanz 4 EP

Material number 719

Revision date: 20.3.2024
Version: 10.0
Replaces version: 9.1
Language: en-DE
Date of print: 5.4.2024

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Page: 2 of 13

Hazard statements:	H226	Flammable liquid and vapour.
	H304	May be fatal if swallowed and enters airways.
	H413	May cause long lasting harmful effects to aquatic life.
	EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements:	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
	P331	Do NOT induce vomiting.
	P403+P235	Store in a well-ventilated place. Keep cool.
	P405	Store locked up.
	P501	Dispose of contents/container to hazardous or special waste collection point.

Special labelling

Text for labelling: Contains: Naphtha (petroleum), hydrotreated heavy

2.3 Other hazards

Special danger of slipping by leaking/spilling product. Potentially explosive mixtures may form if adequate ventilation is not provided.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Mixture of the substances listed below with non-hazardous additions

Hazardous ingredients:

Identifiers	Designation Classification	Content
list no. 918-167-1 CAS -	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3; H226. Asp. Tox. 1; H304. Aquatic Chronic 4; H413. (EUH066).	>= 90 %

Full text of H- and EUH-statements: see section 16.

Additional information: The highly refined mineral oil contains <3% (w/w) DMSO extract, according to IP346.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: If medical advice is needed, have product container or label at hand.
Avoid contact with skin, eyes and clothes. Take off immediately all contaminated clothing.



Eni metalStanz 4 EP

Material number 719

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 20.3.2024
Version: 10.0
Replaces version: 9.1
Language: en-DE
Date of print: 5.4.2024

Page: 3 of 13

In case of inhalation:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if problems persist.
Following skin contact:	Immediately clean with water and soap followed by thorough rinsing. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
After swallowing:	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Immediately get medical attention. Caution if victim vomits: Risk of aspiration!

4.2 Most important symptoms and effects, both acute and delayed

Inhaling can lead to irritations of the respiratory tract and mucous membrane.
May be fatal if swallowed and enters airways. Higher doses may lead to a narcotic effect.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Symptoms can occur only after several hours. Medical surveillance necessary for at least 48 hours.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide, Sand.
Co-ordinate fire-fighting measures to the fire surroundings.

Extinguishing media which must not be used for safety reasons:

Water

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour. Air combined with vapours may form potentially explosive mixtures that are heavier than air. Vapours may proceed on the ground over great distances and cause fire and backflashes.

May form dangerous gases and vapours in case of fire.

Furthermore, there may develop: nitrogen oxides (NO_x), carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:

Heating will lead to pressure increase: Danger of bursting and explosion. Keep containers cool with water spray.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.



Eni metalStanz 4 EP

Material number 719

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 20.3.2024
Version: 10.0
Replaces version: 9.1
Language: en-DE
Date of print: 5.4.2024

Page: 4 of 13

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe mist/vapours/spray. Avoid contact with the substance.
If possible, eliminate leakage. Provide adequate ventilation.
Wear appropriate protective equipment. Keep unprotected people away.
Take off contaminated clothing and wash it before reuse.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Danger of explosion!
In case of release, notify competent authorities. If necessary notify appropriate authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).
Beware of reignition. Thoroughly clean surrounding area.
In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information: Use explosion-proof equipment and non-sparking tools/utensils.
Special danger of slipping by leaking/spilling product.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment.
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.
When handling large quantities, supply emergency spray.

Precautions against fire and explosion:
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take action to prevent static discharges.
Use only explosion-protected equipment/instruments. Do not weld.
In partially filled containers explosive mixtures may form.



Eni metalStanz 4 EP

Material number 719

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 20.3.2024
Version: 10.0
Replaces version: 9.1
Language: en-DE
Date of print: 5.4.2024

Page: 5 of 13

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.
Keep container dry. Keep only in the original container.
Protect from heat and direct sunlight.
Store containers in upright position.
Make sure spills can be contained, e.g. in sump pallets or kerbed areas.
Do not store at temperatures below: 0 °C
Recommended storage temperature: 5 °C - 40 °C
Storage stability: 24 months

Hints on joint storage: Do not store together with: Oxidizing agents, acids.
Keep away from food, drink and animal feedingstuffs.

Storage class: 3 = Flammable liquids

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
-	Naphtha (petroleum), hydrotreated heavy	Germany: TRGS 900 Kurzzeit	600 mg/m ³ (hydrocarbons, aliphatic, C9-C14)
		Germany: TRGS 900 Langzeit	300 mg/m ³ (hydrocarbons, aliphatic, C9-C14)

8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

Personal protection equipment

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded.

Recommendation:

Combination filtering device (DIN EN 141): A2 - P3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection:

Protective gloves according to DIN EN 374.

Glove material: Acrylonitrile-butadiene-rubber

Breakthrough time: 4 h

Layer thickness: 0,12 mm

Unsuitable material: butyl caoutchouc (butyl rubber), natural rubber (Caoutchouc), natural latex, polychloroprene and chloroprene rubber.

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection:

Tightly sealed goggles according to DIN EN ISO 16321-1:2022.



Eni metalStanz 4 EP

Material number 719

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 20.3.2024

Version: 10.0

Replaces version: 9.1

Language: en-DE

Date of print: 5.4.2024

Page: 6 of 13

Body protection: Flame retardant, antistatic and chemical resistant protective clothing.

General protection and hygiene measures:

Do not breathe mist/vapours/spray. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not get in eyes, on skin, or on clothing. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. When using do not eat or drink. Wash hands thoroughly after handling. When handling large quantities, supply emergency spray.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa	liquid
Colour:	yellow
Odour:	Characteristic
Odour threshold:	No data available
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flammability:	Flammable liquid and vapour.
Upper/lower flammability or explosive limits:	LEL (Lower Explosion Limit): Not determined UEL (Upper Explosive Limit): Not determined
Flash point/flash point range:	58 °C
Auto-ignition temperature:	240 °C
Decomposition temperature:	No data available
pH:	Not determined
Viscosity, kinematic:	at 40 °C: 1,3 mm ² /s
Water solubility:	Not determined
Partition coefficient: n-octanol/water:	1,990 - 6,730 log K(o/w) (Naphtha (petroleum), hydrotreated heavy) Based on the n-octanol/water partition coefficient accumulation in organisms is possible.
Vapour pressure:	No data available
Density:	at 20 °C: 0,76 g/mL
Vapour density:	Not determined
Particle characteristics:	Not applicable

9.2 Other information

Explosive properties:	Vapours can form explosive mixtures with air.
Oxidizing characteristics:	Not oxidising
Auto-ignition temperature:	No data available
Evaporation rate:	No data available



Eni metalStanz 4 EP

Material number 719

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 20.3.2024

Version: 10.0

Replaces version: 9.1

Language: en-DE

Date of print: 5.4.2024

Page: 7 of 13

SECTION 10: Stability and reactivity

10.1 Reactivity

Flammable liquid and vapour.
Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Heating will lead to pressure increase: Danger of bursting and explosion.

10.4 Conditions to avoid

Protect from heat and direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Oxidizing agents, acids.

10.6 Hazardous decomposition products

No decomposition when used properly.

Thermal decomposition: No data available



Eni metalStanz 4 EP

Material number 719

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 20.3.2024

Version: 10.0

Replaces version: 9.1

Language: en-DE

Date of print: 5.4.2024

Page: 8 of 13

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.

Skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.

Aspiration hazard: Asp. Tox. 1; H304 = May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties:

No data available

Symptoms

The following symptoms may occur: respiratory complaints, headache, dizziness, discomfort

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: May cause long lasting harmful effects to aquatic life.
Information about Naphtha (petroleum), hydrotreated heavy
Daphnia toxicity: EL50, Daphnia magna (Big water flea): > 1mg/L/21d

Water Hazard Class: 1 = slightly hazardous to water (Self-classification (mixture).)

12.2 Persistence and degradability

Further details: Information about Naphtha (petroleum), hydrotreated heavy
Degradation rate (oxygen consumption): 7,3%/4d
Degradation rate (formation of carbon dioxide): 0%/3d



Eni metalStanz 4 EP

Material number 719

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 20.3.2024

Version: 10.0

Replaces version: 9.1

Language: en-DE

Date of print: 5.4.2024

Page: 9 of 13

12.3 Bioaccumulative potential

Information about Naphtha (petroleum), hydrotreated heavy

BCF: $\geq 6,91$ - ≤ 3.625

Partition coefficient: n-octanol/water:

1,990 - 6,730 log K(o/w) (Naphtha (petroleum), hydrotreated heavy)

Based on the n-octanol/water partition coefficient accumulation in organisms is possible.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 14 06 03* = other solvents and solvent mixtures
* = Evidence for disposal must be provided.

Recommendation: Dispose of waste according to applicable legislation.
Do not dispose of with household waste.

Package

Waste key number: 15 01 10* = packaging containing residues of or contaminated by dangerous substances
* = Evidence for disposal must be provided.

Recommendation: Handle contaminated packages in the same way as the substance itself. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID, ADN, IMDG, IATA-DGR:
UN 3295

14.2 UN proper shipping name

ADR/RID, ADN, IMDG, IATA-DGR:
UN 3295, HYDROCARBONS, LIQUID, N.O.S.



Eni metalStanz 4 EP

Material number 719

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 20.3.2024
Version: 10.0
Replaces version: 9.1
Language: en-DE
Date of print: 5.4.2024

Page: 10 of 13

14.3 Transport hazard class(es)

ADR/RID, ADN: Class 3, Code: F1
IMDG: Class 3, Subrisk -
IATA-DGR: Class 3



14.4 Packing group

ADR/RID, ADN, IMDG, IATA-DGR:
III

14.5 Environmental hazards

Dangerous for the environment:

Substance/mixture is not environmentally hazardous according to the criteria of the UN model regulations.

Marine pollutant - IMDG: no

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board: ADR/RID: Kemmler-number 30, UN number UN 3295
Hazard label: 3
Limited quantities: 5 L
EQ: E1
Package - Instructions: P001 IBC03 LP01 R001
Special provisions for packing together: MP19
Portable tanks - Instructions: T4
Portable tanks - Special Provisions: TP1 TP29
Tank coding: LGBF
Tunnel restriction code: (D/E)

Inland waterway craft (ADN)

Hazard label: 3
Limited quantities: 5 L
EQ: E1
Transport permitted: T
Equipment necessary: PP - EX - A
ventilation: VE01



Eni metalStanz 4 EP

Material number 719

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 20.3.2024
Version: 10.0
Replaces version: 9.1
Language: en-DE
Date of print: 5.4.2024

Page: 11 of 13

Sea transport (IMDG)

EmS: F-E, S-D
Special Provisions: 223
Limited quantities: 5 L
Excepted quantities: E1
Package - Instructions: P001, LP01
Package - Provisions: -
IBC - Instructions: IBC03
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T4
Tank instructions - Provisions: TP1, TP29
Stowage and handling: Category A.
Properties and observations: Immiscible with water.
Segregation group: none

Air transport (IATA)

Hazard label: Flamm. liquid
Excepted Quantity Code: E1
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y344 - Max. Net Qty/Pkg. 10 L
Passenger and Cargo Aircraft: Pack.Instr. 355 - Max. Net Qty/Pkg. 60 L
Cargo Aircraft only: Pack.Instr. 366 - Max. Net Qty/Pkg. 220 L
Special Provisions: A3 A324
Emergency Response Guide-Code (ERG): 3L

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Germany

Storage class: 3 = Flammable liquids
Water Hazard Class: 1 = slightly hazardous to water (Self-classification (mixture).)
Incident regulation: Richtlinie 2012/18/EU (Seveso III):
Physikalische Gefahren: Ziffer 1.2.5.3 = Code P5c, Mengenschwelle 5 000 000kg / 50 000 000kg
Technical guidance air: 5.2.5, Organic materials:
Concentration: >= 25%
Mass flow rate: 0,5 kg/h
Mass concentration: 50 mg/m³
Information on working limitations: Observe employment restrictions for young people. Observe employment restrictions for expectant or nursing mothers.
Further regulations, limitations and legal requirements: The product is not subject to the Chemicals Prohibition Ordinance (ChemVerbotsV).

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

National regulations - EC member states

Volatile organic compounds (VOC):

approx. 96,1 % by weight

Labelling of packaging with <= 125mL content



Signal word:

Danger

Hazard statements:

H304

May be fatal if swallowed and enters airways.

H413

May cause long lasting harmful effects to aquatic life.

EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P301+P310

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331

Do NOT induce vomiting.

P405

Store locked up.

P501

Dispose of contents/container to hazardous or special waste collection point.

Further regulations, limitations and legal requirements:

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] refer to Germany, 12. BImSchV

Use restriction according to REACH annex XVII, no.: 3, 40, 75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: P5c

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Wording of the H-phrases under paragraph 2 and 3:

H226 = Flammable liquid and vapour.

H304 = May be fatal if swallowed and enters airways.

H413 = May cause long lasting harmful effects to aquatic life.

EUH066 = Repeated exposure may cause skin dryness or cracking.

Reason of change:

Changes in section 1: Details of the supplier of the safety data sheet
General revision

Date of first version:

8.4.2022

Department issuing data sheet:

see section 1: Department responsible for information



Eni metalStanz 4 EP

Material number 719

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 20.3.2024
Version: 10.0
Replaces version: 9.1
Language: en-DE
Date of print: 5.4.2024

Page: 13 of 13

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
Aquatic Chronic: Hazardous to the aquatic environment - chronic
AS/NZS: Australian Standards/New Zealand Standards
Asp. Tox.: Aspiration toxicity
BCF: Bioconcentration Factor
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DIN: German Institute for Standardization
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EL50: Effective loading rate 50%
EN: European Standard
EQ: Excepted quantities
EU: European Union
Flam. Liq.: Flammable liquid
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
LEL: Lower Explosion Limit
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OEL: Occupational Exposure Limit Value
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
TLV: Threshold Limit Value
TRGS: Technical Rules for Hazardous Substances
UN: United Nations
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

Most recent product information is available at:
<http://sumdat.net/23thahan>

