

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Revision date: 04/10/2022 Supersedes: 04/05/2020 Version: 6.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Product form : Mixture Trade name : Eni Grease LP 2 Product code : 4972 : Lubricant grease Type of product : 0410-2022 Formula Product group : Trade product 1.2. Relevant identified uses of the substance or mixture and uses advised against 1.2.1. Relevant identified uses Main use category : Industrial use, Professional use Industrial/Professional use spec Wide dispersive use Use of the substance/mixture Lubricant grease Do not use the product for any purposes that have not been advised by the manufacturer. Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Eni S.p.A., P.Ie E. Mattei 1, 00144 Rom, ITALY, Tel. +39 06 59821, www.eni.com Competent person responsible for the safety data sheet (Reg. EC nr. 1907/2006): SDSInfo@eni.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY, www.oilproducts.eni.com Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0 e-mail: technik.wuerzburg@enilive.com

1.4. Emergency telephone number

Emergency number

: CNIT +39 0382 24444 (24h) (IT + EN)

Poison centre (UK): National Poisons Information Service Edinburgh (24h) (+44) 844 892 0111 0870 600 6266 (UK only) (Source: UN-WHO)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Not classified

Adverse physicochemical, human health and environmental effects

Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May cause an allergic skin reaction. Slightly irritant to eyes. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements

: EUH208 - Contains Amines, C10-14-tert-alkyl. May produce an allergic reaction. EUH210 - Safety data sheet available on request.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2.3. Other hazards (not relevant for classification)	
Other hazards not contributing to the classification	 Combustible product. Thermal decomposition generates toxic vapours. Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. In case of contact with eyes, this product may cause irritation. Ingestion may cause nausea, vomiting and diarrhea. May cause long-term adverse effects in the environment. A potential risk may arise from the release of hydrogen sulfide, when the product is stored or handled at high temperature. Hydrogen sulfide may accumulate in the tanks or other confined spaces, with danger to the workers that enter the spaces. In these cases overexposure to hydrogen sulfide may cause irritation to airways, nausea, dizziness, loss of consciousness and death.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Component	
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated (101316-72-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Residual oils (petroleum,) solvent-refined (64742-01- 4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Component	
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated(101316-72-7)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
Residual oils (petroleum,) solvent-refined(64742-01- 4)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
Distillates (petroleum), hydrotreated heavy paraffinic(64742-54-7)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Notes

: Composition/ Information on ingredients: Mixture of hydrocarbons Thickeners Additives

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated (see note [*], see note [**])	(CAS-No.) 101316-72-7 (EC-No.) 309-877-7 (EC Index-No.) 649-530-00-X (REACH-no) 01-2119489969-06- 0000	50 - 60	Not classified
Residual oils (petroleum,) solvent-refined; Baseoil— unspecified; [A complex combination by hydrocarbons obtained as the solvent insoluble fraction from solvent refining of a residuum using a polar organic solvent such as phenol or furfural. It consists of hydrocarbons having carbon numbers predominantly higher than C25 and boiling above approximately 400°C (752°F).] (see note [*], see note [**])	(CAS-No.) 64742-01-4 (EC-No.) 265-101-6 (EC Index-No.) 649-459-00-4 (REACH-no) 01-2119488707-21	15 - 20	Not classified
Distillates (petroleum), hydrotreated heavy paraffinic (see note [*], see note [**])	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	≥ 2 < 2.5	Asp. Tox. 1, H304
Amines, C10-14-tert-alkyl (Additive)	(EC-No.) 701-175-2 (REACH-no) 01-2119456798-18	< 0,1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=251 mg/kg bodyweight) Acute Tox. 2 (Inhalation:dust,mist), H330 (ATE=0,05 mg/l/4h) Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Notes

: Note [*]:

this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

Note [**]:

substance with occupational exposure limits for some EU countries affecting the category of mineral oils (finely refined mineral base oil mists; see section 8.1)

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	: Remove to fresh air, keep the casualty warm and at rest. If breathing is difficult, give oxygen if possible, or assisted ventilation. Seek medical advice. See also section 4.3.
First-aid measures after skin contact	: Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If skin irritation or rash occurs, get medical advice/attention.
First-aid measures after eye contact	 Rinse immediately with plenty of water. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist.
First-aid measures after ingestion	: Do NOT induce vomiting. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed		
Symptoms/effects after inhalation Symptoms/effects after skin contact	 None under normal conditions at ambient temperatures. Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May cause an allergic skin reaction. 	
Symptoms/effects after eye contact Symptoms/effects after ingestion	 Contact with eyes may cause a light transient irritation. Accidental ingestion of small quantities of the product may cause nausea, discomfort and gastric disturbances. 	
Symptoms/effects upon intravenous administration Chronic symptoms	: No information available. : None known.	

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	Dry chemical, CO2, or water spray or regular foam.Do not use a heavy water stream. Use water stream to cool containers.
5.2. Special hazards arising from the subst	ance or mixture
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. No direct explosion hazard. Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, NOx (harmful/toxic gases). Combustion products include sulphur oxides (SO2 and SO3) and Hydrogen sulphide H2S. LiOx. ZnOx. POx.
5.3. Advice for firefighters	
Firefighting instructions Special protective equipment for firefighters	 Shut off source of product, if possible. Move undamaged containers from immediate hazard area if it can be done safely. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area. Personal protection equipment for firefighters (see also sect. 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure
Other information	 mode. EN 443. EN 469. EN 659. In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

SECTION 6: Accidental releas	e measures
6.1. Personal precautions, protec	tive equipment and emergency procedures
General measures	: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid direct contact with released material. Avoid accidental sprays on hot surfaces or electrical contacts. Keep upwind. Spill area may be slippery.
6.1.1. For non-emergency personnel	
Protective equipment Emergency procedures	 See Section 8. Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Personal protective equipment Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory
	protection: A half or full-face respirator with filter(s) for organic vapours (A) (or A+B when applicable for H2S), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. A Self Contained
	Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
Emergency procedures	: Notify local authorities according to relevant regulations.

6.2. Environmental precautions

Prevent product from entering sewers, rivers or other bodies of water. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

For containment	: Collect free product with suitable mechanical means. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
Methods for cleaning up	: Wash contaminated area with large amounts of water.
Other information	: Recommended measures are based on the most likely spillage scenarios for this material however, local conditions (wind, air temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and stora	age
7.1. Precautions for safe handling	
Precautions for safe handling Hygiene measures	 This material is combustible, but will not ignite readily. Keep away from heat/sparks/open flames/hot surfaces. Avoid contact with skin, eyes and clothing. Do not use compressed air for filling, discharging, or handling operations. Use and store only outdoors or in a well-ventilated area. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. Ensure that proper housekeeping measures are in place. Do not breathe fume/ mist/
	vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Separate working clothes from town clothes. Launder separately.
7.2. Conditions for safe storage, in	cluding any incompatibilities
Storage conditions	: Store in dry, well ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not smoke.

	and other ignition sources. No smoking. Do not smoke.
Incompatible products	: Keep away from: strong oxidants.
Storage temperature	: < 50 °C

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Storage area	: Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.
Packages and containers:	: If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.
Packaging materials	: For containers, or container linings use materials specifically approved for use with this product.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Lubricating oils (petroleum), C24-50, solvent-	extd., dewaxed, hydrogenated (101316-72-7)	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KTV (OEL STEL)	3 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

the solvent insoluble fraction from solvent re	seoil— unspecified; [A complex combination by hydrocarbons obtained as fining of a residuum using a polar organic solvent such as phenol or arbon numbers predominantly higher than C25 and boiling above	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KTV (OEL STEL)	3 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits	·	
WEL TWA (OEL TWA) [1]	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KTV (OEL STEL)	3 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Eni Grease LP 2	
DNEL/DMEL (additional information)	
Additional information	Not applicable
PNEC (additional information)	
Additional information	Not applicable

Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated (101316-72-7)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0,97 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2,73 mg/m ³	
Long-term - local effects, inhalation	5,58 mg/m ³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0,74 mg/kg bodyweight/day	
PNEC (Oral)		

PNEC oral (secondary poisoning)	9,33 mg/kg food

Residual oils (petroleum,) solvent-refined; Baseoil— unspecified; [A complex combination by hydrocarbons obtained as the solvent insoluble fraction from solvent refining of a residuum using a polar organic solvent such as phenol or furfural. It consists of hydrocarbons having carbon numbers predominantly higher than C25 and boiling above approximately 400°C (752°F).] (64742-01-4)

DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0,97 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2,73 mg/m³	
Long-term - local effects, inhalation	5,58 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0,74 mg/kg bodyweight/day	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Long-term - local effects, inhalation	1,19 mg/m³
PNEC (Oral)	
PNEC oral (secondary poisoning)	9,33 mg/kg food

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	1 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2,7 mg/m³	
Long-term - local effects, inhalation	5,6 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0,74 mg/kg bodyweight/day	
Long-term - local effects, inhalation	1,2 mg/m³/day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
PNEC (Oral)		
PNEC oral (secondary poisoning)	9,33 mg/kg food	

Amines, C10-14-tert-alkyl		
DNEL/DMEL (Workers)		
Long-term - systemic effects, inhalation	12,5 mg/m³	
Long-term - local effects, inhalation	12,1 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0,35 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2,5 mg/m³	
Long-term - local effects, inhalation	1,2 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0,001 mg/l	
PNEC aqua (marine water)	0,0001 mg/l	
PNEC aqua (intermittent, freshwater)	0,004 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	2,14 mg/kg dwt	
PNEC sediment (marine water)	0,214 mg/kg dwt	
PNEC (Soil)	PNEC (Soil)	
PNEC soil	0,428 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	4,71 mg/kg food	
PNEC (STP)		
PNEC sewage treatment plant	0,635 mg/l	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

 Note
 : The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Minimize exposure to mists/vapours/aerosol. Before entering storage tanks and commencing any operation in a confined area, carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds.

8.2.2. Personal protection equipment

Personal protective equipment (for industrial or professional use):

Gloves. Protective clothing. Safety glasses. Safety shoes or boots.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. DIN EN 166

8.2.2.2. Skin protection

Skin and body protection:

Non-skid safety shoes or boots, chemical resistant.

Hand protection:

Protective gloves. Adequate materials: nitrile (NBR) or neoprene with a protection index \geq 5 (permeation time \geq 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.

Other skin protection

Materials for protective clothing:

Protective apron. DIN EN 465. DIN EN 466

8.2.2.3. Respiratory protection

Respiratory protection:

Not necessary with sufficient ventilation. In case of insufficient ventilation, wear suitable respiratory equipment (EN 136/140/145). Combination filter device (DIN EN 141). Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H2S) or self-contained breathing apparatus (SCBA). (EN 136/140/145)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

8.2.2.4. Thermal hazards

Thermal hazard protection:

None in normal use conditions.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Do not discharge the product into the environment. Prevent discharge of undissolved substance to or recover from onsite wastewater. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Consumer exposure controls:

Not applicable.

SECTION 9: Physical and chemical properties			
9.1. Information on basic physical and	9.1. Information on basic physical and chemical properties		
Physical state	: Solid		
Colour	: Not available		
Appearance	: Soft paste. Slightly hazy.		
Odour	: characteristic.		
Odour threshold	: There are no data available on the preparation/mixture itself.		
Melting point	: > 150 °C (Pour point) (ASTM D 97)		
Freezing point	: ≈ 0 °C (CAS 101316-72-7)		
Boiling point	: > 250 °C (CAS 101316-72-7)		
Flammability	: Not flammable		
Explosive properties	: None (according to composition).		
Oxidising properties	: None (according to composition).		
Explosive limits	: Not applicable		
	Not determined		
Lower explosive limit (LEL)	: Not determined		
Upper explosive limit (UEL)	: Not determined		
Flash point	: > 230 °C (base oil) (ASTM D 445)		
Auto-ignition temperature	: > 300 °C (CAS 101316-72-7)		
Decomposition temperature	: Not determined		
рН	: There are no data available on the preparation/mixture itself.		
pH solution	: Not available		
Viscosity, kinematic	: 160 mm ² /s (40°C, base oil) (ASTM D 445)		
Solubility	: Water: Immiscible and insoluble		
Log Kow	: Not applicable for mixtures		
Log Pow	: Not applicable for mixtures		
Vapour pressure	: < 0,1 hPa (20°C, CAS 101316-72-7)		
Vapour pressure at 50 °C	: Not determined		
Density	: 0,9 kg/l 15°C (ASTM D 1298)		
Relative density	: Not determined		
Relative vapour density at 20 °C	: Not determined		
Particle size	: Not available		
Particle size distribution	: Not available		
Particle shape	: Not available		
Particle aspect ratio	: Not available		
Particle aggregation state	: Not available		
Particle agglomeration state	: Not available		
Particle specific surface area	: Not available		
Particle dustiness	: Not available		

9.2.1. Information with regard to physical hazard classes		
Critical temperature	: Not applicable for mixtures	
9.2.2. Other safety characteristics		
Penetration	: 280 dmm ((25°C) (ASTM D 217), Class NLGI: 2)	
Drop point / drop range	: 185°C (ASTM D 566)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

10.2. Chemical stability

Stable product, according to its intrinsic properties (in normal conditions of storage and handling).

10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling).

10.4. Conditions to avoid

None in normal conditions.

10.5. Incompatible materials

Strong oxidants.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : Toxic fumes. This product contains sulfur compounds which, in certain circumstances, may generate hydrogen sulfide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition)

Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated (101316-72-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (API 1986, UBTL 1984 - OECD 402)
LC50 Inhalation - Rat	2,18 – 5,53 mg/l/4h (API 1987, Exxon Biomedical Sciences, Inc. 1988, BioResearch Laboratories, Ltd. 1984 - OECD 403)

Residual oils (petroleum,) solvent-refined; Baseoil— unspecified; [A complex combination by hydrocarbons obtained as the solvent insoluble fraction from solvent refining of a residuum using a polar organic solvent such as phenol or furfural. It consists of hydrocarbons having carbon numbers predominantly higher than C25 and boiling above approximately 400°C (752°F).] (64742-01-4)

LD50 oral rat	5000 mg/kg bodyweight
LD50 dermal rat	2000 – 5000 mg/kg bodyweight
LC50 Inhalation - Rat	2,18 – 5,53 mg/l/4h

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

612 mg/kg bodyweight (OECD 401)
251 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), 95% CL: 190 - 322
1,19 mg/l/4h (OECD 403)
: Not classified (Based on available data, the classification criteria are not met) pH: There are no data available on the preparation/mixture itself.
 (according to composition) Not classified (Based on available data, the classification criteria are not met) pH: There are no data available on the preparation/mixture itself.
: (according to composition)
 Not classified (Based on available data, the classification criteria are not met) (according to composition)
Contains a sensitizer 1A (Amines, C10-14-tert-alkyl). Amount contained in the product: 0,0 ÷ 0,099 % m/m max. May cause an allergic skin reaction.
: Not classified (Based on available data, the classification criteria are not met)
: (according to composition)
: Not classified (Based on available data, the classification criteria are not met)
 : (according to composition) This product contains : Lubricating oils (petroleum), C24-50, solvent-extd, dewaxed, hydrogenated; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by solvent extraction and hydrogenation of atmospheric distillation residues. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C24 through C50 and produces a finished oil with a viscosity in the order of 16cSt to 75cSt at 40 °C (104 °F).], Residual oils (petroleum) solvent-refined; Baseoil— unspecified; [A complex combination by hydrocarbons obtained as the solvent insoluble fraction from solvent refinin of a residuum using a polar organic solvent such as phenol or furfural. It consists of hydrocarbons having carbon numbers predominantly higher than C25 and boiling above approximately 400°C (752°F).], Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.
 Not classified (Based on available data, the classification criteria are not met) (according to composition)
 Not classified (Based on available data, the classification criteria are not met) (according to composition)
May cause respiratory irritation.
 Not classified (Based on available data, the classification criteria are not met) (according to composition)
solvent-extd., dewaxed, hydrogenated (101316-72-7)
125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

NOAEL (dermal, rat/rabbit, 90 days)	1000 – 2000 mg/kg bodyweight/day (API 1986, Mobil Environmental and Health Science Laboratory 1983 - OECD 410)
NOAEC (inhalation,rat, vapour, 90 days)	220 – 1500 mg/m³ (Exxon Biomedical Sciences, Inc. 1991, Dalbey W, Osimitz T, Kommineni C, Roy T, Feuston M and Yang J 1991 - OECD 412)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	 > 0,98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)

Amines, C10-14-tert-alkyl	
NOAEL (oral, rat, 90 days)	20 mg/kg bodyweight/day (21-28d) (OECD 410)
NOAEC (inhalation,rat, vapour, 90 days)	19 mg/m³ (28d) (OECD 412)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

Additional information	: (according to composition)
Eni Grease LP 2	

Viscosity, kinematic	160 mm²/s (40°C, base oil) (ASTM D 445)
11.2. Information on other hazards	
11.2.1. Endocrine disrupting properties	
Adverse health effects caused by endocrine disrupting properties	: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %
11.2.2 Other information	
Potential adverse human health effects and symptoms	: Contact with eyes may cause temporary reddening and irritation, Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, May cause an allergic skin reaction, Irritation: may cause irritation to the respiratory system
Other information	: None

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment.
Ecology - water Hazardous to the aquatic environment, short-term (acute)	This product is not soluble in water. It floats on water and forms a film on the surface.Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met)

Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated (101316-72-7)	
LC50 fish 1	> 100 mg/l (LL 50, Exxon 1995 - OECD 203)
EC50 Daphnia 1	> 10000 mg/l (WAF, 48 h, Shell 1988 - OECD 202)
NOEC (acute)	≥ 100 mg/l (Pseudokirchneriella subcapitata, 72h, OECD 201 - Petro-Canada 2008)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

NOEC chronic fish	≥ 1000 mg/l (Oncorhynchus mykiss, NOELR, 14d - QSAR, Redman, A. et al. 2010)
NOEC chronic crustacea	≥ 1000 mg/l (21d, OECD 211 - Shell 1994)

Residual oils (petroleum,) solvent-refined (64742-01-4)	
LC50 fish 1	100 mg/l
EC50 Daphnia 1	10 g/l

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

Amines, C10-14-tert-alkyl	
LC50 fish 1	1,3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 Daphnia 1	0,24 – 6 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	0,44 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC chronic fish	0,078 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '96 d'

12.2. Persistence and degradability

Eni Grease LP 2	
Persistence and degradability	A fraction of the constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.

Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated (101316-72-7)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.

Residual oils (petroleum,) solvent-refined (64742-01-4)	
Persistence and degradability	Substance is complex UVCB. The test methods for this endpoint are not applicable to UVCB substances.

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.

Persistence and degradability Readily biodegradable.	Amines, C10-14-tert-alkyl	
	Persistence and degradability	Readily biodegradable.
Biodegradation 21,8 % (28d) (OECD 301D)	Biodegradation	21,8 % (28d) (OECD 301D)

12.3. Bioaccumulative potential	
Eni Grease LP 2	
Log Pow	Not applicable for mixtures

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Log Kow	Not applicable for mixtures
	Not established. According to the characteristics of the components, the product has a low biodegradability in anaerobic conditions, and may be persistent. Some of the chemical compounds that are present in the product have a potential for bioaccumulation, and may be harmful to aquatic organisms.

Lubricating oils (petroleum), C24-50, solvent-	extd., dewaxed, hydrogenated (101316-72-7)
Bioaccumulative potential	The test methods for this endpoint are not applicable to UVCB substances.

Residual oils (petroleum,) solvent-refined (64	742-01-4)
Bioaccumulative potential	The test methods for this endpoint are not applicable to UVCB substances.

Amines, C10-14-tert-alkyl	
Log Pow	2,9
Bioaccumulative potential	Low bioaccumulation potential.
12.4. Mobility in soil	
Eni Grease LP 2	
Ecology - soil	Product adsorbs onto the soil.

Lubricating oils (petroleum), C24-50, solvent-	extd., dewaxed, hydrogenated (101316-72-7)
Ecology - soil	The test methods for this endpoint are not applicable to UVCB substances.

Residual oils (petroleum,) solvent-refined (64)	742-01-4)
Ecology - soil	The test methods for this endpoint are not applicable to UVCB substances.

12.5. Results of PBT and vPvB assessment

Eni Grease LP 2	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria	a of REACH regulation, annex XIII
Results of PBT-vPvB assessment	The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)

Component	
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated (101316-72-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Residual oils (petroleum,) solvent-refined (64742-01- 4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
12.6. Endocrine disrupting properties	
Adverse effects on the environment caused by endocrine disrupting properties	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %
12.7. Other adverse effects	
Other adverse effects : Additional information :	None No other effects known
SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Waste treatment methods :	Do not dispose of the product, either new or used, by discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector.
Sewage disposal recommendations :	Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Dispose of in a safe manner in accordance with local/national regulations.
Product/Packaging disposal recommendations :	European Waste Catalogue code(s) (Decision 2001/118/CE): 13 08 99* (oil wastes not otherwise specified - wastes not otherwise specified). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.
Additional information :	Empty containers may contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been cleaned, and declared safe.

Ecology - waste materials EURAL code (EWC)

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number or ID n	umber			
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping	g name			
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard o	lass(es)	·		
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group		·		
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental haz	ards	·		
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
None.				

: The product as it is does not contain halogenated substances.

: 13 08 99* - wastes not otherwise specified

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

14.6. Special precautions for user

Overland transport Not regulated Transport by sea Not regulated Air transport Not regulated Inland waterway transport Not regulated Rail transport Not regulated

14.7. Maritime transport in bulk according to IMO instruments

IBC code

: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following res	trictions are applicable according to Annex XV	/II of the REACH Regulation (EC) No 1907/2006:
Reference code	Applicable on	Entry title or description
3(b)	Amines, C10-14-tert-alkyl ; Distillates (petroleum), hydrotreated heavy paraffinic	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Amines, C10-14-tert-alkyl	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Other information, restriction and prohibition regulations

: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances (ODP). Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC. Regulation EU (649/2012) - Export and Import of hazardous chemicals (PIC).

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE). Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

France

fats of mineral or synthetic origin Employment prohibitions or restrictions on the protection of young people at work according to § 22 JArbSchG in the case of formation of hazardous substances have to be observed. WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1) Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) Is not subject of the Hazardous Incident Ordinance (12. BImSchV) TRGS 400: Hazard assessment for activities involving Hazardous Substances
Employment prohibitions or restrictions on the protection of young people at work according to § 22 JArbSchG in the case of formation of hazardous substances have to be observed. WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1) Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) Is not subject of the Hazardous Incident Ordinance (12. BImSchV)
Employment prohibitions or restrictions on the protection of young people at work according to § 22 JArbSchG in the case of formation of hazardous substances have to be observed. WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1) Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) Is not subject of the Hazardous Incident Ordinance (12. BImSchV)
to § 22 JArbSchG in the case of formation of hazardous substances have to be observed. WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1) Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) Is not subject of the Hazardous Incident Ordinance (12. BImSchV)
to § 22 JArbSchG in the case of formation of hazardous substances have to be observed. WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1) Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) Is not subject of the Hazardous Incident Ordinance (12. BImSchV)
Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) Is not subject of the Hazardous Incident Ordinance (12. BImSchV)
wassergefährdender Stoffe (VwVwS) Is not subject of the Hazardous Incident Ordinance (12. BImSchV)
TRGS 400: Hazard assessment for activities involving Hazardous Substances
TRGS 401: Risks resulting from skin contact - identification, assessment, measures TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous Substances: Inhalation Exposure TRGS 555: Working instruction and information for workers TRGS 900: Occupational Exposure Limits TRGS 800: Fire protection measures TRGS 905: List of mutagenic, carcinogenic or teratogenic substances LGK 11 - Combustible solids
Not applicable.
C - Minimize discharge
None of the components are listed
Pregnant/breastfeeding women working with the product must not be in direct contact with it

15.2. Chemical safety assessment

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP] No chemical safety assessment has been carried out

A chemical safety assessment has been carried out for the following components of this mixture:

Residual oils (petroleum,) solvent-refined; Baseoil— unspecified; [A complex combination by hydrocarbons obtained as the solvent insoluble fraction from solvent refining of a residuum using a polar organic solvent such as phenol or furfural. It consists of hydrocarbons having carbon numbers predominantly higher than C25 and boiling above approximately 400°C (752°F).] Amines, C10-14-tert-alkyl Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated

Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated Distillates (petroleum), hydrotreated heavy paraffinic

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Notes
	Flammability (solid, gas)	Modified	
	Adverse health effects caused by endocrine disrupting properties	Added	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

	Adverse effects on the environment caused by endocrine disrupting properties	Added	
	SDS EU format according to COMMISSION REGULATION (EU) 2020/878		
1.1	Formula	Modified	
3	Composition/information on ingredients	Modified	

Abbreviations and acronyn	ns:
	Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.
	N/A = not applicable
	N/D = not available
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Effective concentration for 50 percent of test population (median effective concentration)
IARC	International Agency for Research on Cancer
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)
LD50	Lethal dose for 50 percent of test population (median lethal dose)
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways
SDS	Safety Data Sheet
STP	Sewage treatment plant
vPvB	Very Persistent and Very Bioaccumulative

Data sources

: This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Training advice	: Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.
Other information	: Do not use the product for any purposes that have not been advised by the manufacturer. In exceptional cases (i.e prolunged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. This situation is especially relevant for those operations which involve direct exposure to the vapours in the interior of tanks or other confined spaces. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

Full text of H- and EUH-statements:		
Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B	
Skin Sens. 1A	Skin sensitisation, category 1A	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H311	Toxic in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H330	Fatal if inhaled.	
H335	May cause respiratory irritation.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
EUH208	Contains Amines, C10-14-tert-alkyl. May produce an allergic reaction.	
EUH210	Safety data sheet available on request.	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.