SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Eni aquamet TF

UFI: 6M60-40Y5-700Y-SW0V

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Metalworking fluid

1.3 Details of the supplier of the safety data sheet

Company name: Eni Schmiertechnik GmbH
Street/POB-No.: Paradiesstraße 14
Postal Code, city: 97080 Würzburg
Germany
WWW: www.enischmiertechnik.de
E-mail: info.wuerzburg@eni.com
Telephone: +49 (0)931-90098-0
Telefax: +49 (0)931-98442

Department responsible for information:
Application Engineering & Product Management (AEPM)
Telephone: +49 (0)931-90098-0
E-mail: technik.wuerzburg@eni.com

1.4 Emergency telephone number

GIZ-Nord, Göttingen
Telephone: +49 (0)551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Eye Dam. 1; H318 Causes serious eye damage.

2.2 Label elements

Labelling (CLP)



Signal word: **Danger**

Hazard statements:	H318	Causes serious eye damage.
Precautionary statements:	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P264	Wash hands and face thoroughly after handling.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P310	Immediately call a POISON CENTER/doctor.

Special labelling

Text for labelling: Contains 2-Phenoxyethanol.

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.
The product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: A mixture of base oils and additives.

Hazardous ingredients:

Identifiers	Designation Classification	Content
REACH 01-2119527859-22-xxxx EC No. 271-781-5 CAS 68608-26-4	Sulfonic acids, petroleum, sodium salts Eye Irrit. 2; H319.	5 - 10 %
REACH 01-2119488943-21-xxxx EC No. 204-589-7 CAS 122-99-6	2-Phenoxyethanol Acute Tox. 4; H302. Eye Dam. 1; H318. STOT SE 3; H335. Acute toxicity estimate (ATE): Oral: 1394 mg/kg bw.	5 - 10 %
EC No. 222-720-6 CAS 3586-55-8	(Ethylenedioxy)dimethanol Acute Tox. 4; H302. Skin Irrit. 2; H315. Eye Dam. 1; H318.	1 - 3 %

Full text of H- and EUH-statements: see section 16.

Additional information: The highly refined mineral oil contains <3% (w/w) DMSO extract, according to IP346.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: If medical advice is needed, have product container or label at hand.
Take off contaminated clothing and wash it before reuse.

In case of inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Where appropriate artificial ventilation. Seek medical attention if problems persist.

Following skin contact: Immediately clean with water and soap followed by thorough rinsing. In case of skin reactions, consult a physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently seek the immediate attention of an ophthalmologist.

After swallowing: Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Immediately get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Water spray jet, water mist, foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:
Full water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Nitrogen oxides (NOx), carbon monoxide and carbon dioxide, smoke, traces of incompletely burned carbon compounds.

5.3 Advice for firefighters

Special protective equipment for firefighters:
Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:
Do not inhale explosion and combustion gases.
Use fine water spray to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely.
Do not allow water used to extinguish fire to enter drains, ground or waterways.
Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe mist/vapours/spray. Avoid contact with the substance.
Provide adequate ventilation.
Keep unprotected people away.
Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Do not allow to enter into soil/subsoil.
If necessary notify appropriate authorities.

6.3 Methods and material for containment and cleaning up

Make sure spills can be contained, e.g. in sump pallets or kerbed areas. Prevent spread over a wide area (e.g. by containment or oil barriers).
Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents) and place in closed containers for disposal.
Never return spills in original containers for re-use.

Additional information: Special danger of slipping by leaking/spilling product.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling:
Provide adequate ventilation, and local exhaust as needed. Do not breathe mist/vapours/spray.
Avoid contact with the substance. Wear appropriate protective equipment.
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.
Take off contaminated clothing and wash it before reuse.
Wash hands before breaks and after work.
Have eye wash bottle or eye rinse ready at work place. When handling large quantities, supply emergency spray.

Precautions against fire and explosion:

Only use the material in places where open light, fire and other flammable sources can be kept away. Take precautionary measures against static discharges.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed in a cool, well-ventilated place.
Keep container dry. Keep only in the original container.
Protect against heat, sun rays and frost.
storage temperature: 5 - 40 °C (Shelf life: 12 months)

Hints on joint storage:

Do not store together with: strong oxidizing agents.
Keep away from food, drink and animal feedingstuffs.

Storage class:

10 = Combustible liquids, unless storage class 3

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
122-99-6	2-Phenoxyethanol	Germany: TRGS 900 Kurzzeit	5,7 mg/m³; 1 ppm (Aerosol and vapour)
		Germany: TRGS 900 Langzeit	5,7 mg/m³; 1 ppm (Aerosol and vapour)
3586-55-8	(Ethylenedioxy)dimethanol	Germany: DFG Kurzzeit	1,52 mg/m³; 0,3 ppm
		Germany: DFG Langzeit	0,76 mg/m³; 0,15 ppm

DNEL/DMEL:

Information about 2-Phenoxyethanol:
DNEL workers, dermal, long-term, systemic: 20,83 mg/m³
DNEL workers, inhalative, long-term, systemic: 5,7 mg/m³

PNEC:

Information about 2-Phenoxyethanol:
PNEC water (freshwater): 0,943 mg/L
PNEC water (marine water): 0,0943 mg/L
PNEC sediment (freshwater): 7,237 mg/Kg dw
PNEC STP: 36 mg/L

8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

Personal protection equipment

Occupational exposure controls

Respiratory protection:

Respiratory protection must be worn whenever the WEL levels have been exceeded.
The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product.

Hand protection:

Protective gloves according to DIN EN 374.

permanent contact:
Glove material: Nitrile rubber, polychloroprene
Layer thickness: 0,7 mm
Breakthrough time: > 480 min

During splash contact:
Glove material: Nitrile rubber, polychloroprene
Layer thickness: 0,40 mm
Breakthrough time: > 30 min

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to DIN EN ISO 16321-1:2022.

Body protection: Wear suitable protective clothing.

General protection and hygiene measures:
Do not breathe mist/vapours/spray. Avoid contact with the substance. Do not get in eyes, on skin, or on clothing.
Take off contaminated clothing and wash it before reuse.
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.
Have eye wash bottle or eye rinse ready at work place. When handling large quantities, supply emergency spray.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa	liquid
Colour:	brown
Odour:	Mineral oil
Odour threshold:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	> 100 °C
Flammability:	No data available
Upper/lower flammability or explosive limits:	LEL (Lower Explosion Limit): 0,60 Vol-% UEL (Upper Explosive Limit): 6,50 Vol-%
Flash point/flash point range:	> 130 °C (DIN EN ISO 2592)
Auto-ignition temperature:	> 240 °C
Decomposition temperature:	No data available
pH:	at 20 °C, 10%: 9,0 - 9,2 (DIN 51369)
Viscosity, kinematic:	at 20 °C: approx. 150 mm²/s (DIN EN ISO 3104)
Water solubility:	at 20 °C: Miscible
Partition coefficient: n-octanol/water:	Not applicable
Vapour pressure:	No data available
Density:	at 15 °C: 0,95 g/mL (DIN EN ISO 12185)
Vapour density:	No data available
Particle characteristics:	Not applicable

9.2 Other information

Explosive properties:	No data available
Oxidizing characteristics:	No data available
Auto-ignition temperature:	No data available
Evaporation rate:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Refer to subsection "Possilbility of hazardous reactions".

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

Keep away from heat sources, sparks and open flames.
Protect from direct sunlight.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used properly.

Thermal decomposition: No data available

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Eye Dam. 1; H318 = Causes serious eye damage.

Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.

Skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties: No data available

Other information: Information about baseoil:
LD50 Rat, oral: > 5.000 mg/kg bw
LD50 Rabbit, dermal: > 2.000 mg/kg bw
LC50 Rat, inhalative: > 5,53 mg/L/4h

Symptoms

After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Information about baseoil:
Fish toxicity:
LC50: > 100 mg/L/96h

Water Hazard Class: 3 = highly hazardous to water (Self-classification (mixture).)

12.2 Persistence and degradability

Further details: Abiotic degradation: Poorly eliminated from water.

Biodegradation (main component): Evidence for inherent biodegradability.

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient: n-octanol/water:

Not applicable

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

The product does not contain any substances classified as PBT or vPvB.

12.6 Endocrine disrupting properties

None

12.7 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 12 01 07* = Mineral-based machining oils free of halogens (except emulsions and solutions)
* = Evidence for disposal must be provided.

Recommendation: Emulsion: Waste key number 12 01 09* = Machining emulsions and solutions free of halogens

Dispose of waste according to applicable legislation.

Package

Recommendation: Dispose of waste according to applicable legislation.
Handle contaminated packages in the same way as the substance itself.
Empty containers may contain flammable product residues. Do not cut, weld, bore, burn or incinerate emptied containers unless they have been cleaned and declared safe. Empty containers should be disposed of in accordance with local regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID, ADN, IMDG, IATA-DGR:

not applicable

14.2 UN proper shipping name

ADR/RID, ADN, IMDG, IATA-DGR:

Not restricted

14.3 Transport hazard class(es)

ADR/RID, ADN, IMDG, IATA-DGR:

not applicable

14.4 Packing group

ADR/RID, ADN, IMDG, IATA-DGR:

not applicable

14.5 Environmental hazards

Dangerous for the environment: Substance/mixture is not environmentally hazardous according to the criteria of the UN model regulations.

Marine pollutant - IMDG: no

14.6 Special precautions for user

No dangerous good in sense of these transport regulations.

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Germany

Storage class: 10 = Combustible liquids, unless storage class 3

Water Hazard Class: 3 = highly hazardous to water (Self-classification (mixture).)

Technical guidance air: 5.2.5

Information on working limitations:

Observe employment restrictions for young people.

Further regulations, limitations and legal requirements:

The product is not subject to the Chemicals Prohibition Ordinance (ChemVerbotsV).

National regulations - EC member states

Volatile organic compounds (VOC):

0 % by weight

Further regulations, limitations and legal requirements:

Use restriction according to REACH annex XVII, no.: 3, 75.

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Wording of the H-phrases under paragraph 2 and 3:

H302 = Harmful if swallowed.
H315 = Causes skin irritation.
H318 = Causes serious eye damage.
H319 = Causes serious eye irritation.
H335 = May cause respiratory irritation.

Reason of change: Changes in section 9: Physical and chemical properties
Changes in section 12: Ecological information
Changes in section 15: Regulatory information

Date of first version: 24.10.2022

Department issuing data sheet: see section 1: Department responsible for information

Abbreviations and acronyms:
Acute Tox.: Acute toxicity
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
AS/NZS: Australian Standards/New Zealand Standards
Bw: Body weight
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EN: European Standard
EQ: Excepted quantities
EU: European Union
Eye Dam.: Eye damage
Eye Irrit.: Eye irritation
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
LC50: Median lethal concentration
LD50: Lethal dose 50%
LEL: Lower Explosion Limit
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OEL: Occupational Exposure Limit Value
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
Skin Irrit.: Skin irritation
STOT SE: Specific target organ toxicity - single exposure
STP: Sewage Treatment Plant
TLV: Threshold Limit Value
TRGS: Technical Rules for Hazardous Substances
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

Most recent product information is available at
http://sumdat.net/0rfw7490