



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Eni metalCut WUS G 201

Material number 651

Revision date: 10.2.2023

Version: 2.1

Replaces version: 2.0

Language: en-DE

Date of print: 20.2.2023

Page: 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Eni metalCut WUS G 201

UFI: 7M30-E0T8-H00N-MXMM

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Metalworking fluid

1.3 Details of the supplier of the safety data sheet

Company name: Eni Schmiertechnik GmbH

Street/POB-No.: Paradiesstraße 14

Postal Code, city: DE-97080 Würzburg

WWW: www.enischmiertechnik.de

E-mail: info.wuerzburg@eni.com

Telephone: +49 (0)931-90098-0

Telefax: +49 (0)931-98442

Department responsible for information:

Application Engineering & Product Management (AEPM)

Telephone: +49 (0)931-90098-0

E-mail: technik.wuerzburg@eni.com

1.4 Emergency telephone number

GIZ-Nord, Göttingen

Telephone: +49 (0)551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Eye Irrit. 2; H319 Causes serious eye irritation.

Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (CLP)



Signal word: **Danger**

Hazard statements: H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Eni metalCut WUS G 201

Material number 651

Revision date: 10.2.2023

Version: 2.1

Replaces version: 2.0

Language: en-DE

Date of print: 20.2.2023

Page: 2 of 10

Precautionary statements:	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P280	Wear protective gloves/protective clothing/eye protection.
	P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P331	Do NOT induce vomiting.
	P501	Dispose of contents/container to hazardous or special waste collection point.

Special labelling

EUH208	Contains reaction mass of N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine. May produce an allergic reaction.
--------	--

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

CAS No.	Designation	PBT/vPvB	ED Human	ED Environment
128-37-0	3,5-Di-tert-butyl-4-hydroxytoluene		List II	

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Hazardous ingredients:

Identifiers	Designation Classification	Content
REACH 01-0000020163-82-xxxx EC No. 482-220-0 CAS 848301-69-9	C18-C50 branched, cyclic and linear hydrocarbons – Distillates Asp. Tox. 1; H304.	< 80 %
EC No. 270-478-5 CAS 68442-22-8	Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts Skin Irrit. 2; H315. Eye Dam. 1; H318. Aquatic Chronic 2; H411.	< 3 %
REACH 01-2119565113-46-xxxx EC No. 204-881-4 CAS 128-37-0	3,5-Di-tert-butyl-4-hydroxytoluene Acute Tox. 4; H302. Aquatic Acute 1; H400. Aquatic Chronic 1; H410.	< 0,5 %
REACH 01-2119982395-25-xxxx list no. 939-700-4	reaction mass of N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine Skin Irrit. 2; H315. Skin Sens. 1B; H317. Aquatic Acute 1; H400. Aquatic Chronic 2; H411.	0,1 - 0,5 %

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:	In all cases of doubt, or when symptoms persist, seek medical advice. If medical advice is needed, have product container or label at hand. Take off contaminated clothing and wash it before reuse.
----------------------	--



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Eni metalCut WUS G 201

Material number 651

Revision date: 10.2.2023

Version: 2.1

Replaces version: 2.0

Language: en-DE

Date of print: 20.2.2023

Page: 3 of 10

In case of inhalation:	Remove casualty to fresh air and keep warm and at rest. In case of respiratory tract irritation, consult a physician.
Following skin contact:	Immediately clean with water and soap followed by thorough rinsing. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.
After swallowing:	Do NOT induce vomiting. Rinse mouth with water. Never give anything by mouth to an unconscious person. Seek medical attention. Observe risk of aspiration if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. May be fatal if swallowed and enters airways. May cause allergic reactions in already sensitized persons.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Water spray jet, water mist, foam, extinguishing powder, carbon dioxide

Extinguishing media which must not be used for safety reasons:

Full water jet

5.2 Special hazards arising from the substance or mixture

May form dangerous gases and vapours in case of fire.

Furthermore, there may develop: Nitrogen oxides (NO_x), Acrolein, traces of incompletely burned carbon compounds, carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. Cool endangered containers with water jetspray. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear appropriate protective equipment. Provide adequate ventilation. Use a breathing protection against vapours/aerosol. Avoid contact with skin, eyes and clothes.

Vapours can form explosive mixtures with air. Remove all sources of ignition. Keep unprotected people away.

Stop leak if safe to do so.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains.

If necessary notify appropriate authorities.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents) and place in closed containers for disposal. Ventilate affected area. Clean contaminated objects and areas thoroughly observing environmental regulations.

Additional information:

Special danger of slipping by leaking/spilling product.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Eni metalCut WUS G 201

Material number 651

Revision date: 10.2.2023

Version: 2.1

Replaces version: 2.0

Language: en-DE

Date of print: 20.2.2023

Page: 4 of 10

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Put lids on containers immediately after use. Wear appropriate protective equipment. Avoid breathing mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Have eye wash bottle or eye rinse ready at work place. Use only antistatically equipped (spark-free) tools.

Precautions against fire and explosion:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Store container tightly closed in a dry and cool place. Keep only in the original container. Protect from frost, heat and sunlight.

storage temperature: 5 - 40 °C

storage stability: Average shelf life of 24 months.

Hints on joint storage:

Do not store together with Oxidising agent. Keep away from food, drink and animal feedingstuffs.

Storage class:

10 = Combustible liquids, unless storage class 3

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
128-37-0	3,5-Di-tert-butyl-4-hydroxytoluene	Germany: TRGS 900 Kurzzeit	40 mg/m ³ (Aerosol and vapour, inhalable fraction)
		Germany: TRGS 900 Langzeit	10 mg/m ³ (Aerosol and vapour, inhalable fraction)

DNEL/DMEL:

Information about 3,5-Di-tert-butyl-4-hydroxytoluene

DNEL, long-term, workers, inhalative, systemic: 1,76 mg/m³

DNEL, long-term, consumer, inhalative, systemic: 0,435 mg/m³

DNEL, long-term, workers, dermal, systemic: 0,5 mg/m³

DNEL, long-term, consumer, dermal, systemic: 0,25 mg/m³

DNEL, long-term, workers, oral, systemic: 0,25 mg/m³

DNEL, long-term, consumer, oral, systemic: 0,25 mg/m³

NOAEL, long-term, consumer, inhalative, systemic: 25 mg/kg/bw/d

NOAEC, long-term, consumer, inhalative, systemic: 10,87 mg/m³

NOAEL, long-term, workers, inhalative, systemic: 25 mg/kg/bw/d

NOAEC, long-term, workers, inhalative, systemic: 22,04 mg/m³

NOAEL, long-term, workers, dermal, systemic: 25 mg/kg/bw/d

NOAEL, long-term, consumer, dermal, systemic: 25 mg/kg/bw/d

NOAEL, long-term, workers, oral, systemic: 25 mg/kg/bw/d

NOAEL, long-term, consumer, oral, systemic: 25 mg/kg/bw/d



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Eni metalCut WUS G 201

Material number 651

Revision date: 10.2.2023

Version: 2.1

Replaces version: 2.0

Language: en-DE

Date of print: 20.2.2023

Page: 5 of 10

PNEC: Information about 3,5-Di-tert-butyl-4-hydroxytoluene
PNEC, water (freshwater): 0,000199 mg/L
PNEC, water (marine water): 0,00002 mg/L
PNEC STP: 0,017 mg/L
PNEC, sediment (freshwater): 0,458 mg/kg
PNEC, sediment (marine water): 0,046 mg/kg/dw
PNEC, soil: 0,045 mg/kg/dw
PNEC, oral: 1667 mg/kg Food

8.2 Exposure controls

Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Personal protection equipment

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded. Use filter type A/P2 according to EN 14387.
The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product.

Hand protection: Protective gloves according to EN 374
permanent contact, Glove material: Nitrile rubber, Chloroprene rubber, Polychloroprene or polyvinyl chloride: (0,7 mm),
Layer thickness layer thickness penetration time >480 min.
During splash contact, Glove material: Nitrile rubber, Chloroprene rubber, Polychloroprene or polyvinyl chloride: (0,4 mm),
Layer thickness layer thickness penetration time >30 min.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: tightly sealed goggles according to EN 166

Body protection: Wear suitable protective clothing.

General protection and hygiene measures:

Avoid breathing mist/vapours/spray. Do not get in eyes, on skin, or on clothing.

Take off contaminated clothing and wash it before reuse.

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

Have eye wash bottle or eye rinse ready at work place.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa	liquid
Colour:	light brown
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	> 240 °C (1013 hPa)
Flammability:	No data available
Upper/lower flammability or explosive limits:	LEL (Lower Explosion Limit): 0,60 Vol-% UEL (Upper Explosive Limit): 6,50 Vol-%
Flash point/flash point range:	> 180 °C (DIN EN ISO 2592)
Decomposition temperature:	No data available
pH:	No data available



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Eni metalCut WUS G 201

Material number 651

Revision date: 10.2.2023

Version: 2.1

Replaces version: 2.0

Language: en-DE

Date of print: 20.2.2023

Page: 6 of 10

Viscosity, kinematic:	at 40 °C: approx. 13 mm ² /s (DIN EN ISO 3104)
Water solubility:	at 20 °C: Insoluble
Partition coefficient: n-octanol/water:	No data available
Vapour pressure:	No data available
Density:	at 15 °C: 0,846 g/mL (DIN EN ISO 12185)
Vapour density:	No data available
Particle characteristics:	Not applicable

9.2 Other information

Explosive properties:	Product is not explosive.
Oxidizing characteristics:	Product has no oxidizing effect.
Auto-ignition temperature:	> 240 °C
Evaporation rate:	No data available
Additional information:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Refer to subsection "Possibility of hazardous reactions".

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Protect from frost, heat and sunlight.

10.5 Incompatible materials

strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products when regulations for storage and handling are observed.

Thermal decomposition: No data available



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Eni metalCut WUS G 201

Material number 651

Revision date: 10.2.2023

Version: 2.1

Replaces version: 2.0

Language: en-DE

Date of print: 20.2.2023

Page: 7 of 10

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.
ATEmix (calculated): 2.000 mg/kg < ATE ≤ 5.000 mg/kg

Acute toxicity (dermal): Based on available data, the classification criteria are not met.
ATEmix (calculated): 2.000 mg/kg < ATE ≤ 5.000 mg/kg

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.
ATEmix (calculated): > 20 mg/L

Skin corrosion/irritation: Based on available data, the classification criteria are not met.
Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation: Eye Irrit. 2; H319 = Causes serious eye irritation. Upon direct contact with eyes may cause burning, tearing, redness.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Based on available data, the classification criteria are not met.
Contains reaction mass of N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine.
May produce an allergic reaction.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.

Aspiration hazard: Asp. Tox. 1; H304 = May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties: This product contains a substance that has endocrine disrupting properties with respect to humans.

Other information: Information about C18-C50 branched, cyclic and linear hydrocarbons – Distillates:
LD50 Rat, oral: > 5.000 mg/kg
LD50 Rabbit, dermal: > 5.000 mg/kg
LC50 Rat, inhalative: > 5 mg/L/4h

Symptoms

The following symptoms may occur:
Cough, respiratory complaints, fever, pneumonia and Pulmonary edema is possible.
After contact with skin: Repeated exposure may cause skin dryness or cracking.
After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.

Water Hazard Class: 1 = slightly hazardous to water (Self-classification (mixture).)

12.2 Persistence and degradability

Further details: Information about C18-C50 branched, cyclic and linear hydrocarbons – Distillates: readily biodegradable (according to OECD criteria)



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Eni metalCut WUS G 201

Material number 651

Revision date: 10.2.2023

Version: 2.1

Replaces version: 2.0

Language: en-DE

Date of print: 20.2.2023

Page: 8 of 10

12.3 Bioaccumulative potential

Bioconcentration factor (BCF): No indication of bioaccumulation potential.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

General information: Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 12 01 07* = mineral-based machining oils free of halogens (except emulsions and solutions)
* = Evidence for disposal must be provided.

Recommendation: Dispose of waste according to applicable legislation.

Package

Recommendation: Non-contaminated packages may be recycled. Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID, IMDG, IATA-DGR: not applicable

ADN: ID 9006

14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR: Not restricted

ADN: ID 9006, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3 Transport hazard class(es)

ADR/RID, IMDG, IATA-DGR: not applicable

ADN: Class 9, Code: M12

14.4 Packing group

ADR/RID, ADN, IMDG, IATA-DGR:

not applicable

14.5 Environmental hazards

Dangerous for the environment: Substance/mixture is not environmentally hazardous according to the criteria of the UN model regulations.

Marine pollutant - IMDG: no

14.6 Special precautions for user

Inland waterway craft (ADN)

Hazard label: -
Transport permitted: T
Equipment necessary: PP



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Eni metalCut WUS G 201

Material number 651

Revision date: 10.2.2023

Version: 2.1

Replaces version: 2.0

Language: en-DE

Date of print: 20.2.2023

Page: 9 of 10

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Germany

Storage class: 10 = Combustible liquids, unless storage class 3

Water Hazard Class: 1 = slightly hazardous to water (Self-classification (mixture).)

Technical guidance air: 5.2.5

Information on working limitations:

Observe employment restrictions for young people.

Observe employment restrictions for expectant or nursing mothers.

Further regulations, limitations and legal requirements:

The product is not subject to the Chemicals Prohibition Ordinance (ChemVerbotsV).

National regulations - EC member states

Labelling of packaging with <= 125mL content



Signal word:

Danger

Hazard statements:

H304

May be fatal if swallowed and enters airways.

H412

Harmful to aquatic life with long lasting effects.

EUH208

Contains reaction mass of

N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine. May produce an allergic reaction.

Precautionary statements:

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P301+P310

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331

Do NOT induce vomiting.

P501

Dispose of contents/container to hazardous or special waste collection point.

Further regulations, limitations and legal requirements:

Use restriction according to REACH annex XVII, no.: 3

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Contains reaction mass of N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine.
May produce an allergic reaction.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Eni metalCut WUS G 201

Material number 651

Revision date: 10.2.2023

Version: 2.1

Replaces version: 2.0

Language: en-DE

Date of print: 20.2.2023

Page: 10 of 10

Wording of the H-phrases under paragraph 2 and 3:

H302 = Harmful if swallowed.

H304 = May be fatal if swallowed and enters airways.

H315 = Causes skin irritation.

H317 = May cause an allergic skin reaction.

H318 = Causes serious eye damage.

H319 = Causes serious eye irritation.

H400 = Very toxic to aquatic life.

H410 = Very toxic to aquatic life with long lasting effects.

H411 = Toxic to aquatic life with long lasting effects.

H412 = Harmful to aquatic life with long lasting effects.

EUH208 = Contains reaction mass of

N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine. May produce an allergic reaction.

Reason of change: General revision

Date of first version: 12.4.2022

Department issuing data sheet: see section 1: Department responsible for information

Abbreviations and acronyms:

- Acute Tox.: Acute toxicity
- ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- Aquatic Acute: Hazardous to the aquatic environment - acute
- Aquatic Chronic: Hazardous to the aquatic environment - chronic
- AS/NZS: Australian Standards/New Zealand Standards
- Asp. Tox.: Aspiration toxicity
- ATE: Acute toxicity estimate
- CAS: Chemical Abstracts Service
- CFR: Code of Federal Regulations
- CLP: Classification, Labelling and Packaging
- DMEL: Derived minimal effect level
- DNEL: Derived no-effect level
- EC: European Community
- EN: European Standard
- EQ: Excepted quantities
- EU: European Union
- Eye Dam.: Eye damage
- Eye Irrit.: Eye irritation
- IATA: International Air Transport Association
- IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
- IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
- IMDG Code: International Maritime Dangerous Goods Code
- LC50: Median lethal concentration
- LD50: Lethal dose 50%
- LEL: Lower Explosion Limit
- MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
- NOAEC: No observed adverse effect concentration
- NOAEL: No Observed Adverse Effect Level
- OECD: Organisation for Economic Co-operation and Development
- OEL: Occupational Exposure Limit Value
- OSHA: Occupational Safety and Health Administration
- PBT: Persistent, bioaccumulative and toxic
- PNEC: Predicted no-effect concentration
- REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
- RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
- Skin Irrit.: Skin irritation
- Skin Sens.: Skin sensitisation
- STP: Sewage Treatment Plant
- TLV: Threshold Limit Value
- TRGS: Technical Rules for Hazardous Substances
- vPvB: Very persistent and very bioaccumulative
- WEL: Workplace Exposure Limit

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

Most recent product information is available at:
<http://sumdat.net/n3hb2y04>

