

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Revision date: 27/12/2023 Version: 1.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

: Eni i-Sint tech P 5W-30 Trade name

Product code : 1012 Type of product : Lubricants Formula : 0188-2018 Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use

Industrial/Professional use spec : Used in closed systems

Wide dispersive use

Use of the substance/mixture : Lubricant for internal combustion engines

Do not use the product for any purposes that have not been advised by the manufacturer.

Function or use category : Lubricants and additives

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Eni Sustainable Mobility S.p.A., Viale Giorgio Ribotta 51, 00144 Rom, ITALY, Tel. +39 06 59821, www.eni.com Competent person responsible for the safety data sheet (Reg. EC nr. 1907/2006): SDS.ESM.info@eni.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY, www.oilproducts.eni.com Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0 e-mail: technik.wuerzburg@enilive.com

# 1.4. Emergency telephone number

**Emergency number** : CNIT +39 0382 24444 (24h) (IT + EN)

Poison Center

#### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Hazardous to the aquatic environment - Chronic Hazard, H412

Category 3

Full text of H- and EUH-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

Contact with eyes may cause temporary reddening and irritation. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

#### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

CLP Signal word

Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P273 - Avoid release to the environment.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### **Nordic countries regulation**

#### Denmark

MAL code : 00-1 (Executive Order No. 301 from 1993)

#### 2.3. Other hazards (not relevant for classification)

Other hazards not contributing to the classification

: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. If the product is handled or used at high temperature, contact with hot product or vapours may cause burns. Do not wait for symptoms to develop. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (121158-58-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0.1 %

Component	
Distillates (petroleum), hydrotreated heavy paraffinic(64742-54-7)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate(125643-61-0)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched(121158-58-5)	The substance is included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

# **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

# 3.2. Mixtures

Notes

: Composition/ Information on ingredients:

Mixture of hydrocarbons

Additives

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), hydrotreated heavy paraffinic (Main component, see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	80 - 90	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889- 13	10 – 15	Not classified
Mineral base oil, severely refined (For identification of the substance, see note [*] ) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	EC-No.: N/A	1 - 10	Not classified
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (Additive)	CAS-No.: 125643-61-0 EC-No.: 406-040-9 EC Index-No.: 607-530-00-7 REACH-no: 01-0000015551-	0,5 - 1,5	Aquatic Chronic 4, H413
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts	CAS-No.: 84605-29-8 EC-No.: 283-392-8 REACH-no: 01-2119493626- 26	0,59 – 1,05	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411 (M=1)
phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (Additive) Substance included in REACH Candidate List (Phenol, alkylation products (mainly in para position) with C12-rich branched alkyl chains from oligomerisation, covering any individual isomers and/ or combinations thereof (PDDP))	CAS-No.: 121158-58-5 EC-No.: 310-154-3 EC Index-No.: 604-092-00-9 REACH-no: 01-2119513207-	0,001 – 0,033	Skin Corr. 1C, H314 Eye Dam. 1, H318 Repr. 1B, H360F Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts	CAS-No.: 84605-29-8 EC-No.: 283-392-8 REACH-no: 01-2119493626- 26	(6,25 ≤ C < 100) Skin Irrit. 2, H315 (10 < C ≤ 12,5) Eye Irrit. 2, H319 (12,5 < C ≤ 100) Eye Dam. 1, H318

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Notes

: [\*] Note: this product may be formulated with one or more of the following severely refined mineral base oils (not classified as hazardous):

CAS 64742-54-7/EC 265-157-1/REACH Reg. # 01-2119484627-25-xxxx; CAS 64742-65-0/EC 265-169-7/REACH Reg. # 01-2119471299-27-xxxx; CAS 64742-70-7/EC 265-174-4/REACH Reg. # 01-2119487080-42-xxxx; CAS 64742-56-9/EC 2265-159-2/ REACH Reg. # 01-2119480132-48-xxxx

All these substances have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L -Annex VI Reg (CE) 1272/2008, # 1.1.3)

Note [\*\*]:

this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

Full text of H- and EUH-statements: see section 16

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures after inhalation

: In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also section 4.3.

First-aid measures after skin contact

Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If inflammation or irritation persists, seek medical advice. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice. Do not put ice on the burn.

First-aid measures after eye contact

Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation persists, seek medical advice. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice.

First-aid measures after ingestion

Do not induce vomiting to avoid aspiration into the lungs. Keep at rest. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation

: This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only if the product is used at high temperature, or in case of sprays and mists. In these cases overexposure to vapours may cause irritation to airways, nausea and dizziness.

Symptoms/effects after skin contact Symptoms/effects after eye contact Contact with hot product may cause thermal burns.

Contact with eyes may cause a light transient irritation. Contact with hot product or vapours may cause burns.

Symptoms/effects after ingestion

Accidental ingestion of small quantities of the product may cause irritation, nausea and gastric disturbances. Taking into account the taste of the product, however, ingestion of dangerous quantites is very unlikely.

Symptoms/effects upon intravenous administration Chronic symptoms

No information available.

None to be reported, according to the present classification criteria.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns. If there is any suspicion of inhalation of H2S (hydrogen sulphide). The casualty should be sent immediately to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

27/12/2023 (Revision date) FU - en 4/22

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media

: Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations).

Unsuitable extinguishing media

Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

# 5.2. Special hazards arising from the substance or mixture

Fire hazard

: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.

Explosion hazard

: In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m³ of air.

Hazardous decomposition products in case of fire

: Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, NOx, H2S and SOx (harmful/toxic gases). Oxygenated compounds (aldehydes, etc.). POx. ZnOx. CaOx.

#### 5.3. Advice for firefighters

Firefighting instructions

: Shut off source of product, if possible. Move containers away from the fire area if this can be done without risk. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.

Special protective equipment for firefighters

: Wear personal protection equipment. (see chapter 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN 443. EN 469. EN 659.

Other information

: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid direct contact with released material. Avoid accidental sprays on hot surfaces or electrical contacts. Keep upwind.

#### 6.1.1. For non-emergency personnel

Protective equipment Emergency procedures : See Section 8.

: Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

#### 6.1.2. For emergency responders

Protective equipment

Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heatresistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (A) (or A+B when applicable for H2S), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. A Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

27/12/2023 (Revision date) EU - en 5/22

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Emergency procedures : If required, notify relevant authorities according to all applicable regulations.

#### 6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

#### 6.3. Methods and material for containment and cleaning up

For containment

: Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.

Other information

Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

#### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling

Ensure that all relevant regulations regarding handling and storage facilities of flammable products are followed. Do not use compressed air for filling, discharging, or handling operations. Keep away from heat/sparks/open flames/hot surfaces. Use and store only outdoors or in a well-ventilated area. During transfer operations, ensure that all equipment and containers are correctly grounded. Avoid the build-up of electric charges. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".

Hygiene measures

Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Take off immediately all contaminated clothing and wash it before reuse. Contaminated materials should not be allowed to accumulate in the workplaces and should never be kept inside the pockets. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in dry, well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible products

: Keep away from strong oxidizers.

Storage area

: Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.

Packages and containers:

: If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.

27/12/2023 (Revision date) EU - en 6/22

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Packaging materials

: For containers, or container linings use materials specifically approved for use with this product. Compatibility should be checked with the manufacturer.

# 7.3. Specific end use(s)

No information available.

# SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Mineral base oil, severely refined		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Mineral base oil, severely refined		
-		
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Lubricating oils (petroleum), C20-50, hydrotrea Baseoil - unspecified (72623-87-1)	ated neutral oil-based	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

# 8.1.2. Recommended monitoring procedures

Monitoring methods	
	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.

# 8.1.3. Air contaminants formed

No additional information available

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 8.1.4. DNEL and PNEC

Eni i-Sint tech P 5W-30	
DNEL/DMEL (additional information)	
Additional information Not applicable	
PNEC (additional information)	
Additional information	Not applicable
Note	: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived

The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

#### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability. See also Section 16, "Other information".

#### 8.2.2. Personal protection equipment

#### Personal protective equipment (for industrial or professional use):

Face shield. Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust/aerosol mask.

#### Personal protective equipment symbol(s):











### 8.2.2.1. Eye and face protection

### Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.

#### 8.2.2.2. Skin protection

#### Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

#### Hand protection:

When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined.

# 8.2.2.3. Respiratory protection

#### Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: if the product is handled without adequate containment means for the vapours: full or half-face gas mask with filter for organic vapours (A) or organic vapours/H2S (A+B). (EN 136/140/145). Combination filter device (DIN EN 141). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145). Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H2S) or self-contained breathing apparatus (SCBA). (EN 136/140/145)

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 8.2.2.4. Thermal hazards

#### Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

#### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Do not discharge the product into the environment. Prevent discharge of undissolved substance to or recover from onsite wastewater. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

#### Consumer exposure controls:

No special requirements.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Yellow-brown.
Appearance : Liquid, bright & clear.
Odour : Slight odour of petroleum.

Odour threshold : There are no data available on the preparation/mixture itself.

Melting point Not determined Freezing point Not determined Boiling point Not determined Flammability Not available Lower explosion limit : Not determined Upper explosion limit Not determined : > 200 °C (ASTM D 92) Flash point Auto-ignition temperature : Not determined Decomposition temperature : Not determined : Not applicable рΗ

Viscosity, kinematic : 68 mm²/s (40 °C) (ASTM D 445) Solubility : Water: Immiscible and insoluble

Log Kow : Not available

Log Pow : Not applicable for mixtures

Vapour pressure : Not determined Vapour pressure at 50°C : Not determined

Density : 846 kg/m³ (ASTM D 4052)

Relative density : Not determined Relative vapour density at 20°C : Not determined Particle characteristics : Not applicable

#### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Explosion limits : ≥ 45 g/m³ (Aerosol)

9.2.2. Other safety characteristics

Relative evaporation rate (butylacetate=1) : Negligible.

Additional information : No data available

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

#### 10.2. Chemical stability

Stable product, according to its intrinsic properties.

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard. Sensitivity to heat, friction or shock cannot be assessed in advance.

#### 10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Avoid the build-up of electrostatic charge.

#### 10.5. Incompatible materials

Strong oxidants.

LD50 oral rat

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce: Toxic fumes. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

: Not classified (Based on available data, the classification criteria are not met) Acute toxicity (oral) Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met) Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Additional information :	(according to composition)	
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
Mineral base oil, severely refined		
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 401)	
LD50 dermal rat	> 5000 mg/kg bodyweight (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)		
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
Phosphorodithioic acid, mixed O,O-bis(1,3-dir	methylbutyl and iso-Pr)esters, zinc salts (84605-29-8)	
LD50 dermal rat	2002 mg/kg bodyweight	
LC50 Inhalation - Rat	2,3 mg/l/4h	
phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (121158-58-5)		
LD50 oral rat	2100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1620 - 2730	
LD50 dermal rabbit	≈ 15000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		

> 5000 mg/kg (OECD 401)

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SDS EU IOITHAL ACCORDING TO COMMISSION REGULATION (EU) 2020/676		
Lubricating oils (petroleum), C20-50, hydrot	reated neutral oil-based	
Baseoil - unspecified (72623-87-1)		
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
	: Not classified (Based on available data, the classification criteria are not met) pH: Not applicable	
Additional information	: (according to composition)	
Distillates (petroleum), hydrotreated heavy		
pH	Not applicable	
Mineral base oil, severely refined		
рН	Not applicable	
Lubricating oils (petroleum), C20-50, hydrot Baseoil - unspecified (72623-87-1)	reated neutral oil-based	
рН	Not applicable	
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)	
Additional information	pH: Not applicable : (according to composition)	
Distillates (petroleum), hydrotreated heavy	paraffinic (64742-54-7)	
pH	Not applicable	
Mineral base oil, severely refined		
рН	Not applicable	
Lubricating oils (petroleum), C20-50, hydrot Baseoil - unspecified (72623-87-1)	reated neutral oil-based	
рН	Not applicable	
Respiratory or skin sensitisation Additional information	: Not classified	
Germ cell mutagenicity	<ul> <li>(according to composition)</li> <li>Not classified (Based on available data, the classification criteria are not met)</li> </ul>	
Additional information	: (according to composition)	
Carcinogenicity Additional information	Not classified (Based on available data, the classification criteria are not met)     (according to composition)	
Additional information	This product contains: Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil—unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.  All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)	
Reproductive toxicity Additional information	<ul><li>Not classified (Based on available data, the classification criteria are not met)</li><li>(according to composition)</li></ul>	
phenol, dodecyl-, branched; phenol, 2-dode	cyl-, branched; phenol, 3-dodecyl-, branched (121158-58-5)	
NOAEL (animal/male, F1)	1,5 mg/kg	
NOAEL (animal/female, F1)	15 mg/kg (OECD 416)	
STOT-single exposure Additional information	Not classified (Based on available data, the classification criteria are not met)     (according to composition)	

27/12/2023 (Revision date) EU - en 12/22

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

reaction mass of isomers of: C7-9-alkyl 3-(3,5	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)		
LOAEL (oral, rat)	5 mg/kg bw/day (28 d)		
· · · · ·	Not classified (Based on available data, the classification criteria are not met) (according to composition)		
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)		
Mineral base oil, severely refined			
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)		
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)			
NOAEL (oral, rat, 90 days)	5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)		
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)			
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)		
·	Not classified (Based on available data, the classification criteria are not met) Viscosity, kinematic: > 20,5 mm2/s (40 °C) (ASTM D 445)		
Eni i-Sint tech P 5W-30			
Viscosity, kinematic	68 mm²/s (40 °C) (ASTM D 445)		
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)		
Viscosity, kinematic	17,9 mm²/s (40 °C) (ASTM D 445)		
Mineral base oil, severely refined			
Viscosity, kinematic	> 21 mm²/s		
Hydrocarbon	Yes		
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)			
Viscosity, kinematic	48 mm²/s (40°C) (ASTM D 445)		

# 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

13/22

Component	
phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched(121158-58-5)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)

: Contact with eyes may cause temporary reddening and irritation.

### 11.2.2. Other information

27/12/2023 (Revision date)

Potential adverse human health effects and

symptoms

Other information : None

EU - en

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

# SECTION 12: Ecological information

12.1. Toxicity				
	An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment.  This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only in			
Ecology - water	case of sprays and mists. In these cases overexposure to mists (e.g. through prolonged use in confined insufficiently ventilated spaces) may cause irritation to airways, nausea and dizziness.  This product is not soluble in water. It floats on water and forms a film on the surface. The			
	damage to aquatic organisms is of mechanical kind (immobilization and entrapment)  Not classified (Based on available data, the classification criteria are not met)			
(acute) Hazardous to the aquatic environment, long-term : (chronic)	Harmful to aquatic life with long lasting effects. (Based on available data, the classification criteria are not met)			
Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)			
LC50 fish 1	> 100 mg/l (LL 50)			
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)			
Mineral base oil, severely refined				
LC50 fish 1	> 100 mg/l (LL 50)			
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)			
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)				
LC50 fish 1	> 1000 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)			
LC50 fish 2	> 2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)			
EC50 Daphnia 1	0,9 mg/l Test organisms (species): Daphnia magna			
EC50 Daphnia 2	> 1000 mg/l Test organisms (species): Daphnia magna			
EC50 72h - Algae [1]	> 3 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)			
ErC50 (algae)	> 33,7 mg/l (OECD 201, 72 h, Pseudokirchnerella subspicata)			
NOEC (acute)	33,7 mg/l (72 h, Pseudokirchnerella subspicata)			
NOEC (chronic)	≤ 0,01 mg/l Test organisms (species): Daphnia magna Duration: '21 d'			
NOEC chronic crustacea	≥ 1 mg/l (21d, Daphnia magna)			
Phosphorodithioic acid, mixed O,O-bis(1,3-di	methylbutyl and iso-Pr)esters, zinc salts (84605-29-8)			
LC50 fish 1	46 mg/l			
EC50 Daphnia 1	23 mg/l			
EC50 72h - Algae [1]	21 – 24 mg/l			
phenol, dodecyl-, branched; phenol, 2-dodec	yl-, branched; phenol, 3-dodecyl-, branched (121158-58-5)			
LC50 fish 1	40 mg/l (Pimephales promelas)			
EC50 Daphnia 1	0,037 mg/l Test organisms (species): Daphnia magna			
EC50 other aquatic organisms 1	> 0,58 mg/l (96h, Mysidopsis Bahia)			
EC50 72h - Algae [1]	0,15 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)			

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

EC50 72h - Algae [2]	0,36 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
ErC50 (algae)	0,36 mg/l (21d)	
LOEC (chronic)	0,012 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	0,0037 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
LC50 fish 1	> 100 mg/l (LL 50)	
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)	

# 12.2. Persistence and degradability

Eni i-Sint tech P 5W-30			
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.		
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.		
Mineral base oil, severely refined			
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.		
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)			
Persistence and degradability	Not biodegradable.		
phenol, dodecyl-, branched; phenol, 2-dodecy	phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (121158-58-5)		
Biodegradation	25 % (28 d, OECD TG 301 B)		
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)			
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.		

# 12.3. Bioaccumulative potential

Eni i-Sint tech P 5W-30			
og Pow Not applicable for mixtures			
Bioaccumulative potential Not established.			
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)			
Bioconcentration factor (BCF REACH) 260 (35 d, Oncorhynchus mykiss, OECD 305)			
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts (84605-29-8)			
Log Kow	0,56		

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (121158-58-5)		
Bioconcentration factor (BCF REACH) 794,33		
Log Kow	7,14	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
Log Kow > 6		

# 12.4. Mobility in soil

Eni i-Sint tech P 5W-30	
Ecology - soil	No data available.

#### 12.5. Results of PBT and vPvB assessment

Eni i-Sint tech P 5W-30				
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII				
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII				
Results of PBT-vPvB assessment	The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)			
Component				
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)			
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)			
phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (121158-58-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII			
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII			

# 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

# Component phenol, dodecyl-, branched; phenol, 2-dodecyl-,

pnenoi, dodecyi-, branched; pnenoi, 2-dodecyi-, branched; phenoi, 3-dodecyi-, branched(121158-58-5)

Has an endocrine mode of action, i.e. it alters the function(s) of the endocrine system

#### 12.7. Other adverse effects

Other adverse effects : None.

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Additional information

: This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste treatment methods : Do not dispose of the product, either new or used, by dumping on the ground, or discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official

collector.

Sewage disposal recommendations

Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Dispose of in a safe manner in accordance with local/national regulations.

Product/Packaging disposal recommendations

European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05\* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual

use of the product, alterations and contaminations.

Additional information : Empty containers may contain combustible product residues. Do not cut, weld, bore, burn or

incinerate emptied containers, unless they have been cleaned and declared safe.

Ecology - waste materials

EURAL code (EWC)

: The product as it is does not contain halogenated substances.

: 13 02 05\* - Mineral-based non-chlorinated engine, gear and lubricating oils

# **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
None.				

#### 14.6. Special precautions for user

### **Overland transport**

Not regulated

### Transport by sea

Not regulated

#### Air transport

Not regulated

### Inland waterway transport

Not regulated

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### Rail transport

Not regulated

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Other information, restriction and prohibition regulations

: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances (ODP). Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC. Regulation EU (649/2012) - Export and Import of hazardous chemicals (PIC).

#### **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)			
Reference code	Applicable on	Entry title or description	
3(b)	Distillates (petroleum), hydrotreated heavy paraffinic; Phosphorodithioic acid, mixed O,O-bis(1,3- dimethylbutyl and iso- Pr)esters, zinc salts	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	
3(c)	Eni i-Sint tech P 5W-30; reaction mass of isomers of: C7-9-alkyl 3-(3,5-ditert-butyl-4-hydroxyphenyl)propionate; Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	
30.	phenol, dodecyl-, branched; phenol, 2- dodecyl-, branched; phenol, 3-dodecyl-, branched	Substances which are classified as reproductive toxicant category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 5 or Appendix 6, respectively.	

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### **REACH Candidate List (SVHC)**

Contains substance(s) listed on the REACH Candidate List in concentrations ≥ 0.1 % or SCL: phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (EC 310-154-3, CAS 121158-58-5)

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

#### **Finland**

: Occupational Safety and Health Act No. 738/2002. Finnish National Regulations

#### France

Maladies professionelles (F)		
Code	Description	
RG 36	Diseases caused by oils and fats of mineral or synthetic origin	

# Germany

to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.

National Rules and Recommendations TRGS 900: Occupational Exposure Limits.

TRGS 800: Fire protection measures.

TRGS 555: Working instruction and information for workers.

TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous

Substances: Inhalation Exposure.

TRGS 401: Risks resulting from skin contact - identification, assessment, measures. TRGS 400: Hazard assessment for activities involving Hazardous Substances.

VbF class (D)

Water hazard class (WGK) (D) WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1). WGK remark

Classification based on the components in compliance with Verwaltungsvorschrift

wassergefährdender Stoffe (VwVwS).

Storage class (LGK, TRGS 510) : LGK 10 - Combustible liquids.

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

**Netherlands** 

Saneringsinspanningen : C - Minimize discharge

SZW-lijst van kankerverwekkende stoffen : None of the components are listed SZW-lijst van mutagene stoffen : None of the components are listed : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid

phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched is

SZW-lijst van reprotoxische stoffen - Ontwikkeling : None of the components are listed

27/12/2023 (Revision date) FU - en 19/22

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### **Denmark**

MAL code : 00-1 (Executive Order No. 301 from 1993)

Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with it

**Norway** 

Norwegian National Regulations : Working Environment Act (LOV-2005-06-17 NO. 62).

People under the age of 18 may not work with this product at all.

Sweden

Swedish National Regulations : This product is in compliance with Ordinance 1998:944.

Work Environment Act (1977: 1160).

Chemical Hazards in the Working Environment (AFS 2011:19).

#### 15.2. Chemical safety assessment

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

No chemical safety assessment has been carried out

A chemical safety assessment has been carried out for the following components of this mixture::

Distillates (petroleum), hydrotreated heavy paraffinic

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Baseoil - unspecified

# **SECTION 16: Other information**

Indication of changes				
Section Changed item Change Notes				
	First issue.			

Abbreviations and acronyms:			
	Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.		
	N/A = not applicable		
	N/D = not available		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road		
ATE	Acute Toxicity Estimate		
BCF	Bioconcentration factor		
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008		
DMEL	Derived Minimal Effect level		
DNEL	Derived-No Effect Level		
EC50	Effective concentration for 50 percent of test population (median effective concentration)		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)		
LD50	Lethal dose for 50 percent of test population (median lethal dose)		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		

27/12/2023 (Revision date) EU - en 20/22

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:			
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
PBT	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006		
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
vPvB	Very Persistent and Very Bioaccumulative		

Data sources

Training advice

Other information

- : This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
- : Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.
- Do not use the product for any purposes that have not been advised by the manufacturer. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. If this possibility is suspected, a specific assessment of inhalation risks from the presence of H2S in confined spaces must be made, to help determine prevention measures and controls (i.e. PPE) appropriate to local circumstances, and adequate emergency procedures. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

Full text of H- and EUH-statements:				
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1			
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1			
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2			
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4			
Asp. Tox. 1	Aspiration hazard, Category 1			
Eye Dam. 1	Serious eye damage/eye irritation, Category 1			
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2			
H304	May be fatal if swallowed and enters airways.			
H314	Causes severe skin burns and eye damage.			
H315	Causes skin irritation.			
H318	Causes serious eye damage.			
H319	Causes serious eye irritation.			
H360F	May damage fertility.			
H400	Very toxic to aquatic life.			
H410	Very toxic to aquatic life with long lasting effects.			
H411	Toxic to aquatic life with long lasting effects.			

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:			
H412	Harmful to aquatic life with long lasting effects.		
H413	May cause long lasting harmful effects to aquatic life.		
Repr. 1B	Reproductive toxicity, Category 1B		
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:				
Aquatic Chronic 3	H412	Calculation method		

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.