

Greases

AUTOL TOP 2000

KP 2 K-30

resistant to salt water
extremely adhesive

DIN 51 825 T.3

Super-Longtime-Grease with a synthetic base oil for longer regreasing intervals.

Soap Basis		special Ca. soap
Temperature range	°C	-30 to +120
Drop point	°C	150
NLGI-class		2
Base oil viscosity at 40°C	mm ² /s	approx. 800
Behaviour to Water		0-90
Corrosion protection properties (EMCOR-Test)		Corr. -grade. 0 and 0
VKA-Test	Nw	3000

AUTOL TOP 2000 is a special grease with exceptional adhesive properties and very good extreme-pressure-properties - a real Super-Longtime-Grease suitable for very long regreasing intervals.

Under difficult conditions it reduces wear and is especially resistant to wash outs in the lubrication points. It is extremely resistant to salt water, cooling lubricants, plant preservatives and many lyes.

Due to its composition and if applied as directed, according to the manufacturers regulations, it is physiological harmless and therefore also suitable for the application as lubricant in the foodstuff industry.

Applications:

AUTOL TOP 2000 is a high pressure grease for the lubrication of vehicles, industrial, constructional and agricultural machines. It is reliable as a "problem solver" at lubrication points with critical stress (shock loads, high humidity, salt water, high pressure with low relative movement, etc.) These are industrial robots, continuous transporters as well as for boats or winter service. Despite the high base oil viscosity the application in central lubricating systems is possible without problems.

For the use in wheel and axle bearings we recommend **AUTOL TOP 2000 High Temp.**

Attention! The highest short-time peak temperature permitted is +125°C.

Please observe the manufacturer's specifications when selecting products.