

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet LAK-E; Art. no. 0756
Revision date : 01.11.2018
Print date : 29.11.2018

Version (Revision) : 6.0.0 (5.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

eni aquamet LAK-E

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Metal working fluids

Uses advised against

No information available.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/downstream user/distributor)

Eni Schmiertechnik GmbH

Street :

Paradiesstraße 14

Postal code/city :

97080 Würzburg

Telephone :

(+49) 931-90098-0

Telefax :

(+49) 931-98442

Information contact :

Technical Department, Tel. (+49) 931 900 98-142

email:

technik.wuerzburg@agip.de, www.enischmiertechnik-datenblaetter.de

1.4 Emergency Telephone Number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

Carc. 1B ; H350 - Carcinogenicity : Category 1B ; May cause cancer.

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Muta. 2 ; H341 - Germ cell mutagenicity : Category 2 ; Suspected of causing genetic defects.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Health hazard (GHS08) · Corrosion (GHS05) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

reaction products of paraformaldehyde and 2-hydroxypropylamine (ratio 3:2)

2-(2-AMINOETHOXY)-ETHANOL ; CAS No. : 929-06-6

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet LAK-E; Art. no. 0756
Revision date : 01.11.2018
Print date : 29.11.2018

Version (Revision) : 6.0.0 (5.0.0)

Hazard statements

H350 May cause cancer.
H341 Suspected of causing genetic defects.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor/....
P405 Store locked up.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Mixture of substances listed below with nonhazardous additions.

Hazardous ingredients

2,2'-(METHYLIMINO)DIETHANOL ; REACH registration No. : 01-2119488970-24-XXXX ; EC No. : 203-312-7; CAS No. : 105-59-9

Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

Sulfonic acids, petroleum, sodium salt ; REACH registration No. : 01-2119527859-22-0001 ; EC No. : 271-781-5; CAS No. : 68608-26-4

Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

reaction products of paraformaldehyde and 2-hydroxypropylamine (ratio 3:2)

Weight fraction : $\geq 1 - < 2,5 \%$
Classification 1272/2008 [CLP] : Acute Tox. 3 ; H311 Carc. 1B ; H350 Muta. 2 ; H341 STOT RE 2 ; H373 Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Acute Tox. 4 ; H332 Skin Sens. 1 ; H317 Aquatic Chronic 2 ; H411

Alcohols, C16-18 and C18-unsatd., ethoxylated ; REACH registration No. : 01-2119489407-26 ; EC No. : 500-236-9; CAS No. : 68920-66-1

Weight fraction : $\geq 1 - < 2,5 \%$
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Aquatic Chronic 2 ; H411

2-(2-AMINOETHOXY)-ETHANOL ; REACH registration No. : 01-2119520701-52-0000 ; EC No. : 213-195-4; CAS No. : 929-06-6

Weight fraction : $\geq 1 - < 3 \%$
Classification 1272/2008 [CLP] : Skin Corr. 1B ; H314 Eye Dam. 1 ; H318

2-(2-BUTOXYETHOXY)ETHANOL ; REACH registration No. : 01-2119475104-44-0006 ; EC No. : 203-961-6; CAS No. : 112-34-5

Weight fraction : $\geq 1 - < 5 \%$

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet LAK-E; Art. no. 0756
Revision date : 01.11.2018
Print date : 29.11.2018

Version (Revision) : 6.0.0 (5.0.0)

Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319
PYRIDINE-2-THIOL 1-OXIDE, SODIUM SALT ; EC No. : 223-296-5; CAS No. : 3811-73-2
Weight fraction : $\geq 0,025 - < 0,25$ %
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ;
H315 Eye Irrit. 2 ; H319 Aquatic Acute 1 ; H400 Aquatic Chronic 2 ; H411
3-IODO-2-PROPYNYL BUTYLCARBAMATE ; EC No. : 259-627-5; CAS No. : 55406-53-6
Weight fraction : $\geq 0,025 - < 0,1$ %
Classification 1272/2008 [CLP] : Acute Tox. 3 ; H331 STOT RE 1 ; H372 Eye Dam. 1 ; H318 Acute Tox. 4 ;
H302 Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove victim out of the danger area. When in doubt or if symptoms are observed, get medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest.

In case of skin contact

Change contaminated, saturated clothing. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam, Extinguishing powder, Carbon dioxide (CO₂), Water spray jet, Water mist, Sand,

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide, Nitrogen oxides (NO_x), Smoke and other incomplete combustion products.

5.3 Advice for firefighters

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet LAK-E; Art. no. 0756
Revision date : 01.11.2018
Print date : 29.11.2018

Version (Revision) : 6.0.0 (5.0.0)

5.4 Additional information

Do not inhale explosion and combustion gases. Use water spray jet to protect personnel and to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Avoid contact with skin, eyes and clothes. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Ventilate affected area.

6.2 Environmental precautions

Cover drains. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For containment

Cover drains. Stop and contain spill/release if it can be done safely. Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Wipe up with absorbent material (eg. cloth, fleece). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically, placing in appropriate containers for disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Wear personal protection equipment (refer to section 8). Use only in well-ventilated areas. Handle and open container with care. Avoid contact with skin, eyes and clothes. Do not breathe gas/fumes/vapour/spray.

Protective measures

Measures to prevent fire

Only use the material in places where open light, fire and other flammable sources can be kept away.

Environmental precautions

Do not allow to enter into surface water or drains.

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Do not put any product-impregnated cleaning rags into your trouser pockets.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Store in a place accessible by authorized persons only. Keep locked up.

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product. Protect containers against damage.

Hints on joint storage

Keep away from: Oxidizing agent

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet LAK-E; Art. no. 0756
Revision date : 01.11.2018
Print date : 29.11.2018

Version (Revision) : 6.0.0 (5.0.0)

Storage class (TRGS 510) : 6.1C

Do not store together with

Food and feedingstuffs

Further information on storage conditions

Recommended storage temperature : 20 °C

Protect against : Frost Heat. UV-radiation/sunlight

Storage stability : Product may be stored for up to 12 months under described conditions.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

2-(2-AMINOETHOXY)-ETHANOL ; CAS No. : 929-06-6

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 0,2 ppm / 0,87 mg/m³

Peak limitation : 1(I)

Remark : H, Sh

Version : 17.10.2017

2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 10 ppm / 67 mg/m³

Peak limitation : 1,5(I)

Remark : Y

Version : 17.10.2017

Limit value type (country of origin) : STEL (EC)

Limit value : 15 ppm / 101,2 mg/m³

Version : 07.02.2006

Limit value type (country of origin) : TWA (EC)

Limit value : 10 ppm / 67,5 mg/m³

Version : 07.02.2006

PYRIDINE-2-THIOL 1-OXIDE, SODIUM SALT ; CAS No. : 3811-73-2

Limit value type (country of origin) : TRGS 900 (D)

Parameter : E: inhalable fraction

Limit value : 1 mg/m³

Peak limitation : 2(II)

Remark : H, Z

Version : 17.10.2017

3-IODO-2-PROPYNYL BUTYLCARBAMATE ; CAS No. : 55406-53-6

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 0,005 ppm / 0,058 mg/m³

Peak limitation : 2(I)

Remark : Sh, Y

Version : 17.10.2017

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type : DNEL worker (systemic) (2,2'-(METHYLIMINO)DIETHANOL ; CAS No. : 105-59-9)

Exposure route : Dermal

Exposure frequency : Long-term (repeated)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet LAK-E; Art. no. 0756
Revision date : 01.11.2018
Print date : 29.11.2018

Version (Revision) : 6.0.0 (5.0.0)

Limit value : 19 mg/kg bw/d
Limit value type : DNEL worker (systemic) (2,2'-(METHYLIMINO)DIETHANOL ; CAS No. : 105-59-9)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 26 mg/m³
Limit value type : DNEL worker (systemic) (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 2080 mg/kg bw/d
Limit value type : DNEL worker (systemic) (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 294 mg/m³
Limit value type : DNEL worker (local) (2-(2-AMINOETHOXY)-ETHANOL ; CAS No. : 929-06-6)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 0,67 mg/m³
Limit value type : DNEL worker (systemic) (2-(2-AMINOETHOXY)-ETHANOL ; CAS No. : 929-06-6)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 7,3 mg/kg bw/d
Limit value type : DNEL worker (systemic) (2-(2-AMINOETHOXY)-ETHANOL ; CAS No. : 929-06-6)
Exposure route : Inhalation
Exposure frequency : Short-term (acute)
Limit value : 1,12 mg/m³
Limit value type : DNEL worker (systemic) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 20 mg/kg
Limit value type : DNEL worker (systemic) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 67,5 mg/m³

Remark

The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation.

PNEC

Limit value type : PNEC (Aquatic, freshwater) (2,2'-(METHYLIMINO)DIETHANOL ; CAS No. : 105-59-9)
Limit value : 0,1 mg/l
Limit value type : PNEC (Aquatic, marine water) (2,2'-(METHYLIMINO)DIETHANOL ; CAS No. : 105-59-9)
Limit value : 0,0045 mg/l
Limit value type : PNEC (Sediment, freshwater) (2,2'-(METHYLIMINO)DIETHANOL ; CAS No. : 105-59-9)
Limit value : 0,78 mg/kg
Limit value type : PNEC soil, freshwater (2,2'-(METHYLIMINO)DIETHANOL ; CAS No. : 105-59-9)
Limit value : 0,097 mg/kg
Limit value type : PNEC (Sewage treatment plant) (2,2'-(METHYLIMINO)DIETHANOL ; CAS No. : 105-

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet LAK-E; Art. no. 0756
Revision date : 01.11.2018
Print date : 29.11.2018

Version (Revision) : 6.0.0 (5.0.0)

Limit value :	59-9)
Limit value type :	10 mg/l PNEC (Aquatic, freshwater) (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Limit value :	0,002 mg/l
Limit value type :	PNEC (Aquatic, marine water) (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Limit value :	0,002 mg/l
Limit value type :	PNEC (Sediment, freshwater) (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Limit value :	6,33 mg/kg
Limit value type :	PNEC (Soil) (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Limit value :	1 mg/kg
Limit value type :	PNEC (Sewage treatment plant) (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Limit value :	10000 mg/l
Limit value type :	PNEC (Aquatic, freshwater) (2-(2-AMINOETHOXY)-ETHANOL ; CAS No. : 929-06-6)
Limit value :	0,0202 mg/l
Limit value type :	PNEC (Aquatic, marine water) (2-(2-AMINOETHOXY)-ETHANOL ; CAS No. : 929-06-6)
Limit value :	0,0202 mg/l
Limit value type :	PNEC (Sediment, freshwater) (2-(2-AMINOETHOXY)-ETHANOL ; CAS No. : 929-06-6)
Limit value :	0,945 mg/kg
Limit value type :	PNEC (Sediment, marine water) (2-(2-AMINOETHOXY)-ETHANOL ; CAS No. : 929-06-6)
Limit value :	0,0945 mg/kg
Limit value type :	PNEC (Sewage treatment plant) (2-(2-AMINOETHOXY)-ETHANOL ; CAS No. : 929-06-6)
Limit value :	28 mg/l
Limit value type :	PNEC (Aquatic, freshwater) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Limit value :	1 mg/l
Limit value type :	PNEC (Aquatic, marine water) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Limit value :	0,1 mg/l
Limit value type :	PNEC (Sediment, freshwater) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Limit value :	4 mg/kg
Limit value type :	PNEC (Sediment, marine water) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Limit value :	0,4 mg/kg
Limit value type :	PNEC (Sewage treatment plant) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Limit value :	200 mg/l

8.2 Exposure controls

Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

Personal protection equipment

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Eye/face protection

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet LAK-E; Art. no. 0756
Revision date : 01.11.2018
Print date : 29.11.2018

Version (Revision) : 6.0.0 (5.0.0)

Eye glasses with side protection DIN EN 166

Skin protection

Hand protection

Tested protective gloves must be worn: DIN EN 374

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material :

Wearing time with permanent contact:

Material: NBR (Nitrile rubber), CR (polychloroprene, chloroprene rubber),

Thickness of the glove material: 0,70 mm

Breakthrough time (maximum wearing time): > 480 min

Wearing time with occasional contact (splashes):

NBR (Nitrile rubber), CR (polychloroprene, chloroprene rubber),

Thickness of the glove material: 0,40 mm

Breakthrough time (maximum wearing time): > 30 min

Unsuitable material : PVA (Polyvinyl alcohol),

Breakthrough time (maximum wearing time) : For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

Body protection: not required. If prolonged or repeated contact is likely, chemical, and oil resistant clothing is recommended.

Respiratory protection

Usually no personal respirative protection necessary. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Respiratory protection necessary at: exceeding exposure limit values, insufficient ventilation, aerosol or mist formation.

Suitable respiratory protection apparatus

Combination filtering device (EN 14387)

General health and safety measures

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Do not put any product-impregnated cleaning rags into your trouser pockets. Wash contaminated clothing prior to re-use. Apply skin care products after work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : brown

Odour : characteristic

Safety relevant basis data

Oxidising liquids : Not oxidising.

Explosive properties : Not explosive according to EU A.14.

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet LAK-E; Art. no. 0756
Revision date : 01.11.2018
Print date : 29.11.2018

Version (Revision) : 6.0.0 (5.0.0)

The product is stable under storage at normal ambient temperatures.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Oxidising agent, strong.

10.6 Hazardous decomposition products

Formaldehyde

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological data are not available. The statement is derived from the properties of the single components.

Acute effects

No data available to indicate product may be an acute toxic oral, dermal or inhalation hazard.

Irritant and corrosive effects

Primary irritation to the skin

Causes skin irritation.

Irritation to eyes

Causes serious eye damage.

Sensitisation

May cause sensitization by skin contact.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Classification of mixtures as having effects of carcinogenicity, mutagenicity or toxicity for reproduction must be calculated from available information regarding substances in the mixture.

Carcinogenicity

May cause cancer.

Germ cell mutagenicity

Suspected of causing genetic defects.

Reproductive toxicity

No indications of human reproductive toxicity exist.

STOT-single exposure

STOT SE 1 and 2

Not expected to cause organ damage from a single exposure.

STOT-repeated exposure

STOT RE 1 and 2

Not expected to cause organ damage from prolonged or repeated exposure.

Aspiration hazard

Based on the available data the classification criteria for aspiration toxicity are not met. For viscosity data, see section 9.

11.4 Other adverse effects

Other observations

Processing vapours can irritate the respiratory tracts, skin and eyes.

SECTION 12: Ecological information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet LAK-E; Art. no. 0756
Revision date : 01.11.2018
Print date : 29.11.2018

Version (Revision) : 6.0.0 (5.0.0)

12.1 Toxicity

For the product ecotoxicological data are not available. The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3).

Aquatic toxicity

Harmful to aquatic life.

12.2 Persistence and degradability

Part of the components is biodegradable.

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Waste code product

12 01 10*

Waste name

Synthetic machining oils.

Waste treatment options

Appropriate disposal / Product

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package

Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet LAK-E; Art. no. 0756
Revision date : 01.11.2018
Print date : 29.11.2018

Version (Revision) : 6.0.0 (5.0.0)

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

National regulations

-

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : < 5 %

Water hazard class (WGK)

Class : 2 (Significant hazardous to water) Classification according to AwSV

Additional information

Berufsgenossenschaftliche Regeln (BGR)

The product corresponds with TRGS 611.

To follow :

-

-

15.2 Chemical safety assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
CAS: Chemical Abstracts Service (division of the American Chemical Society)
GHS: Globally Harmonized System on the Classification and Labelling of Chemicals
CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
EC50: Effective concentration, 50 percent
DNEL: Derived No Effect Level

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet LAK-E; Art. no. 0756
Revision date : 01.11.2018
Print date : 29.11.2018

Version (Revision) : 6.0.0 (5.0.0)

PNEC: Predicted No Effect Concentration
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3 Key literature references and sources for data

Sources of information used in preparing this SDS included one or more of the following: Product Dossiers and SDS from suppliers, complemented by public sources, as appropriate (GESTIS, the EU IUCLID Data Base, U.S. NTP publications, e.g.).

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

16.6 Training advice

Provide adequate information, instruction and training for operators.

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.