

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Eni metalCut 22 TB; Art.-no. 960
Revision : 17.02.2017
Print date : 27.02.2017

Version (Revision) : 5.0.0 (4.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Eni metalCut 22 TB

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

cooling grease

Observe technical data sheet.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Eni Schmiertechnik GmbH

Street : Paradiesstraße 14

Postal code/city : D – 97080 Würzburg

Telephone : +49 931 900 98-0

Telefax : +49 931 98442

Information contact :

Technical department, Tel. +49 931 900 98-145

technik.wuerzburg@agip.de

www.enischmiertechnik-datenblaetter.de

1.4 Emergency telephone number

+49 22 81 92 40 (Informationszentrale gegen Vergiftungen des Landes NRW, Universitätsklinikum Bonn).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

Classification procedure

Calculation method.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Health hazard (GHS08)

Signal word

Danger

Hazard components for labelling

Distillates (petroleum), hydrotreated light paraffinic ; CAS No. : 64742-55-8

Hazard statements

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/....

P331 Do NOT induce vomiting.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Eni metalCut 22 TB; Art.-no. 960
Revision : 17.02.2017
Print date : 27.02.2017

Version (Revision) : 5.0.0 (4.0.0)

P405 Store locked up.

Special rules for supplemental label elements for certain mixtures

EUH208 Contains Sulfonic acids, Petroleum, Calcium Salts, Oil soluble ; Benzenesulfonic acid, mono-C16-24-alkyl derivs,calcium salts.May produce an allergic reaction.

2.3 Other hazards

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

Distillates (petroleum), hydrotreated light paraffinic ; REACH registration No. : 01-2119487077-29 ; EC No. : 265-158-7; CAS No. : 64742-55-8

Weight fraction : $\geq 25 - < 50$ %
Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304

Zinc-bis[0,0-bis(2-ethylhexyl)]bis(dithiophosphate) ; REACH registration No. : 01-2119493635-27 ; EC No. : 224-235-5; CAS No. : 4259-15-8

Weight fraction : $\geq 1 - < 10$ %
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Aquatic Chronic 2 ; H411

Isopropylated triphenyl phosphate ; REACH registration No. : 01-2119535109-41 ; EC No. : 273-066-3; CAS No. : 68937-41-7

Weight fraction : $\geq 0 - < 1$ %
Classification 1272/2008 [CLP] : Repr. 2 ; H361fd STOT RE 2 ; H373 Aquatic Chronic 2 ; H411

2,6-Di-tert-Butyl-p-cresol ; REACH registration No. : 01-2119555270-46 ; EC No. : 204-881-4; CAS No. : 128-37-0

Weight fraction : $\geq 0 - < 1$ %
Classification 1272/2008 [CLP] : Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

Benzenesulfonic acid,C10-16-alkyl derivs.,calcium salts ; EC No. : 271-529-4; CAS No. : 68584-23-6

Weight fraction : $\geq 0 - < 1$ %
Classification 1272/2008 [CLP] : Skin Sens. 1B ; H317

Sulfonic acids, Petroleum, Calcium Salts, Oil soluble ; REACH registration No. : 01-2119488992-18-0000 ; EC No. : 263-093-9; CAS No. : 61789-86-4

Weight fraction : $\geq 0,1 - < 1$ %
Classification 1272/2008 [CLP] : Skin Sens. 1B ; H317

Benzenesulfonic acid, mono-C16-24-alkyl derivs,calcium salts ; EC No. : 274-263-7; CAS No. : 70024-69-0

Weight fraction : $\geq 0,1 - < 1$ %
Classification 1272/2008 [CLP] : Skin Sens. 1B ; H317

Additional information

Full text of H- and EUH-phrases: see section 16.

3.3 Additional information

Highly refined mineral oil (IP 346 DMSO extract < 3%).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. When in doubt or if symptoms are observed, get medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. When in doubt or if symptoms are observed, get medical advice.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician. Oils and greases injected under your skin with high pressure equipment is a serious damage. Seek medical attention IMMEDIATELY. Bring a copy of this safety data sheet with you to the hospital for information to the medical staff.

After eye contact

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Eni metalCut 22 TB; Art.-no. 960
Revision : 17.02.2017
Print date : 27.02.2017

Version (Revision) : 5.0.0 (4.0.0)

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye. Call a physician immediately.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

The following symptoms may occur: Respiratory complaints , Headache , Dizziness , Nausea . Symptoms can occur only after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam , Extinguishing powder , Carbon dioxide (CO₂) , Sand .
Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Water .

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon dioxide (CO₂) , Nitrogen oxides (NO_x) , Sulphur oxides , Carbon monoxide , Aliphatic and aromatic pyrolysis products.

5.3 Advice for firefighters

Special protective equipment for firefighters

Do not inhale explosion and combustion gases. Use suitable breathing apparatus.

5.4 Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Special danger of slipping by leaking/spilling product. Provide fresh air.

Avoid contact with skin, eyes and clothes.

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

For non-emergency personnel

Avoid contact with skin, eyes and clothes. Use personal protection equipment. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Special danger of slipping by leaking/spilling product. Provide adequate ventilation. See protective measures under point 7 and 8.

For emergency responders

Suitable material : NBR (Nitrile rubber)

Unsuitable material : Butyl caoutchouc (butyl rubber) , NR (natural rubber, natural latex) , CR (polychloroprene, chloroprene rubber)

6.2 Environmental precautions

Make sure spills can be contained, e.g. in sump pallets or kerbed areas. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3 Methods and material for containment and cleaning up

For containment

Clear spills immediately. Cover drains.

For cleaning up

Take up with oil-absorbing compound. Treat the recovered material as prescribed in the section on waste disposal. Never return spills

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Eni metalCut 22 TB; Art.-no. 960
Revision : 17.02.2017
Print date : 27.02.2017

Version (Revision) : 5.0.0 (4.0.0)

in original containers for re-use. Clean contaminated articles and floor according to the environmental legislation.

6.4 Reference to other sections

Wear personal protection equipment (refer to section 8). Disposal: see section 13 .

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No hazardous reaction when handled and stored according to provisions. (Health hazards : None) . Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol. Provide fresh air.

Respiratory protection necessary at: generation/formation of aerosols , insufficient ventilation , insufficient exhaust .

Protective measures

Measures to prevent fire

No special fire protection measures are necessary.

Measures to prevent aerosol and dust generation

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Specific requirements or handling rules

No special measures are necessary.

7.2 Conditions for safe storage, including any incompatibilities

Packaging materials

Unsuitable container/equipment material: Zinc

Requirements for storage rooms and vessels

Floors should be impervious, resistant to liquids and easy to clean. Make sure spills can be contained, e.g. in sump pallets or kerbed areas. Shafts and sewers must be protected from entry of the product. Keep/Store only in original container. Protect containers against damage. Ensure adequate ventilation of the storage area.

Hints on joint storage

Possibility of hazardous reactions : Oxidising agent .

Storage class (TRGS 510) : 10

Further information on storage conditions

Keep/Store only in original container. Keep in a cool, well-ventilated place.

Do not store at temperatures below : 0 °C .

Recommended storage temperature : 5 °C - 40 °C .

Protect against : Protect against direct sunlight. Keep away from heat.

Storage stability : 24 months . Observe technical data sheet.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

Distillates (petroleum), hydrotreated light paraffinic ; CAS No. : 64742-55-8

Limit value type (country of origin) : TWA (EC)

Limit value : 5 mg/m³

Version :

Limit value type (country of origin) : TLV/TWA (EC)

Limit value : 5 mg/m³

Version :

2,6-Di-tert-Butyl-p-cresol ; CAS No. : 128-37-0

Limit value type (country of origin) : TRGS 900 (D)

Parameter : measured as the inhaleable fraction

Limit value : 10 mg/m³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Eni metalCut 22 TB; Art.-no. 960
Revision : 17.02.2017
Print date : 27.02.2017

Version (Revision) : 5.0.0 (4.0.0)

Version :
Limit value type (country of origin) : TRGS 900 (D)
Parameter : alveolar particles
Limit value : 3 mg/m³
Version :

8.2 Exposure controls

A substance-tailored exposure-driven testing according to REACH, annex XI, chapter 3 was not performed.

Appropriate engineering controls

See section 7. No additional measures necessary.

Personal protection equipment

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Eye/face protection

Additional eye protection measures : Wear eye/face protection.

Skin protection

Hand protection

Tested protective gloves must be worn Breakthrough time (maximum wearing time) : 4 hours (NBR (Nitrile rubber) , Thickness of the glove material : 0,4 mm) . See information supplied by the manufacturer.

Unsuitable material : Butyl caoutchouc (butyl rubber) , NR (natural rubber, natural latex) , CR (polychloroprene, chloroprene rubber)

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Fresh air masks are recommended, or combination filters A2-P2 for works of short duration.

General health and safety measures

Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work. Keep away from food, drink and animal feeding stuffs. Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : liquid

Colour : light brown

Odour

characteristic

Safety relevant basis data

Melting point/melting range :		not applicable	Literature value
Decomposition temperature :		not determined	
Flash point :		180 °C	
Lower explosion limit :		not determined	
Upper explosion limit :		not determined	
Danger of explosion:		formation of explosive mixture possible	
Density :	(20 °C)	0,88 g/cm ³	DIN 51757
Relative density :	(20 °C)	not determined	
Solubility in / Miscibility with Water:		Insoluble	
pH :	(23 °C / 50 g/l)	not applicable	DIN 51 369
pH-Wert, Konzentration unbestimmt oder bei Sättigungskonzentration :	(20 °C)		
log P O/W :		not determined	
Viscosity kinematic:	(40 °C)	19,3 mm ² /s	DIN 51562
Odour threshold :		not determined	
Relative vapour density :	(20 °C)	not determined	
Vapourisation rate :		not determined	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Eni metalCut 22 TB; Art.-no. 960
Revision : 17.02.2017
Print date : 27.02.2017

Version (Revision) : 5.0.0 (4.0.0)

Oxidising liquids : Not oxidising.

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non-reactive under normal use conditions.

10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

In case of exceeding the storage temperature: Danger of bursting container.

10.5 Incompatible materials

Reaction with oxidizing agents possible. Acid

10.6 Hazardous decomposition products

Does not decompose when used for intended uses. Thermal decomposition can lead to the escape of irritating gases and vapours.

Hazardous decomposition products : Carbon monoxide , Carbon dioxide , aldehydes , Ketone , Sulphur oxides , Nitrogen oxides (NOx)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter :	LD50 (Distillates (petroleum), hydrotreated light paraffinic ; CAS No. : 64742-55-8)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (Zinc-bis[0,0-bis(2-ethylhexyl)]bis(dithiophosphate) ; CAS No. : 4259-15-8)
Exposure route :	Oral
Species :	Rat
Effective dose :	3100 mg/kg
Parameter :	LD50 (2,6-Di-tert-Butyl-p-cresol ; CAS No. : 128-37-0)
Exposure route :	Oral
Species :	Rat
Effective dose :	890 - 2930 mg/kg
Parameter :	LD50 (2,6-Di-tert-Butyl-p-cresol ; CAS No. : 128-37-0)
Exposure route :	Oral
Species :	Mouse
Effective dose :	1040 mg/kg

Based on available data, the classification criteria are not met.

Acute dermal toxicity

Parameter :	LD50 (Distillates (petroleum), hydrotreated light paraffinic ; CAS No. : 64742-55-8)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (Zinc-bis[0,0-bis(2-ethylhexyl)]bis(dithiophosphate) ; CAS No. : 4259-15-8)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	5001 mg/kg
Parameter :	LD50 (2,6-Di-tert-Butyl-p-cresol ; CAS No. : 128-37-0)
Exposure route :	Dermal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Eni metalCut 22 TB; Art.-no. 960
Revision : 17.02.2017
Print date : 27.02.2017

Version (Revision) : 5.0.0 (4.0.0)

Species : Rabbit
Effective dose : > 2000 mg/kg

Based on available data, the classification criteria are not met.

Acute inhalation toxicity

Parameter : LC50 (Distillates (petroleum), hydrotreated light paraffinic ; CAS No. : 64742-55-8)
Exposure route : Inhalation
Species : Rat
Effective dose : > 5000 mg/m³
Exposure time : 4 h

Based on available data, the classification criteria are not met.

Irritant and corrosive effects

Primary irritation to the skin

Based on available data, the classification criteria are not met.

Irritation to eyes

Parameter : Irritation to eyes (Zinc-bis[0,0-bis(2-ethylhexyl)]bis(dithiophosphate) ; CAS No. : 4259-15-8)
Species : Rabbit
Effective dose : >= 50 %
Exposure time : 72 h

Based on available data, the classification criteria are not met.

Irritation to respiratory tract

Based on available data, the classification criteria are not met.

Sensitisation

In case of skin contact

Based on available data, the classification criteria are not met.

In case of inhalation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.3 Symptoms related to the physical, chemical and toxicological characteristics

In case of ingestion

No known symptoms to date.

In case of skin contact

No known symptoms to date.

In case of inhalation

No known symptoms to date.

In case of eye contact

No known symptoms to date.

SECTION 12: Ecological information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Eni metalCut 22 TB; Art.-no. 960
Revision : 17.02.2017
Print date : 27.02.2017

Version (Revision) : 5.0.0 (4.0.0)

12.1 Toxicity

There are no data available on the mixture itself.

Aquatic toxicity

Acute (short-term) algae toxicity

Parameter :	EC50 (Zinc-bis[0,0-bis(2-ethylhexyl)]bis(dithiophosphate) ; CAS No. : 4259-15-8)
Species :	Daphnia
Effective dose :	1 - 10 mg/l
Parameter :	EC50 (Isopropylated triphenyl phosphate ; CAS No. : 68937-41-7)
Species :	Daphnia
Effective dose :	> 1000 mg/l
Exposure time :	48 h
Parameter :	EC0 (2,6-Di-tert-Butyl-p-cresol ; CAS No. : 128-37-0)
Species :	Daphnia
Effective dose :	> 0,3 mg/l
Exposure time :	48 h
Parameter :	EC50 (2,6-Di-tert-Butyl-p-cresol ; CAS No. : 128-37-0)
Species :	Algae
Effective dose :	> 0,42 mg/l
Exposure time :	72 h

12.2 Persistence and degradability

There are no data available on the mixture itself.

12.3 Bioaccumulative potential

There are no data available on the mixture itself.

12.4 Mobility in soil

There are no data available on the mixture itself.

12.5 Results of PBT and vPvB assessment

There are no data available on the mixture itself.

12.6 Other adverse effects

There are no data available on the mixture itself.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Recycle according to official regulations.

13.1 Waste treatment methods

Product/Packaging disposal

The waste is to be kept separate from other types of waste until its recycling. Recycle according to official regulations. Waste for recycling is to be classified and labelled.

Waste codes/waste designations according to EWC/AVV

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Waste code product

List of proposed waste codes/waste designations in accordance with AAV : 130208

Waste code packaging

List of proposed waste codes/waste designations in accordance with AAV : 150110

Properties of waste which render it hazardous

Ecotoxic.

Waste treatment options

Appropriate disposal / Product

Evidence for disposal must be provided. Send to a physico-chemical treatment facility under observation of official regulations.

Appropriate disposal / Package

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Eni metalCut 22 TB; Art.-no. 960
Revision : 17.02.2017
Print date : 27.02.2017

Version (Revision) : 5.0.0 (4.0.0)

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Non-contaminated packages must be recycled or disposed of. Packing which cannot be properly cleaned must be disposed of. Handle contaminated packages in the same way as the substance itself. Evidence for disposal must be provided.

Other disposal recommendations

Dispose according to legislation. Do not allow to enter into surface water or drains.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

REACH Regulation – the European Parliament and Council Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals

CLP Regulation – the European Parliament and Council Regulation (EC) No 1272/2008 concerning reclassification, labelling and packaging of substances and mixtures

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]. This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH : None

Other regulations (EU)

Regulation (EC) No. 1005/2009 on substances that lead to the depletion of the ozone layer

not relevant

National regulations

Water hazard class (WGK)

Class : 1 (Slightly hazardous to water) Classification according to VwVwS

15.2 Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

01. Relevant identified uses · 02. Classification of the substance or mixture · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 02. Special rules for supplemental label elements for certain mixtures · 03. Hazardous ingredients · 03. Composition / Information on ingredients - Additional information · 06. Methods and material for containment and cleaning up - For cleaning up · 07. Protective measures - Measures to prevent aerosol and dust generation · 07. Packaging materials · 07. Hints on joint storage - Storage class · 07. Further information on storage conditions - Storage stability · 08. Occupational exposure limit values · 08. Respiratory protection · 09. Physical state · 11. Aspiration hazard · 13. Waste code product · 13. Appropriate disposal / Product · 13. Properties of waste which render it

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Eni metalCut 22 TB; Art.-no. 960
Revision : 17.02.2017
Print date : 27.02.2017

Version (Revision) : 5.0.0 (4.0.0)

hazardous

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

Data arise from reference works and literature.

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

Please refer to our internet website for more information: See section 1.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.