

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** eni metalCut 10 UNI, Art.-no. 0383  
**Revision date :** 01.04.2015  
**Print date :** 17.04.2015

**Version (Revision) :** 3.0.0 (1.0.1)

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

eni metalCut 10 UNI

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Metal working fluids

##### Uses advised against

No information available.

#### 1.3 Details of the supplier of the safety data sheet

##### Supplier (manufacturer/importer/downstream user/distributor)

Eni Schmiertechnik GmbH

**Street :** Paradiesstraße 14

**Postal code/city :** 97080 Würzburg

**Telephone :** (+49) 931-90098-0

**Telefax :** (+49) 931-98442

**Information contact :** Technical Department, Tel. (+49) 931 900 98-142

**email:** [technik.wuerzburg@agip.de](mailto:technik.wuerzburg@agip.de), [www.enischmiertechnik-datenblaetter.de](http://www.enischmiertechnik-datenblaetter.de)

#### 1.4 Emergency Telephone Number

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Category 3 ; Harmful to aquatic life with long lasting effects.

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard pictograms



Health hazard (GHS08)

##### Signal word

Danger

##### Hazard components for labelling

Distillates (petroleum), hydrotreated light paraffinic ; CAS No. : 64742-55-8

##### Hazard statements

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

##### Precautionary statements

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** eni metalCut 10 UNI, Art.-no. 0383  
**Revision date :** 01.04.2015  
**Print date :** 17.04.2015

**Version (Revision) :** 3.0.0 (1.0.1)

P405 Store locked up.  
P501 Dispose of contents/container according to national legislations.

### 2.3 Other hazards

None

## SECTION 3: Composition / information on ingredients

### 3.2 Mixtures

#### Description

Preparation of solvent refined mineral oils with low content of aromatic hydrocarbons and additives.

#### Hazardous ingredients

Distillates (petroleum), hydrotreated light paraffinic ; REACH registration No. : 01-2119487077-29-0002 ; EC No. : 265-158-7; CAS No. : 64742-55-8

Weight fraction :  $\geq 50\%$   
Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304

2,6-DI-TERT-BUTYL-P-CRESOL ; REACH registration No. : 01-2119565113-46-0000 ; EC No. : 204-881-4; CAS No. : 128-37-0

Weight fraction : 0,25 - 0,5 %  
Classification 1272/2008 [CLP] : Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

#### Additional information

Full text of R-, H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice.

#### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. Where appropriate artificial ventilation. In case of respiratory tract irritation, consult a physician.

#### In case of skin contact

Change contaminated, saturated clothing. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

#### After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Call a physician immediately. Rinse mouth thoroughly with water. Where appropriate artificial ventilation. Observe risk of aspiration if vomiting occurs. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

#### Self-protection of the first aider

No direct artificial respiration to be given by first aider. No mouth-to-mouth or mouth-to-nose resuscitation. Use Ambu bag or ventilator.

Protect your self against exposure to chemicals or blood-borne diseases by wearing gloves and eye protection. After providing first aid wash your exposed skin with soap and water.

### 4.2 Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Cough Respiratory complaints Dyspnoea Fever Symptoms can occur only after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni metalCut 10 UNI, Art.-no. 0383  
Revision date : 01.04.2015  
Print date : 17.04.2015

Version (Revision) : 3.0.0 (1.0.1)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Foam, Extinguishing powder, Carbon dioxide (CO<sub>2</sub>), Water spray, Water mist

#### Unsuitable extinguishing media

Strong water jet

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide, Nitrogen oxides (NO<sub>x</sub>), Smoke and other incomplete combustion products.

### 5.3 Advice for firefighters

#### Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

### 5.4 Additional information

Do not inhale explosion and combustion gases. Use water spray jet to protect personnel and to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Avoid contact with skin, eyes and clothes. Wear breathing apparatus if exposed to vapours/aerosols. Ventilate affected area. Vapours can form explosive mixtures with air. Remove all sources of ignition.

### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Make sure spills can be contained, e.g. in sump pallets or kerbed areas. In case of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3 Methods and material for containment and cleaning up

#### For containment

Stop and contain spill/release if it can be done safely. Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

#### For cleaning up

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically, placing in appropriate containers for disposal. Ventilate affected area. Clean contaminated objects and areas thoroughly observing environmental regulations.

### 6.4 Reference to other sections

See Section 8 for information on appropriate personal protective equipment.

See Section 12 for environmental precautions.

See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Use only in well-ventilated areas. Put lids on containers immediately after use. Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists Keep away from sources of ignition. - No smoking. Use only antistatically equipped (spark-free) tools.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** eni metalCut 10 UNI, Art.-no. 0383  
**Revision date :** 01.04.2015  
**Print date :** 17.04.2015

**Version (Revision) :** 3.0.0 (1.0.1)

### Protective measures

#### Measures to prevent fire

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Take precautionary measures against static discharge.

#### Environmental precautions

Do not allow to enter into surface water or drains.

### Advices on general occupational hygiene

When using do not eat, drink, smoke. Wash hands before breaks and after work.

## 7.2 Conditions for safe storage, including any incompatibilities

### Packaging materials

Only use containers specifically approved for the substance/product.

### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect containers against damage. Provide earthing of containers, equipment, pumps and ventilation facilities.

### Hints on joint storage

Keep away from: Oxidising agent

**Storage class :** 10

### Do not store together with

Food and feedingstuffs

### Further information on storage conditions

**Recommended storage temperature :** 5 - 40°C / 40 - 105°F.

**Protect against :** Frost, Heat, UV-radiation/sunlight, Water Humidity.

**Storage stability :** Product may be stored for up to 24 months under described conditions.

## 7.3 Specific end use(s)

None

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

2,6-DI-TERT-BUTYL-P-CRESOL ; CAS No. : 128-37-0

Limit value type (country of origin) : TRGS 900 ( D )

Parameter : E: inhalable fraction

Limit value : 10 mg/m<sup>3</sup>

Peak limitation : 4(II)

Remark : Y

Version : 01.09.2012

metal working coolant

Limit value type (country of origin) : AGW ( D )

Parameter : vapour + aerosol

Limit value : 10 mg/m<sup>3</sup>

Version :

#### DNEL/DMEL and PNEC values

##### DNEL/DMEL

Limit value type : DNEL/DMEL (Industrial) ( 2,6-DI-TERT-BUTYL-P-CRESOL ; CAS No. : 128-37-0 )

Exposure route : Dermal

Exposure frequency : chronic / systemic effects

Limit value : 8,3 mg/kg

Limit value type : DNEL/DMEL (Industrial) ( 2,6-DI-TERT-BUTYL-P-CRESOL ; CAS No. : 128-37-0 )

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** eni metalCut 10 UNI, Art.-no. 0383  
**Revision date :** 01.04.2015  
**Print date :** 17.04.2015

**Version (Revision) :** 3.0.0 (1.0.1)

Exposure route : Inhalation  
Exposure frequency : chronic / systemic effects  
Limit value : 5,8 mg/m<sup>3</sup>

### Remark

The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation.

### PNEC

Limit value type : Fresh water : ( 2,6-DI-TERT-BUTYL-P-CRESOL ; CAS No. : 128-37-0 )  
Limit value : 0,004 mg/l  
Limit value type : Sea water : ( 2,6-DI-TERT-BUTYL-P-CRESOL ; CAS No. : 128-37-0 )  
Limit value : 0,0004 mg/l  
Limit value type : Sediment (fresh water) : ( 2,6-DI-TERT-BUTYL-P-CRESOL ; CAS No. : 128-37-0 )  
Limit value : 1,29 mg/kg  
Limit value type : Sewage plant : ( 2,6-DI-TERT-BUTYL-P-CRESOL ; CAS No. : 128-37-0 )  
Limit value : 100 mg/l  
Limit value type : Soil : ( 2,6-DI-TERT-BUTYL-P-CRESOL ; CAS No. : 128-37-0 )  
Limit value : 1,04 mg/kg

## 8.2 Exposure controls

### Appropriate engineering controls

Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

### Personal protection equipment

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

### Eye/face protection

Eye glasses with side protection (DIN EN 166)

### Skin protection

#### Hand protection

Tested protective gloves must be worn: DIN EN 374

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Check leak tightness/impermeability prior to use.

#### Suitable material :

Wearing time with permanent contact:

Material: NBR (Nitrile rubber), CR (polychloroprene, chloroprene rubber), PVA (Polyvinyl alcohol),

Thickness of the glove material: 0,70 mm

Breakthrough time (maximum wearing time): > 480 min

Wearing time with occasional contact (splashes):

Material: NBR (Nitrile rubber), CR (polychloroprene, chloroprene rubber), PVA (Polyvinyl alcohol),

Thickness of the glove material: 0,40 mm

Breakthrough time (maximum wearing time): > 30 min

**Breakthrough time (maximum wearing time):** : For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Body protection

Body protection: not required. If prolonged or repeated contact is likely, chemical, and oil resistant clothing is recommended.

#### Other protection measures

When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

### Respiratory protection

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** eni metalCut 10 UNI, Art.-no. 0383  
**Revision date :** 01.04.2015  
**Print date :** 17.04.2015

**Version (Revision) :** 3.0.0 (1.0.1)

Usually no personal respiratory protection necessary.  
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.  
Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation aerosol or mist formation.

#### Suitable respiratory protection apparatus

Combination filtering device (EN 14387)

#### General health and safety measures

When using do not eat, drink, smoke. Wash hands before breaks and after work. Wash contaminated clothing prior to re-use. Do not put any product-impregnated cleaning rags into your trouser pockets. Apply skin care products after work.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**Appearance :** liquid

**Colour :** colourless

**Odour :** mineral oil like

#### Safety relevant basis data

<b>pH value :</b>			No data available	
<b>Melting point/melting range :</b>	<		-10 °C	
<b>Boiling temperature :</b>	( 1013 hPa )	>	200 °C	
<b>Flash point :</b>			150 - 0 °C	DIN EN ISO 2592
<b>Flammability (Solid, Gas):</b>			not applicable	
<b>Lower explosion limit :</b>			0,6 Vol-%	
<b>Upper explosion limit :</b>			6,5 Vol-%	
<b>Vapour pressure :</b>	( 20 °C )		No data available	
<b>Vapour Density (Air = 1):</b>			no data available	
<b>Evaporation Rate :</b>			no data available	
<b>Density :</b>	( 15 °C )		0,827 g/cm <sup>3</sup>	DIN EN ISO 12185
<b>Water solubility :</b>	( 20 °C )		non miscible	
<b>Partition Coefficient (n-octanol/water):</b>	( log Pow )		not applicable	
<b>Viscosity :</b>	( 40 °C )	ca.	8 mm <sup>2</sup> /s	DIN EN ISO 3104
<b>Ignition temperature :</b>	>		200 °C	
<b>Decomposition temperature :</b>			No data available	
<b>Odour threshold :</b>			No data available	
<b>Oxidizing Properties:</b>			not oxidising	
<b>Explosive Properties:</b>			not explosive	

### 9.2 Other information

None

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

### 10.4 Conditions to avoid

No information available.

### 10.5 Incompatible materials

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** eni metalCut 10 UNI, Art.-no. 0383  
**Revision date :** 01.04.2015  
**Print date :** 17.04.2015

**Version (Revision) :** 3.0.0 (1.0.1)

Oxidising agent, strong.

### 10.6 Hazardous decomposition products

Hazardous decomposition products are not expected to form during normal storage.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Toxicological data are not available. The statement is derived from the properties of the single components. Data apply to the main component.

#### Acute effects

No data available to indicate product may be an acute toxic oral, dermal or inhalation hazard.

##### Acute oral toxicity

Parameter : LD50 ( Distillates (petroleum), hydrotreated light paraffinic ; CAS No. : 64742-55-8 )  
Exposure route : Oral  
Species : Rat  
Effective dose : > 5000 mg/kg

##### Acute dermal toxicity

Parameter : LD50 ( Distillates (petroleum), hydrotreated light paraffinic ; CAS No. : 64742-55-8 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : > 5000 mg/kg

##### Acute inhalation toxicity

Parameter : LC50 ( Distillates (petroleum), hydrotreated light paraffinic ; CAS No. : 64742-55-8 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : > 5 mg/l  
Exposure time : 4 h

#### Irritant and corrosive effects

Not an irritant.

##### Primary irritation to the skin

Parameter : Primary irritation to the skin ( Distillates (petroleum), hydrotreated light paraffinic ; CAS No. : 64742-55-8 )  
Result : Mild effects but not relevant for classification.

##### Irritation to eyes

Parameter : Irritation to eyes ( Distillates (petroleum), hydrotreated light paraffinic ; CAS No. : 64742-55-8 )  
Result : Mild effects but not relevant for classification.

#### Sensitisation

not sensitising.

##### In case of skin contact

Parameter : Skin sensitisation ( Distillates (petroleum), hydrotreated light paraffinic ; CAS No. : 64742-55-8 )  
Species : Guinea pig  
Result : negativ

#### Repeated dose toxicity (subacute, subchronic, chronic)

##### Subacute dermal toxicity

Has degreasing effect on the skin.

#### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

##### Carcinogenicity

no known significant effects or critical hazards.

##### Germ cell mutagenicity/Genotoxicity

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** eni metalCut 10 UNI, Art.-no. 0383  
**Revision date :** 01.04.2015  
**Print date :** 17.04.2015

**Version (Revision) :** 3.0.0 (1.0.1)

no known significant effects or critical hazards.

### **Reproductive toxicity**

no known significant effects or critical hazards.

### **Specific target organ toxicity (single exposure)**

#### **STOT SE 1 and 2**

Not expected to cause organ damage from a single exposure.

### **Specific target organ toxicity (repeated exposure)**

#### **STOT RE 1 and 2**

Not expected to cause organ damage from prolonged or repeated exposure.

### **Aspiration hazard**

May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material. For viscosity data, see chapter 9.

### **11.3 Other adverse effects**

Processing vapours can irritate the respiratory tracts, skin and eyes.

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

For the product ecotoxicological data are not available. The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see chapter 3).

#### **Aquatic toxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

##### **Acute (short-term) fish toxicity**

Parameter : LC50 ( 2,6-DI-TERT-BUTYL-P-CRESOL ; CAS No. : 128-37-0 )  
Species : Brachydanio rerio (zebra-fish)  
Effective dose : > 0,57 mg/l  
Exposure time : 96 h  
Evaluation : Very toxic to fish.

##### **Acute (short-term) daphnia toxicity**

Parameter : EC50 ( 2,6-DI-TERT-BUTYL-P-CRESOL ; CAS No. : 128-37-0 )  
Species : Daphnia magna (Big water flea)  
Effective dose : > 0,17 mg/l  
Exposure time : 48 h  
Evaluation : Very toxic to daphnia.

##### **Acute (short-term) algae toxicity**

Parameter : IC50 ( 2,6-DI-TERT-BUTYL-P-CRESOL ; CAS No. : 128-37-0 )  
Species : Desmodesmus subspicatus  
Effective dose : > 0,42 mg/l  
Exposure time : 72 h  
Evaluation : Very toxic to algae.

### **12.2 Persistence and degradability**

#### **Abiotic degradation**

##### **Physicochemical elimination**

Poorly watersoluble product. Can be mechanically precipitated to a large extent in biological sewage plants.

##### **Biodegradation**

Part of the components is biodegradable.

### **12.3 Bioaccumulative potential**

Contains components with the potential to bioaccumulate.

### **12.4 Mobility in soil**

Floats on water.



# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** eni metalCut 10 UNI, Art.-no. 0383  
**Revision date :** 01.04.2015  
**Print date :** 17.04.2015

**Version (Revision) :** 3.0.0 (1.0.1)

Adsorbs to soil and has low mobility.

### 12.5 Results of PBT and vPvB assessment

The substance does not fulfill the screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

### 12.6 Other adverse effects

Damage can be caused through mechanical influence of the product (eg. sticking).

### 12.7 Further ecological information

Do not allow uncontrolled discharge of product into the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product/Packaging disposal

##### Waste codes/waste designations according to EWC/AVV

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

##### Waste code product

12 01 07\*

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

##### Waste name

Mineral-based machining oils free of halogens (except emulsions and solutions).

##### Waste treatment options

##### Appropriate disposal / Product

Can be incinerated together with household waste in compliance with applicable technical regulations following consultation with approved waste disposal management companies and authorities in charge.

##### Appropriate disposal / Package

Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of. Dispose of waste according to applicable legislation.

##### Other disposal recommendations

Containers, even those that have been emptied, can contain product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, drill, grind, weld or perform similar operations on or near containers.

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

### 14.1 UN number

No dangerous goods in sense of this transport regulation.

### 14.2 UN proper shipping name

No dangerous goods in sense of this transport regulation.

### 14.3 Transport hazard class(es)

No dangerous goods in sense of this transport regulation.

### 14.4 Packing group

No dangerous goods in sense of this transport regulation.

### 14.5 Environmental hazards

No dangerous goods in sense of this transport regulation.

### 14.6 Special precautions for user

None

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** eni metalCut 10 UNI, Art.-no. 0383  
**Revision date :** 01.04.2015  
**Print date :** 17.04.2015

**Version (Revision) :** 3.0.0 (1.0.1)

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulations

##### Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : < 5 %

##### Water hazard class (WGK)

Class : 1 (Slightly hazardous to water) Classification according to VwVwS

#### 15.2 Chemical Safety Assessment

No information available.

### SECTION 16: Other information

#### 16.1 Indication of changes

None

#### 16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CLP: Regulation for Classification, Labelling and Packaging

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EC50: Effective concentration, 50 percent

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

#### 16.3 Key literature references and sources for data

Sources of information used in preparing this SDS included one or more of the following: Product Dossiers and SDS from suppliers, complemented by public sources, as appropriate (GESTIS, the EU IUCLID Data Base, U.S. NTP publications, e.g.).

#### 16.4 Relevant H- and EUH-phrases (Number and full text)

H304 May be fatal if swallowed and enters airways.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

#### 16.5 Training advice

Provide adequate information, instruction and training for operators.

#### 16.6 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**



**Trade name :** eni metalCut 10 UNI, Art.-no. 0383  
**Revision date :** 01.04.2015  
**Print date :** 17.04.2015

**Version (Revision) :** 3.0.0 (1.0.1)

---

mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---