



## Agip Additiv EP BU

**Agip Additiv EP BU** is a mixture of fatty acid ester and agents to improve the lubrication properties of not water miscible cooling lubricants.

### Characteristics (typical figures):

Additiv EP BU		Unit	Test method
Colour number	1		
Viscosity at 40°C	65	mm <sup>2</sup> /s	DIN 51 562
Density at 20°C	900	kg/m <sup>3</sup>	DIN 51 757
Flashpoint	360	°C	DIN ISO 2592
Copper corrosion	1-100A3	Corr.-grade	ASTM D 130

### Properties and Performance:

- increases the lubrication effect
- compatible with cupreous materials
- homogeneous mixture in mineral oils

### Applications:

**Agip Additiv EP BU** is an agent package to improve the lubrication effect of not water miscible cooling lubricants. It is added according to the requirement 1 - 15%. The addition can take place by dumping.

### Information:

Observe the valid VDI Guidelines 3035 and 3397 (1 - 3) when using the product. To maintain the function of a cooling lubricant the product has to be stored frost free.

The product is a water hazardous liquid.

The BGR/GUV-R 143 - Operations with cooling lubricants - has to be observed for safe handling.

For specific technical questions please contact our technical department. Get information in reference to our training seminar about the subject cooling lubricants.