



eni i-Ride PG 15W-50

eni i-Ride PG 15W-50 is a semi-synthetic high-performance multigrade oil of the newest technology and is applicable for air as well as water cooled 4-stroke engines, especially at severe conditions.

Characteristics (typical figures):

eni i-Ride PG 15W-50		Unit	15W-50	Test method
Kin. Viscosity	at -25°C	mm ² /s	6700	
	at 40°C	mm ² /s	126	DIN 51561
	at 100°C	mm ² /s	17,4	ASTM D 445
Viscosity index			154	DIN ISO 2909
Density at 15°C		kg/m ³	880	ASTM D 1298
Flashpoint o. C.		°C	220	ASTM D 92
Pourpoint		°C	-27	ASTM D 97

Properties and Performance:

- ⇒ **eni i-Ride PG 15W-50** has sufficient flowability at low temperatures and a high Viscosity in the upper temperature range. Therefore this lubricant can be used as all-year oil.
- ⇒ Its excellent detergent/dispersant properties minimize the liner lacquering and the formation of deposits in the engine. Therefore **eni i-Ride PG 15W-50** prevents the jamming of the piston rings and keeps possible deposits in suspense.
- ⇒ Its excellent wear protection properties ensure a long lifetime of all moving parts. Due to the high surface adhesion a low-wear engine start is ensured also after longer downtime.

Applications:

eni i-Ride PG 15W-50 is best suitable for very different and severe operation conditions, such as long-distance travel at high temperatures or stop-and-go travel at low temperatures.

Specifications:

eni i-Ride PG 15W-50 meets the following specifications and approvals:

ACEA A3
 API SJ
 Jaso MA, Jaso MA2
 PIAGGIO-GROUP