

Gas engine oil

AUTOL Gasmotorenöl ELA 40

SAE 40
with medium content of sulphated
ash

MAN M 3271-2

Deutz Gas engine oil
MWM
MTU

MDE
Caterpillar
Jenbacher TA 1000-1107*

AUTOL Gasmotorenöl ELA 40 is a gas engine oil with a medium content of sulphated ash for engines that are operated with natural gas or slightly aggressive combustion gases.

Characteristics (typical figures):

Viscosity	at 40°C	mm ² /s	138
	at 100°C	mm ² /s	14,0
Viscosity index			97
Density at 15°C		kg/m ³	872
Flashpoint o. C.		°C	254
Pour point		°C	-12
Sulphated ash		%m/m	0,5
BN		mgKOH/g	5,5

AUTOL Gasmotorenöl ELA 40 has a high ageing stability as well as a very good wear protection and prevents piston deposits, sludging and coking. Due to the application of selected base oils the oil consumption is minimised and due to the alkaline reserve long oil-change intervals are ensured, depending on the actual conditions on spot and the used gas quality.

Applications:

AUTOL Gasmotorenöl ELA 40 is an effective gas engine oil for engines with and without exhaust gas treatment that are operated with natural gas, however also suitable for bio gas and sewage gas if this is approved by the engine manufacturer.

AUTOL Gasmotorenöl ELA 40 is approved by name respectively meets the requirements* of the above listed specifications.

Please observe the manufacturer's specifications when selecting products.