



eni Rotra ATF II D

eni Rotra ATF II D is a special fluid mainly suitable in modern automatic transmissions and in many other applications where very low temperature performance, stability to mechanical loads and high Viscosity Index are required. **eni Rotra ATF II D** is specifically designed for filling and topping-up automatic transmissions built by makers who recommend the use of GM DEXRON II D type products.

CHARACTERISTICS (TYPICAL FIGURES):

Eni Rotra ATF II D	Unit	Test metod
Kin. Viscosity	at 40°C	mm ² /s
	at 100°C	mm ² /s
	at -40°C	mPa.s
Viscosity index		
Density at 15°C	kg/m ³	
Flashpoint o. C.	°C	
Pourpoint	°C	

PROPERTIES AND PERFORMANCE

- Careful selection of the Viscosity Index improver ensures excellent viscosity characteristics even after extended service.
- Its very low pour point guarantees excellent performance at the lowest service temperatures
- Its correctly balanced friction modifiers ensure quiet, smooth operation resulting in optimum transmission efficiency.
- **eni Rotra ATF II D** has an excellent oxidation stability thus preventing deterioration of components at very high temperatures and avoiding any sludge formation tendency.
- Its good detergent-dispersant properties help keep impurities in suspension preventing deposit formation.
- Its EP additives help minimize wear and guard against damage to gear surfaces.
- **eni Rotra ATF II D** is not corrosive to steel and copper and to ferrous and nonferrous alloys in general.
- Its antirust properties inhibit rust formation in the hydraulic systems of automatic transmissions.
- Its antifoam qualities minimize any tendency to foaming formation that could adversely affect oil circulation and lubricating properties.
- **eni Rotra ATF II D** is perfectly compatible with all types of rubber used in gaskets and seals.



eni Rotra ATF II D

SPECIFICATIONS

eni Rotra ATF II D is officially approved or meets the requirements of the following specifications:

- GM DEXRON II D
- FORD MERCON
- MAN 339 Typ V1, Typ Z-1
- MB 236.6
- VOITH H55.6335.xx
- ZF TE-ML 04D, 05L, 09, 11A, 14A, 17C
- ALLISON C4
- CATERPILLAR TO-2