

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet HD EP FAD, Art.-no. 0438
Revision date : 11.09.2015
Print date : 06.07.2016

Version (Revision) : 3.0.0 (1.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

eni aquamet HD EP FAD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Metal working fluids

Uses advised against

No information available.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/downstream user/distributor)

Eni Schmiertechnik GmbH

Street : Paradiesstraße 14

Postal code/city : 97080 Würzburg

Telephone : (+49) 931-90098-0

Telefax : (+49) 931-98442

Information contact : Technical Department, Tel. (+49) 931 900 98-142

email: technik.wuerzburg@agip.de, www.enischmiertechnik-datenblaetter.de

1.4 Emergency Telephone Number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Category 3 ; Harmful to aquatic life with long lasting effects.

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2A ; Causes serious eye irritation.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Warning

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P264 Wash hands thoroughly after handling.

P273 Avoid release to the environment.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet HD EP FAD, Art.-no. 0438
Revision date : 11.09.2015
Print date : 06.07.2016

Version (Revision) : 3.0.0 (1.0.0)

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P337+P313 If eye irritation persists: Get medical advice/attention.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352 IF ON SKIN: Wash with plenty of water/....
Special rules for supplemental label elements for certain mixtures
EUH208 Contains 2,2'-[[[(5-methyl-1H-benzotriazol-1-yl)methyl] imino]bisethanol ; 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Preparation of solvent refined mineral oils with low content of aromatic hydrocarbons and additives.

Hazardous ingredients

Alcohols, C16-18 and C18-unsatd., ethoxylated ; REACH registration No. : 01-2119489407-26 ; EC No. : 500-236-9; CAS No. : 68920-66-1

Weight fraction : 10 - 15 %
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Aquatic Chronic 2 ; H411

BORIC ACID ; REACH registration No. : 01-2119486683-25- ; EC No. : 233-139-2; CAS No. : 10043-35-3

Weight fraction : < 5,5 %
Classification 1272/2008 [CLP] : Repr. 1B ; H360FD

2-(2-BUTOXYETHOXY)ETHANOL ; REACH registration No. : 01-2119475104-44-0006 ; EC No. : 203-961-6; CAS No. : 112-34-5

Weight fraction : 1 - 5 %
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

2,2'-[[[(5-methyl-1H-benzotriazol-1-yl)methyl] imino]bisethanol ; EC No. : 279-501-3; CAS No. : 80584-88-9

Weight fraction : 0,1 - 0,5 %
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Sens. 1 ; H317 Aquatic Chronic 3 ; H412

1,2-BENZISOTHIAZOL-3(2H)-ONE ; EC No. : 220-120-9; CAS No. : 2634-33-5

Weight fraction : 0,005 - 0,05 %
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400

Further ingredients

The highly refined mineral oil contains less than 3% (w/w) DMSO-extract, according to IP 346 and is not considered to be carcinogenic.

Additional information

Full text of R-, H- and EUH-phrases: see section 16.

3.3 Additional information

Contains Substances of the SVHC-Candidate List (Substances of Very High Concern): Boric Acid.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove victim out of the danger area. If unconscious place in recovery position and seek medical advice. When in doubt or if symptoms are observed, get medical advice.

Following inhalation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet HD EP FAD, Art.-no. 0438
Revision date : 11.09.2015
Print date : 06.07.2016

Version (Revision) : 3.0.0 (1.0.0)

Remove casualty to fresh air and keep warm and at rest. Where appropriate artificial ventilation. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Change contaminated, saturated clothing. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person or a person with cramps. Where appropriate artificial ventilation. Do NOT induce vomiting.

Self-protection of the first aider

No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam, Extinguishing powder, Carbon dioxide (CO₂), Sand, Water mist,

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide, Nitrogen oxides (NO_x), Smoke and other incomplete combustion products.

5.3 Advice for firefighters

Keep unnecessary and unprotected personnel from entering. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Do not inhale explosion and combustion gases. Remove persons to safety. Use water spray jet to protect personnel and to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Remove persons to safety. Avoid contact with skin, eyes and clothes. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Ventilate affected area. Remove all sources of ignition.

6.2 Environmental precautions

Cover drains. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Make sure spills can be contained, e.g. in sump pallets or kerbed areas. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet HD EP FAD, Art.-no. 0438
Revision date : 11.09.2015
Print date : 06.07.2016

Version (Revision) : 3.0.0 (1.0.0)

6.3 Methods and material for containment and cleaning up

For containment

Cover drains. Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control. Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Wipe up with absorbent material (eg. cloth, fleece). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically, placing in appropriate containers for disposal. Ventilate affected area. Clean contaminated articles and floor according to the environmental legislation.

6.4 Reference to other sections

See Section 8 for information on appropriate personal protective equipment.
See Section 12 for environmental precautions.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Wear personal protection equipment (refer to section 8).
Use only in well-ventilated areas. Handle and open container with care. Avoid contact with skin, eyes and clothes. Do not breathe gas/fumes/vapour/spray. Special danger of slipping by leaking/spilling product. Keep away from sources of ignition. - No smoking.

Protective measures

Measures to prevent fire

Usual measures for fire prevention.

Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Do not put any product-impregnated cleaning rags into your trouser pockets.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product. Protect containers against damage.

Hints on joint storage

Keep away from: Oxidising agent

Storage class : 10

Storage class (TRGS 510) : 10

Do not store together with

Food and feedingstuffs

Further information on storage conditions

Recommended storage temperature : 5 - 40°C / 40 - 105°F.

Protect against : Frost, Heat, UV-radiation/sunlight

Storage stability : Product may be stored for up to 12 months under described conditions.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet HD EP FAD, Art.-no. 0438
Revision date : 11.09.2015
Print date : 06.07.2016

Version (Revision) : 3.0.0 (1.0.0)

2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 10 ppm / 67 mg/m³
Peak limitation : 1,5(I)
Remark : Y
Version : 06.11.2015
Limit value type (country of origin) : STEL (EC)
Limit value : 15 ppm / 101,2 mg/m³
Version : 07.02.2006
Limit value type (country of origin) : TWA (EC)
Limit value : 10 ppm / 67,5 mg/m³
Version : 07.02.2006

BORIC ACID ; CAS No. : 10043-35-3
Limit value type (country of origin) : TRGS 900 (D)
Parameter : E: inhalable fraction
Limit value : 0,5 mg/m³
Peak limitation : 2(I)
Remark : Y
Version : 06.11.2015

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type : DNEL worker (systemic) (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 2080 mg/kg bw/d
Limit value type : DNEL worker (systemic) (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 294 mg/m³
Limit value type : DNEL worker (systemic) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 20 mg/kg
Limit value type : DNEL worker (systemic) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 67,5 mg/m³
Limit value type : DNEL worker (systemic) (BORIC ACID ; CAS No. : 10043-35-3)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 392 mg/kg bw/d
Limit value type : DNEL worker (systemic) (BORIC ACID ; CAS No. : 10043-35-3)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 8,8 mg/m³

Remark

The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet HD EP FAD, Art.-no. 0438
Revision date : 11.09.2015
Print date : 06.07.2016

Version (Revision) : 3.0.0 (1.0.0)

PNEC

Limit value type :	PNEC aquatic, freshwater (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Limit value :	0,002 mg/l
Limit value type :	PNEC aquatic, marine water (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Limit value :	0,002 mg/l
Limit value type :	PNEC sediment, freshwater (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Limit value :	6,33 mg/kg
Limit value type :	PNEC aquatic, freshwater (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Limit value :	1 mg/l
Limit value type :	PNEC aquatic, marine water (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Limit value :	0,1 mg/l
Limit value type :	PNEC sediment, freshwater (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Limit value :	4 mg/kg
Limit value type :	PNEC sediment, marine water (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Limit value :	0,4 mg/kg
Limit value type :	PNEC sewage treatment plant (STP) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Limit value :	200 mg/l
Limit value type :	PNEC aquatic, freshwater (BORIC ACID ; CAS No. : 10043-35-3)
Limit value :	1,35 mg/l
Limit value type :	PNEC aquatic, marine water (BORIC ACID ; CAS No. : 10043-35-3)
Limit value :	1,35 mg/l
Limit value type :	PNEC sediment, freshwater (BORIC ACID ; CAS No. : 10043-35-3)
Limit value :	1,8 mg/kg
Limit value type :	PNEC sediment, marine water (BORIC ACID ; CAS No. : 10043-35-3)
Limit value :	1,8 mg/kg
Limit value type :	PNEC sewage treatment plant (STP) (BORIC ACID ; CAS No. : 10043-35-3)
Limit value :	1,75 mg/l

8.2 Exposure controls

Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

Personal protection equipment

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Eye/face protection

Eye glasses with side protection DIN EN 166

Skin protection

Hand protection

Tested protective gloves must be worn (DIN EN 374). The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Do not wear gloves near rotary machines and tools.

Suitable material :

Wearing time with permanent contact:

Material: NBR (Nitrile rubber), CR (polychloroprene, chloroprene rubber),

Thickness of the glove material: 0,70 mm

Breakthrough time (maximum wearing time): > 480 min

Wearing time with occasional contact (splashes):

NBR (Nitrile rubber), CR (polychloroprene, chloroprene rubber),

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet HD EP FAD, Art.-no. 0438
Revision date : 11.09.2015
Print date : 06.07.2016

Version (Revision) : 3.0.0 (1.0.0)

Thickness of the glove material: 0,40 mm
Breakthrough time (maximum wearing time): > 30 min

Unsuitable material : PVA (Polyvinyl alcohol),

Breakthrough time (maximum wearing time): : For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

Body protection not required. If prolonged or repeated contact is likely, chemical, and oil resistant clothing is recommended.

Respiratory protection

Usually no personal respiratory protection necessary. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Respiratory protection necessary at: exceeding exposure limit values, insufficient ventilation, aerosol or mist formation.

General health and safety measures

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Do not put any product-impregnated cleaning rags into your trouser pockets. Wash contaminated clothing prior to re-use. Apply skin care products after work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : yellow

Odour : characteristic

Safety relevant basis data

pH :	(20 °C / 5 Wt %)	9,4	DIN 51369
Melting point/melting range :		not determined	
Initial boiling point and boiling range :	(1013 hPa)	> 100 °C	
Flash point :		> 130 °C	DIN EN ISO 2592
Flammability (Solid, Gas):		not applicable	
Lower explosion limit :		0,6 Vol-%	
Upper explosion limit :		6,5 Vol-%	
Vapour pressure :	(20 °C)	No data available	
Vapour Density (Air = 1):		no data available	
Evaporation Rate :		no data available	
Density :	(15 °C)	0,974 g/cm ³	DIN EN ISO 12185
Water solubility :	(20 °C)	miscible	
log P O/W :		not applicable	
Cinematic viscosity :	(20 °C)	170 mm ² /s	DIN EN ISO 3104
Ignition temperature :		> 240 °C	
Decomposition temperature :		No data available	
Odour threshold :		No data available	
Maximum VOC content (EC) :		3,5 Wt %	
Maximum VOC content (Switzerland) :		2 Wt %	
Oxidising liquids :	Not oxidizing.		
Explosive properties :	Not explosive according to EU A.14.		

9.2 Other information

None

SECTION 10: Stability and reactivity

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet HD EP FAD, Art.-no. 0438
Revision date : 11.09.2015
Print date : 06.07.2016

Version (Revision) : 3.0.0 (1.0.0)

10.1 Reactivity

No information available.

10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Oxidising agent, strong.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological data are not available. The statement is derived from the properties of the single components.

Acute effects

No data available to indicate product may be an acute toxic oral, dermal or inhalation hazard.

Acute oral toxicity

Parameter : LD50 (BASEOIL)
Exposure route : Oral
Species : Rat
Effective dose : > 5000 mg/kg

Acute dermal toxicity

Parameter : LD50 (BASEOIL)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 5000 mg/kg

Acute inhalation toxicity

Parameter : LC50 (BASEOIL)
Exposure route : Inhalation
Species : Rat
Effective dose : > 5,53 mg/l
Exposure time : 4 h

Irritant and corrosive effects

Irritating to eyes and skin.

Sensitisation

not sensitising.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

no known significant effects or critical hazards.

Germ cell mutagenicity

no known significant effects or critical hazards.

Reproductive toxicity

no known significant effects or critical hazards.

STOT-single exposure

STOT SE 1 and 2

Not expected to cause organ damage from a single exposure.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet HD EP FAD, Art.-no. 0438
Revision date : 11.09.2015
Print date : 06.07.2016

Version (Revision) : 3.0.0 (1.0.0)

STOT-repeated exposure

STOT RE 1 and 2

Not expected to cause organ damage from prolonged or repeated exposure.

Aspiration hazard

Based on the available data the classification criteria for aspiration toxicity are not met. For viscosity data, see section 9.

SECTION 12: Ecological information

12.1 Toxicity

For the product ecotoxicological data are not available. The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3).

Aquatic toxicity

Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Moderately/partially biodegradable.

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Waste code product

12 01 07*

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

(Waste key of the emulsion: 12 01 09*)

Waste name

Mineral-based machining oils free of halogens (except emulsions and solutions).

Waste treatment options

Appropriate disposal / Product

Consult the appropriate local waste disposal expert about waste disposal. Dispose according to legislation.

Appropriate disposal / Package

Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of.

Dispose of waste according to applicable legislation.

Other disposal recommendations

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet HD EP FAD, Art.-no. 0438
Revision date : 11.09.2015
Print date : 06.07.2016

Version (Revision) : 3.0.0 (1.0.0)

proper instructions. Do not pressurise, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : 5 - 10 %

Water hazard class (WGK)

Class : 2 (Hazardous to water) Classification according to VwVwS

Additional information

Berufsgenossenschaftliche Regeln (BGR)

The product corresponds with TRGS 611.

15.2 Chemical safety assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

02. Classification of the substance or mixture · 02. Label elements · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 02. Special rules for supplemental label elements for certain mixtures · 02. Labelling (67/548/EEC or 1999/45/EC) · 02. Labelling (67/548/EEC or 1999/45/EC) - Hazard components for labelling · 02. Special provisions concerning the labelling of certain mixtures · 03. Hazardous ingredients · 07. Hints on joint storage - Storage class · 08. Occupational exposure limit values · 15. Technische Anleitung Luft (TA-Luft)

16.2 Abbreviations and acronyms

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
GHS = Globally Harmonized System of Classification and Labelling of Chemicals

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : eni aquamet HD EP FAD, Art.-no. 0438
Revision date : 11.09.2015
Print date : 06.07.2016

Version (Revision) : 3.0.0 (1.0.0)

IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables
LC50 = Lethal Concentration fifty
LD50 = Lethal Dose fifty per cent.
LogPow = logarithm of the octanol/water partition coefficient
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
STEL = Short term exposure limit
SVHC = Substances of Very High Concern
TWA = Time weighted average
UVCB = Complex hydrocarbon substance
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

16.3 Key literature references and sources for data

Sources of information used in preparing this SDS included one or more of the following: Product Dossiers and SDS from suppliers, complemented by public sources, as appropriate (GESTIS, the EU IUCLID Data Base, U.S. NTP publications, e.g.).

16.4 Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H360FD	May damage fertility. May damage the unborn child.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

16.5 Training advice

Provide adequate information, instruction and training for operators.

16.6 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.