



Eni i-Ride Moto 15W-50

Eni i-Ride Moto 15W-50 is a high-performance multigrade oil of the newest technology and is applicable for air as well as water cooled 4-stroke engines, especially at severe conditions.

Characteristics (typical figures):

Eni i-Ride Moto 15W-50	Unit	15W-50	Test method
Kin. Viscosity	at -25°C	mm ² /s	6800
	at 40°C	mm ² /s	145
	at 100°C	mm ² /s	18,8
Viscosity index		147	DIN ISO 2909
Density at 15°C	kg/m ³	875	ASTM D 1298
Flashpoint o. C.	°C	205	ASTM D 92
Pourpoint	°C	-27	ASTM D 97

Properties and Performance:

- ⇒ **Eni i-Ride Moto 15W-50** has sufficient flowability at low temperatures and a high Viscosity in the upper temperature range. Therefore this lubricant can be used as all-year oil.
- ⇒ Its excellent detergent/dispersant properties minimize the liner lacquering and the formation of deposits in the engine. Therefore **Eni i-Ride Moto 15W-50** prevents the jamming of the piston rings and keeps possible deposits in suspense.
- ⇒ Its excellent wear protection properties ensure a long lifetime of all moving parts. Due to the high surface adhesion a low-wear engine start is ensured also after longer downtime.

Applications:

Eni i-Ride Moto 15W-50 is best suitable for very different and severe operation conditions, such as long-distance travel at high temperatures or stop-and-go travel at low temperatures.

Specifications:

Eni i-Ride Moto 15W-50 meets the following specifications and approvals:

API SL
Jaso MA, Jaso MA2