



eni Fresia ESB 25

Safety Data Sheet
According to Regulation (EC) No. 453/2010

Revision date: **01/07/2013**
Supersedes: **26/03/2012**

Version: **2.2**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : eni Fresia ESB 25
EC index no : N/A
EC no : N/A
CAS No : N/A
REACH registration No : N/A
Product code : 5213
Formula : 0040-2012
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Industrial use, Professional use
Industrial/Professional use spec : Wide dispersive use
Used in closed systems
Use of the substance/mixture : Metalworking fluid

Do not use the product for any purposes that have not been advised by the manufacturer. In that case, the user could be exposed to unpredictable risks.
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

ENI S.p.A.
P.le E. Mattei 1 - 00144 ROMA Italy
Tel (+39) 06 59821
www.eni.com

Contact:
Refining & Marketing Division
Via Laurentina 449 00142 ROMA Italy
Tel (+39) 06 59881 Fax (+39) 06 59885700

Competent person responsible for the Safety Data Sheet (Reg. EC nr. 1907/2006): qualt-t@eni.com

1.4. Emergency telephone number

Emergency number : CNIT +39 0382 24444 (24h) (IT + EN)

Poison centre (UK):
National Poisons Information Service Edinburgh (24h)
(+44) 844 892 0111
0870 600 6266 (UK only)
(Source: UN-WHO)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

Adverse physicochemical, human health and environmental effects

None to be reported, according to the present EU regulations.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

According to EU criteria, there are no labelling obligations for this product.

Other:

General advice : "Use suitable gloves when handling product. Dispose of used/leftover product and package properly. Protect the environment."

2.3. Other hazards (not relevant for classification)

Physical/chemical : This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.

Health : If the product is handled or used at high temperature, contact with hot product or vapours may cause burns.,Any material in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment.,Do not wait for symptoms to develop.

Environment : None.

Contaminants : None.

This substance/mixture does not meet the PBT criteria of REACH, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH, annex XIII.

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixture

Composition/information on ingredients : Synthetic base stock (ester)
White mineral oil (petroleum)
Additives

Hazardous ingredients and/or with
relevant occupational exposure limits : See table

Name	Product identifier	%	Classification according to Directive 67/548/EEC
Alkyl Phosphite, Alkanolamine ester, polymer (Additive)	(CAS No) N/D (EC no) Polymer (EC index no) N/A (REACH-no) N/A	4,99 - 9,99	Xi; R38
White mineral oil (petroleum) (Additive)	(CAS No) 8042-47-5 (EC no) 232-455-8 (EC index no) N/A (REACH-no) 01-2119487078-27	4,99 - 9,99	Not classified
Alkylated diphenylamines	(CAS No) N/A (EC no) N/A (EC index no) N/A (REACH-no) N/D	0,099 - 0,99	R53
Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di- trans-butyl-4-hydroxyphenyl)propionate (Additive)	(CAS No) 125643-61-0 (EC no) 406-040-9 (EC index no) 607-530-00-7 (REACH-no) N/D	0,3 - 0,49	R53
Diphenylamine	(CAS No) 122-39-4 (EC no) 204-539-4 (EC index no) 612-026-00-5	< 0,099	T; R23/24/25 R33 N; R50/53

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Alkyl Phosphite, Alkanolamine ester, polymer (Additive)	(CAS No) N/D (EC no) Polymer (EC index no) N/A (REACH-no) N/A	4,99 - 9,99	Skin Irrit. 2, H315
White mineral oil (petroleum) (Additive)	(CAS No) 8042-47-5 (EC no) 232-455-8 (EC index no) N/A (REACH-no) 01-2119487078-27	4,99 - 9,99	Asp. Tox. 1, H304
Alkylated diphenylamines	(CAS No) N/A (EC no) N/A (EC index no) N/A (REACH-no) N/D	0,099 - 0,99	Aquatic Chronic 3, H412

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate (Additive)	(CAS No) 125643-61-0 (EC no) 406-040-9 (EC index no) 607-530-00-7 (REACH-no) N/D	0,3 - 0,49	Aquatic Chronic 4, H413
Diphenylamine	(CAS No) 122-39-4 (EC no) 204-539-4 (EC index no) 612-026-00-5	< 0,099	Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of R-, H- and EUH-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : In case of spontaneous vomiting, transport the victim to a hospital, to verify the possibility that the product has been aspirated into the lungs.
- First-aid measures after inhalation : Inhalation is unlikely because of the low vapour pressure of the substance at ambient temperature. Exposure to vapours may however occur when the substance is handled at high temperatures with poor ventilation. In case of symptoms arising from inhalation of product fumes, mists or vapour : Remove casualty to a quiet and well ventilated place if safe to do so. If casualty is unconscious and not breathing: ensure that there is no obstruction to breathing and give artificial respiration by trained personnel. If necessary, give external cardiac massage and obtain medical advice. If the casualty is breathing: Place in the recovery position. Administer oxygen if necessary.
- First-aid measures after skin contact : Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If inflammation or irritation persists, seek medical advice. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor. Body hypothermia must be avoided. Do not put ice on the burn.
- First-aid measures after eye contact : Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation persists, seek medical advice. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor.
- First-aid measures after ingestion : Do not induce vomiting to avoid aspiration into the lungs. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms / injuries (general indications) : None.
- Symptoms/injuries after inhalation : This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only if the product is used at high temperature, or in case of sprays and mists. In these cases overexposure to vapours may cause irritation to airways, nausea and dizziness.

Symptoms/injuries after skin contact	: Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. Contact with hot product may cause thermal burns.
Symptoms/injuries after eye contact	: Contact with eyes may cause a light transient irritation. Contact with hot product or vapours may cause burns.
Symptoms/injuries after ingestion	: Accidental ingestion of small quantities of the product may cause nausea, discomfort and gastric disturbances. If any, nausea and diarrhoea might occur.
Symptoms/injuries upon intravenous administration	: No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Seek medical attention in all cases of serious burns.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Small-size fires: carbon dioxide, dry chemicals, alcohol-resistant foam, sand or earth. Large fires: alcohol-resistant foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations).
Unsuitable extinguishing media	: Do not use water jets. They could cause splattering, and spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.
Explosion hazard	: In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m ³ of air.
Combustion products	: Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, NO _x , Oxygenated compounds (aldehydes, etc.), PO _x .

5.3. Advice for firefighters

Firefighting instructions	: Stop or contain leak at the source, if safe to do so. If possible, move containers and drums away from danger area. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.
Special protective equipment for firefighters	: Personal protection equipment for firefighters (see also sect. 8). Self-contained breathing apparatus.
Other information	: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid direct contact with released material.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: See Section 8.
----------------------	------------------

Emergency procedures : Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

6.1.2. For emergency responders

Protective equipment : Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. If necessary heat resistant and insulated. Work gloves (preferably gauntlets) providing adequate chemical resistance. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: a half or full-face respirator with filter(s) for organic vapours (AX), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

Emergency procedures : Notify local authorities according to relevant regulations.

6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

6.3. Methods and material for containment and cleaning up

For containment : Soil. Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If it is necessary to store any contaminated materials for safe disposal, only suitable containers (airtight, labelled, sealed, waterproof, earthed and bonded) should be used. Water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.

Other information : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken.

6.4. Reference to other sections

For more information regarding protective equipment see section " Exposure control/personal protection".

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

- Precautions for safe handling : Ensure that all relevant regulations regarding handling and storage facilities of flammable products are followed. Do not use compressed air for filling, discharging, or handling operations. Keep away from heat/sparks/open flames/hot surfaces. Use and store only outdoors or in a well-ventilated area. During transfer and mixing operations, ensure that all equipment is correctly grounded. Avoid the build-up of electric charges. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned.
- Handling temperature : 0 - 65 °C
- Hygiene measures : Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in dry, well ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.
- Incompatible products : Keep away from: strong oxidants.
- Storage temperature : 0 - 55 °C
- Storage area : Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.
- Packages and containers: : Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.
- Packaging materials : For containers, or container linings use materials specifically approved for use with this product. Recommended materials for containers, or container linings use mild steel, stainless steel. Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Compatibility should be checked with the manufacturer.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Diphenylamine (122-39-4)		
Austria	MAK (mg/m ³)	< 5 mg/m ³
Austria	MAK (ppm)	0,7 ppm
Austria	MAK Short time value (mg/m ³)	10 mg/m ³
Austria	MAK Short time value (ppm)	1,4 ppm
Belgium	Limit value (mg/m ³)	10 mg/m ³
France	VLE (mg/m ³)	10 mg/m ³


Diphenylamine (122-39-4)		
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	5 mg/m ³ (Inhalable aerosol)
Germany	TRGS 900 Limitation of exposure peaks (mg/m ³)	10 mg/m ³ (Inhalable aerosol)
Italy - Portugal - USA ACGIH	ACGIH TLV®-TWA (mg/m ³)	10 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³
Spain	VLA-ED (mg/m ³)	10 mg/m ³
United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³
United Kingdom	WEL STEL (mg/m ³)	20 mg/m ³
Denmark	Grænseværdi (langvarig) (mg/m ³)	5 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	20 mg/m ³
Ireland	OEL (15 min ref) (mg/m ³)	10 mg/m ³
Sweden	Nivågränsvärde (NVG) (mg/m ³)	4 mg/m ³
Sweden	Kortidsvärde (KTV) (mg/m ³)	12 mg/m ³

White mineral oil (petroleum) (8042-47-5)		
Austria	MAK (mg/m ³)	5 mg/m ³ (Inhalable aerosol)
Belgium	Limit value (mg/m ³)	5 mg/m ³ (mineral oil mists)
Italy - Portugal - USA ACGIH	ACGIH TLV®-TWA (mg/m ³)	5 mg/m ³ (mineral oil mists)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³ (mineral oil mists)
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	10 mg/m ³ (mineral oil mists)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 (mineral oil mists)
Spain	VLA-ED (mg/m ³)	5 mg/m ³ (mineral oil mists)
Spain	VLA-EC (mg/m ³)	10 mg/m ³ (mineral oil mists)
The Netherlands	MAC TGG 8h (mg/m ³)	5 mg/m ³ (mineral oil mists)
United Kingdom	WEL TWA (mg/m ³)	5 mg/m ³ (mineral oil mists)
United Kingdom	WEL STEL (mg/m ³)	10 mg/m ³ (mineral oil mists)
Denmark	Grænseværdi (langvarig) (mg/m ³)	1 mg/m ³ (mineral oil mists)
Denmark	Grænseværdi (kortvarig) (mg/m ³)	2 mg/m ³ (mineral oil mists)
Hungary	AK-érték	5 mg/m ³ (mineral oil mists)
Sweden	Nivågränsvärde (NVG) (mg/m ³)	1 mg/m ³ (mineral oil mists)
Sweden	Kortidsvärde (KTV) (mg/m ³)	3 mg/m ³ (mineral oil mists)
Canada (Quebec)	VECD (mg/m ³)	5 mg/m ³ (mineral oil mists)
Canada (Quebec)	VEMP (mg/m ³)	10 mg/m ³ (mineral oil mists)

Monitoring methods

: Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts., Refer to relevant legislation and in any case to the good practice of industrial hygiene.

8.2. Exposure controls

Appropriate engineering controls	: Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability.
Personal protective equipment (for industrial or professional use)	: Face shield. Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust/aerosol mask.
	
Hand protection	: When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined. Materials that are presumably adequate: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard.
Eye protection	: When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.
Skin and body protection	: Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.
Respiratory protection	: Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: if the product is handled without adequate containment: use full or half-face masks with adequate filter for mists and organic vapours. (EN 136/140/145). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145). If exposure levels cannot be determined or estimated with adequate confidence, or an oxygen deficiency is possible, only SCBA's should be used.
Thermal hazard protection	: If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.
Environmental exposure controls	: Do not discharge the product into the environment. Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills.
Consumer exposure controls	: No special requirements necessary, if handled at room temperature.

8.3. Hygiene measures

General protective and hygienic measures	: Avoid contact with skin and eyes, Do not breathe vapours or mists., Do not clean hands with dirty or oil-soaked rags., Do not keep dirty rags in the overall pockets., Do not drink, eat or smoke with dirty hands., Wash hands with water and mild soap, do not use solvents or other irritant products which have a defatting effect on the skin., Do not re-use clothes, if they are still contaminated.
--	---

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	: Liquid
Appearance	: Liquid, bright & clear.
Molecular mass	: Not applicable for mixtures
Colour	: Yellow.
Odour	: odourless.
Odour threshold	: There are no data available on the preparation/mixture itself.
pH	: Not applicable.
Relative evaporation rate (butylacetate=1)	: Negligible.
Melting point	: Pour point ≤ -18 °C (ASTM D 97)
Freezing point	: No data available
Boiling point	: ≥ 200 °C (ASTM D 1160)
Flash point	: ≥ 130 °C (ASTM D 93)
Self ignition temperature	: ≥ 300 °C (DIN 51794)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: ≤ 1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: ≤ 901 kg/m ³ (15 °C) (ASTM D 4052)
Solubility	: Water: Immiscible and insoluble Ether: Partially soluble Acetone: Soluble
Log Pow	: Not applicable for mixtures
Log Kow	: No data available
Viscosity, kinematic	: 24 - 26,5 mm ² /s (40 °C) (ASTM D 445)
Viscosity, dynamic	: No data available
Explosive properties	: None.
Oxidising properties	: None.
Explosive limits	: LEL ≥ 45 g/m ³ (Aerosol)

9.2. Other information

VOC content : = 0 % (EU, CH)

The above data are typical values and do not constitute a specification.

SECTION 10: Stability and reactivity**10.1. Reactivity**

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

10.2. Chemical stability

Stable product, according to its intrinsic properties (in normal conditions of storage and handling).

10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard. A mixture with nitrates or other strong oxidisers (e.g. chlorates, perchlorates, liquid oxygen) may create an explosive mass. Sensitivity to heat, friction or shock cannot be assessed in advance.

10.4. Conditions to avoid

Keep away from strong oxidizers. Keep away from open flames, hot surfaces and sources of ignition. Avoid the build-up of electrostatic charge.

10.5. Incompatible materials

Strong oxidants.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)
(according to composition)

eni Fresia ESB 25 (N/A)	
LD50 oral rat	> 2000 mg/kg bodyweight (Calculated data).
LD50 dermal rat	> 2000 mg/kg bodyweight (Calculated data).
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (Calculated data).

Diphenylamine (122-39-4)	
ATE (oral)	100,000 mg/kg
ATE (dermal)	300,000 mg/kg
ATE (dust,mist)	0,500 mg/l/4h

Alkylated diphenylamines (N/A)	
LD50 oral rat	≥ 2000 mg/kg bodyweight (OECD 401)

White mineral oil (petroleum) (8042-47-5)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5 mg/l/4h

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) (according to composition) Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. pH: Not applicable.
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met) (according to composition) pH: Not applicable.
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met) (according to composition) This product does not contain any significant amounts of substances classified as sensitizers (in any case < 0.1 % wt)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met) (according to composition) This product does not contain any significant amounts of substances classified as mutagenic by the EU (in any case < 0.1 % wt)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met) (according to composition) None of the components of this product are listed as carcinogen by NTP, IARC, OSHA, EU or others.
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met) (according to composition) This product does not contain any significant amounts of substances classified as Toxic for Reproduction by the EU (in any case < 0.1 % wt)
Specific target organ toxicity (single exposure)	: Not classified (Based on available data, the classification criteria are not met) (according to composition)
Specific target organ toxicity (repeated exposure)	: Not classified (Based on available data, the classification criteria are not met) (according to composition)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met) (according to composition)
Potential Adverse human health effects and symptoms	: Contact with eyes may cause temporary reddening and irritation. Prolonged and repeated skin contact may cause reddening, irritation and dermatitis.
Other information	: None.

SECTION 12: Ecological information**12.1. Toxicity**

- Ecology - general : According to the components, and by comparison with other products of the same type and composition, it is expected that this product has a toxicity for aquatic organisms > 100 mg/l, and must not be regarded as dangerous to the environment. An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment.
- Ecology - air : This product has a low vapour pressure. A significant exposure may happen only if the product is used at high temperature, or in case of sprays and mists.
- Ecology - water : This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)

eni Fresia ESB 25 (N/A)	
LC50 fish 1	≥ 100 mg/l (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
LC50 other aquatic organisms 1	≥ 100 mg/l (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
EC50 Daphnia 1	≥ 100 mg/l (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.

Diphenylamine (122-39-4)	
LC50 fish 1	3,79 mg/l (96h; Pimephales promelas)
EC50 Daphnia 1	2,3 mg/l (24h)
LC50 fish 2	5,1 mg/l (48h; Oryzias latipes)
ErC50 (algae)	0,18 mg/l (72h)

Alkylated diphenylamines (N/A)	
LC50 fish 1	≥ 100 mg/l (OECD 203)
EC50 Daphnia 1	≥ 100 mg/l (OECD 202)
ErC50 (algae)	≥ 100 mg/l (OECD 201; 96h; Scenedesmus capricornutum)

Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
LC50 fish 1	> 74 mg/l (OECD 203, 96h, Brachydanio rerio)
EC50 Daphnia 1	> 100 mg/l (OECD 202, 24h)
ErC50 (algae)	≥ 3 mg/l (OECD 201, 72 h, Scenedesmus subspicatus)

White mineral oil (petroleum) (8042-47-5)	
LC50 fish 1	> 100 g/l
LC50 other aquatic organisms 1	> 100 g/l
EC50 Daphnia 1	> 100 g/l

12.2. Persistence and degradability**eni Fresia ESB 25 (N/A)**

Persistence and degradability

The product should be considered as "Not persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1). The most significant constituents of the product should be considered as "readily biodegradable".

Diphenylamine (122-39-4)

Biodegradation

26 % (28d)

Alkylated diphenylamines (N/A)

Persistence and degradability

Not biodegradable.

White mineral oil (petroleum) (8042-47-5)

Persistence and degradability

The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.

12.3. Bioaccumulative potential**eni Fresia ESB 25 (N/A)**

Log Pow

Not applicable for mixtures

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment**eni Fresia ESB 25 (N/A)**

This substance/mixture does not meet the PBT criteria of REACH, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH, annex XIII.

Results of PBT-vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered as "Not persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)

Alkyl Phosphite, Alkanolamine ester, polymer (N/D)

This substance/mixture does not meet the PBT criteria of REACH, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH, annex XIII.

White mineral oil (petroleum) (8042-47-5)

This substance/mixture does not meet the PBT criteria of REACH, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH, annex XIII.

12.6. Other adverse effects

Other adverse effects	: None.
Other information	: This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Do not dispose of the product, either new or used, by discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector.
Sewage disposal recommendations	: Dispose of in a safe manner in accordance with local/national regulations. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
Waste disposal recommendations	: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 06* (synthetic engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.
Additional information	: Empty containers may contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been cleaned, and declared safe.
Ecology - waste materials	: The product as it is does not contain halogenated substances.

SECTION 14: Transport information

In accordance with ADR / RID / ADN / IMDG / ICAO / IATA

14.1. UN number

No dangerous good in sense of transport regulations

14.2. UN proper shipping name

Proper Shipping Name : Not applicable

14.3. Transport hazard class(es)

Subsidiary risk (IMDG) : --
Subsidiary risk (IATA) : --

14.4. Packing group

Packing group (UN) : --

14.5. Environmental hazards

Other information : None.

14.6. Special precautions for user

Special transport precautions : None.

14.6.1. Overland transport

State during transport (ADR-RID) : Liquid
Classification code : --
Limited quantities (ADR) :

14.6.2. Transport by sea

Port Regulation Law	: Not applicable.
Limited quantities (IMDG)	: Not applicable
EmS-No. (1)	: --
MFAG-No	: --

14.6.3. Air transport

Instruction "cargo" (ICAO)	: Not applicable
Instruction "passenger" (ICAO)	: Not applicable
Instruction "passenger" - Limited quantities (ICAO)	: Not applicable

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IBC code	: None.
----------	---------

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

Relevant EU Legislation	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace) Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding) Directives 96/82/CE and 2003/105/CE (Control of major-accident hazards involving dangerous substances) Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds) Labelling according to directives 67/548/EEC and 1999/45/EC
-------------------------	--

VOC content : = 0 % (EU, CH)

EURAL code (EWC) : 13 02 06*

15.1.2. National regulations

Maladies professionnelles (F)	: RG 36 - Affections provoquées par les huiles et graisses d'origine minérale ou de synthèse
Water hazard class (WGK) (D)	: 1 (according to composition)
WGK remark	: Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS)
Storage class (LGK) (D)	: LGK 12 - Non-flammable liquids in non-flammable packages

VbF class (D)	: Not applicable.
Regional legislation	: National adoption of EU Directives concerning health and safety on the workplace. National laws on classification and labeling of dangerous substances/preparations (Adoption of Directive 67/548/CE and subsequent Adaptations to Technical Progress - ATP, and Directive 1999/45/CE). National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (96/82/CE - 2003/105/CE). Relevant national laws on prevention of water pollution. Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC). National adoption of Directives 75/439/CEE - 87/101/CEE concerning disposal of used oils.

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out

White mineral oil (petroleum)

SECTION 16: Other information

Indication of changes	: Formula. Viscosity, kinematic. Density. Flash point. Name.
Data sources	: This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers. Complete text of the phrases H and R quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.
Abbreviations and acronyms	: Complete text of the phrases H and R quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.
Training advice	: Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.
Other information	: Do not use the product for any purposes that have not been advised by the manufacturer. In that case, the user could be exposed to unpredictable risks.

Full text of R-, H- and EUH-phrases::

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Acute 1	Hazardous to the aquatic environment — AcuteHazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H331	Toxic if inhaled
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

H412	Harmful to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed
R33	Danger of cumulative effects
R38	Irritating to skin
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R53	May cause long-term adverse effects in the aquatic environment
N	Dangerous for the environment
T	Toxic
Xi	Irritant

SDS EU (Annex II) GENERAL

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product