



eni i-Base 15W-40

eni i-Base 15W-40 is a mineral engine oil suitable for gasoline and diesel engines that equip passenger cars or light vans operating under the severest conditions involving, for example: motorway driving or taxi service in urban traffic (stop-go service).

Characteristics (typical figures):

eni i-Base 15W-40		Unit	15W-40	Test method
Kin. Viscosity	at -20°C	cP	6800	
	at 40°C	mm ² /s	109	DIN 51561
	at 100°C	mm ² /s	14,5	ASTM D 445
Viscosity index			130	DIN ISO 2909
Density at 15°C		kg/m ³	880	ASTM D 1298
Flashpoint o. C.		°C	210	ASTM D 92
Pourpoint		°C	-24	ASTM D 97

Properties and Performance:

- **eni i-Base 15W-40** has an extremely high Viscosity Index which keeps it free-flowing when cold and maintains high viscosity when hot.
- Its superior detergent and dispersant properties effectively inhibit the formation of lacquer, varnish, sludge and other deposits, maintaining in a good condition the engine components.
- Its anti-wear properties ensure long life for all moving parts, substantially reducing the need for engine servicing and overhauls.

International specifications:

- ACEA A3/B4-10
- API SM/CF

Approvals:

- MB approval 229.1
- VW 501 01, 505 00 quality