



eni i-Ride PG 5W-40

eni i-Ride PG 5W-40 is a 4-stroke engine oil with the top synthetic technology of eni. It had been especially developed for the application in 4-stroke high-performance engines and can also be used for motor racing.

Characteristics (typical figures):

eni i-Ride PG 5W-40	Unit	5W-40	Test method
Kin. Viscosity	at -15°C	6300	
	at 40°C	96	DIN 51561
	at 100°C	14,7	ASTM D 445
Viscosity index		158	DIN ISO 2909
Density at 15°C	kg/m ³	851	ASTM D 1298
Flashpoint o. C.	°C	225	ASTM D 92
Pourpoint	°C	-40	ASTM D 97

Properties and Performance:

- ⇒ Excellent shear stability is a guarantee for the Viscosity stability (stay-in-grade), also after longer application under extreme conditions.
- ⇒ The thermal stable base oil has an extreme low evaporation tendency and leads to a low oil consumption.
- ⇒ The special formulation of the eni Research & Development laboratories ensure highest performance concerning the detergent/dispersant properties, corrosion protection, foam prevention, oxidation stability and wear protection properties.

Applications:

eni i-Ride PG 5W-40 is recommended where high engine performance and a safe lubrication film are required.

Specification:

eni i-Ride PG 5W-40 meets the following specification and approvals:

ACEA A3
API SL
Jaso MA
Jaso MA2
Piaggio-Group