

Engine oils

AUTOL SM 1:50

API TC
TSC 3

Self-mixing

High-performance engine oil for all 2-stroke engines with mixed or separate lubrication.

Characteristics (typical figures):

| | | | |
|-------------------|----------|--------------------|------|
| Viscosity | at 40°C | mm ² /s | 65,9 |
| | at 100°C | mm ² /s | 9,3 |
| Viscosity index | | | 121 |
| Density at 15°C | | kg/m ³ | 871 |
| Flash point o. C. | | °C | 150 |
| Pourpoint | | °C | -39 |

AUTOL SM 1:50 is a modern self-mixing 2-stroke engine oil with synthetic components that is suitable for all mixing ratios specified by the manufacturer.

Carefully selected base oils as well as efficient additives prevent the formation of deposits and gum. The good wear and corrosion protection properties ensure a high operational dependability under all conditions and protect the engine's piston rings from jamming.

Applications:

AUTOL SM 1:50 is suitable for the application in all modern 2-stroke engines with mixed or separate lubrication. Next to the application in motorbikes this product can also be used for all 2-stroke engines in constructional, agricultural, forestry and hobby equipment.

The mixing ratios prescribed by the engine manufacturers have to be met under observation of the table below.

| Mixing ratio | 1:25 | 1:33 | 1:40 | 1:50 | 1:100 |
|--|------|------|------|------|-------|
| Litres of gasoline to 1 litre AUTOL SM 1:50 | 23 | 30 | 36 | 45 | 90 |

Please observe the manufacturer's specifications when selecting products!